

Wire Cable Stockings



Application:	Ideally suited to heavy industrial, mining, quarries or construction industries where the transfer of media is under high working pressures.
Features:	These strong steel cable stockings prevent hose whip in case of a burst hose or accidental separation of the coupling or clamp device.
Construction:	<ul style="list-style-type: none"> • 2070 galvanised wire construction • Alloy ferrules • Heavy duty galvanised thimbles • Heat shrink safety protection
Other:	<p>Also available with stainless steel wire, copper ferrules and stainless steel thimbles.</p> <p>Other Configurations:</p> <ul style="list-style-type: none"> • Single offset eye • 4 eye (double eye double end)

Manufactured to Suit OD & Application.

Part No.	Suit Hose OD (mm)	Wire Dia (mm)	Sets x Plys (mm)	Eye Length (mm)	Net Grip Length (mm)	Aggregate Breaking Strength All Strands		Ultimate Tensile Strength (kN)
						kg	kN	
CS30-40	28-40	1.5	6x2	200	600	5800	57	24
CS40-50	40-50	1.5	6x2	230	800	5800	57	35
CS50-60	50-60	2	6x2	290	800	10000	100	62
CS60-70	60-70	2	6x2	290	900	10000	100	62
CS70-85	70-85	2	6x2	290	1000	10000	100	62
CS85-100	85-100	2.5	6x2	390	1000	16000	158	98
CS100-120	100-120	2.5	6x2	400	1200	16000	158	133
CS120-150	120-150	2.5	8x2	420	1400	21500	211	187
CS150-190	150-190	3	8x2	450	1600	31000	305	283