

Acid, chemical & multipurpose

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	31	1,22	16	240	188	7,50	90	0,670	0,455
25	1	37	1,46	16	240	225	9,00	90	0,820	0,555
32	1 1/4	44	1,73	16	240	263	10,25	90	0,980	0,660
38	1 1/2	50	1,97	16	240	338	13,25	90	1,130	0,760
51	2	63	2,48	16	240	413	16,25	90	1,480	0,995
63	2 1/2	77	3,03	16	240	450	17,50	90	2,270	1,530
76	3	92	3,62	16	240	525	20,75	80	2,720	1,830
102	4	118	4,65	16	240	675	26,50	80	3,710	2,495

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



5050G

Acid-chemical S&D 16 bar (240 psi) - XLPE

Tube: Transparent XLPE (Cross Linked Polyethylene)

Reinforcement: High tensile textile cords with embedded steel helix wire

Cover: Green EPDM - abrasion and ozone resistant

Use: Acid and chemical suction and delivery.

Suitable for 90% of existing chemicals

Safety factor: 3:1

Temperature: -30 °C +80 °C (-22 °F +176 °F)