

↔		↔		ⓘ	⤴		⌒	⌒	⬛				
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft			
13	1/2	23	0,98	18	270	130	5,00		0,420	0,285			
16	5/8	26	1,02	18	270	160	6,50		0,460	0,309			
19	3/4	31	1,26	18	270	190	7,50		0,770	0,520			
25	1	38	1,50	18	270	250	10,00		0,900	0,605			
32	1 1/4	46	1,81	18	270	320	12,50		1,270	0,855			
38	1 1/2	52	2,05	18	270	380	15,00		1,370	0,925			
51	2	67	2,64	18	270	510	20,00		2,050	1,380			
63	2 1/2	81	3,19	18	270	630	25,00		2,960	1,986			
76	3	94	3,70	18	270	760	30,00		3,720	2,496			
NA		LA		NEU		EMEA		SA		AP		AU	



EXTRUDED
TUBE

340AH
Steam 18 bar (270 psi)
steel braided

Tube: Black conductive EPDM
Reinforcement: High tensile steel wire braids
Cover: Red EPDM - heat, abrasion and ozone resistant - pin pricked
Use: Saturated and superheated steam
Safety factor: 10:1
Temperature: -40 °C +210 °C (-40 °F +410 °F)
 intermittent to 232 °C (450 °F)