

↔		↔		⌚		⤴		⚖		
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
10	3/8	16	0,63	15	225	40	1,50	90	0,170	0,115
13	1/2	19	0,75	7	100	52	2,00	85	0,205	0,138
14	9/16	20	0,79	6	90	56	2,25	85	0,220	0,150
16	5/8	22	0,87	6	90	64	2,50	85	0,250	0,170
18	23/32	26	1,02	6	90	72	2,75	85	0,320	0,215
20	13/16	28	1,10	5	75	80	3,00	85	0,340	0,230
22	7/8	30	1,18	5	75	88	3,50	85	0,380	0,255
25	1	33	1,30	5	75	100	4,00	85	0,530	0,360
30	1 3/16	38	1,50	4	60	120	4,75	85	0,620	0,420
32	1 1/4	40	1,57	4	60	128	5,00	85	0,655	0,440
35	1 3/8	45	1,77	4	60	140	5,50	85	0,800	0,540
38	1 1/2	48	1,89	4	60	152	6,00	85	0,855	0,570
40	1 9/16	50	1,97	3	45	160	6,25	85	0,895	0,605
45	1 3/4	55	2,17	3	45	180	7,00	80	1,100	0,740
51	2	61	2,40	3	45	204	8,00	80	1,230	0,830
60	2 3/8	72	2,83	2	30	240	9,50	80	1,700	1,140
63	2 1/2	75	2,95	2	30	252	10,00	80	1,775	1,190
70	2 3/4	84	3,31	2	30	280	11,00	80	2,030	1,365
76	3	90	3,54	2	30	304	12,00	70	2,450	1,650
80	3 1/8	94	3,70	2	30	320	12,50	70	2,565	1,720
90	3 1/2	104	4,09	2	30	360	14,00	70	3,000	2,020
102	4	116	4,57	2	30	408	16,00	70	3,480	2,340
105	4 1/8	121	4,76	3	45	420	16,50	90	4,250	2,860
152	6	172	6,77	2	30	608	24,00	70	7,300	4,910
NA	LA	NEU	EMEA	SA	AP	AU				



47200

**General purpose food quality S&D - PVC
FDA - EU 10/2011 A+B+C - AS 2070**

Construction: Transparent PVC - abrasion and ozone resistant
Reinforcement: Steel helix wire

Use: General purpose liquid food and alcoholic beverages suction and delivery - max 20% - Sterilize with 5% soda solution

Safety factor: 3:1

Temperature: -5 °C +60 °C (+23 °F +140 °F)