

Impact Wrenches

Capacity M30–M36



W2220/ W2226C



W2227



W2225C



W2228

| Model | Bolt size mm | Square drive in | Max torque fwd Nm | Recommended torque range Nm | Free speed r/min | Weight kg | Length mm | Air consumption l/s | Rec. Hose size mm | Air inlet thread in | Ordering No. |
|--------|--------------|-----------------|-------------------|-----------------------------|------------------|-----------|-----------|---------------------|-------------------|---------------------|--------------|
| W2220 | M30 | 3/4 | 1,300 | 670–1,200 | 3,800 | 6.3 | 270 | 18 | 13 | 1/2 | 8434 1244 39 |
| W2226C | M36 | 1 | 1,800 | 670–1,200 | 6,800 | 9.6 | 276 | 18 | 13 | 1/2 | 8434 1244 53 |
| W2227 | M30 | 1 | 1,300 | 670–1,200 | 5,000 | 6.8 | 355 | 18 | 13 | 1/2 | 8434 1244 58 |
| W2225C | M26 | 1 | 2,710 | 810–1,500 | 4,000 | 10.1 | 300 | 26 | 13 | 1/2 | 8434 1244 54 |
| W2228 | M36 | 1 | 2,710 | 810–1,500 | 4,000 | 11.6 | 410 | 36 | 13 | 1/2 | 8434 1244 62 |