

Impact Wrenches

Compact line



W2810/W2811



W2815



W2820/ W2820LA

Model	Bolt size mm	Square drive in	Max torque fwd Nm	Recommended torque range Nm	Free speed r/min	Weight kg	Length mm	Air consumption l/s	Rec. Hose size mm	Air inlet thread in	Ordering No.
W2810	M14	3/8	470	200–360	10,000	1.3	160	10	10	1/4	8434 1248 10
W2811	M14	1/2	470	200–360	10,000	1.3	160	10	10	1/4	8434 1248 11
W2815	M16	1/2	1,085	300–680	7,400	2.0	191	16	10	1/4	8434 1248 15
W2815 Pin retainer	M16	1/2	1,085	300–680	7,400	2.0	191	16	10	1/4	8434 1248 16
W2820	M22	3/4	1,490	350–920	4,500	3.8	240	20	13	3/8	8434 1248 20
W2820LA	M22	3/4	1,490	350–920	4,500	3.8	240	20	13	3/8	8434 1248 21

Power socket kits



PRO WS1001



PRO WS1002



PRO WS1003

Model	Square drive in	Socket type	Number of sockets	Sockets included	Ordering No.
PRO WS1001	3/8	Metric impact socket	13	7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm	4112 0607 91
PRO WS1002	1/2	Metric impact socket	14	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26, 27 mm	4112 0607 92
PRO WS1003	1/2	Metric deep impact socket	14	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26, 27 mm	4112 0607 93