

**Nylon King Cable™**

**NEW**

Pneumatic Fittings

**Applications:**

- pneumatic, hydraulic and water hoses

**Features:**

- strong, flexible nylon webbing
- superior corrosion and spark resistance over metal restraints
- rubber grommets securely choke eyes around hose
- must be installed in the extended position (no slack)
- shipped with labels detailing working pressures and safety instructions
- maximum working temperature: **200°F (93°C)**
- minimizes damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly
- contact Dixon at 888.226.4673 for additional options

**Materials:**

- strap: nylon
- grommets: rubber



Length	Recommended for use on the following hose inside diameters:								Part #
	¼"	½"	¾"	1"	2"	3"	4"	6"	
30"	26,000	6,500	2,900	1,650	400	---	---	-	<i>WBN130</i>
40"	---	---	---	1,650	400	175	100	-	<i>WBN140</i>
30"	52,000	13,000	5,800	3,300	750	---	---	-	<i>WBN230</i>
64"	---	---	---	---	750	350	200	90	<i>WBN264</i>
44"	---	---	---	7,300	1,800	820	450	-	<i>WBN344</i>
64"	---	---	---	---	2,300	1,040	580	260	<i>WBN464</i>