

LC 122

Wide Band Micro biocide For Cooling Towers

LC 122 is an effective wide band micro-biocide designed for use in algae and bacteria control. It does not cause foaming and is not lost by evaporation from the system. It is a concentrated blend of organo-sulfur compounds, which should be added only after proper dilution by slug feeding.

Application

Use to control algae and bacteria in re-circulating commercial and industrial water cooling towers. Prior to its use, systems be cleaned to remove algae growth, microbiological slime and other deposits.

Dosage

Initial slug additions of LC 122 per 1,000 gallons of water should be employed every 1 - 5 days or as needed. The frequency of addition depends upon the relative amount of bleed-off and the severity of the microbiological problem. Slug additions should be made in the sump of the cooling tower. During very hot weather, greater frequency or higher dosage may be required to increase its effectiveness.

Handling & Precaution

It is a very strong alkaline treatment and may cause eye damage and skin irritation. Do not get in eyes, skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food. Harmful or fatal if swallowed. In case of skin contact wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amount of clean cool water for at least 15 minutes. If swallowed, call physician. Do not induce vomiting or give anything by mouth to an unconscious person.

Packaging

Available in pail of 20 Lt.. Can also be custom packaged.

Manufactured by :
PT. KIMBRATAS
Jakarta – INDONESIA
Phone : 062-21-5978020
Website : www.lifechem.co.id

Revision Date :
01/12/11

Revision No.
1

LifeChem

For
Quality,
Services
&
Brand Value