

TYPE/MODEL**SPESIFIKASI****MULTI LED 20 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 20 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 2.600 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 100WP - 12 Volt Polycrystalline
BATTERAY	: 80 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 400mm Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 5 Meter - 6 Meter, Galvanize Oktagonal Single Arm

TYPE/MODEL**SPESIFIKASI****MULTI LED 30 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 30 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 3.900 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 140WP - 12 Volt Polycrystalline
BATTERAY	: 100 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 400mm Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 6 Meter, Galvanize Oktagonal Single Arm

TYPE/MODEL**SPESIFIKASI****MULTI LED 40 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 40 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 5.200 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 2 x 80WP - 12 Volt Polycrystalline
BATTERAY	: 120 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 400mm Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 7 Meter, Galvanize Oktagonal Single Arm

TYPE/MODEL**SPESIFIKASI****MULTI LED 50 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 50 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 6.500 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 2 x 100WP - 12 Volt Polycrystalline
BATTERAY	: 2 x 80 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 700mm Double Batt. Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 7 Meter, Galvanize Oktagonal Single Arm

TYPE/MODEL**SPESIFIKASI****MULTI LED 60 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 60 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 7.800 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 2x100WP - 12 Volt Polycrystalline
BATTERAY	: 2x100 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 700mm Double Batt. Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 7 Meter - 8 Meter, Galvanize Oktagonal Single Arm

TYPE/MODEL**SPESIFIKASI****MULTI LED 80 WATT**

LIGHT SOURCE TYPE	: Integrated Optical Source
LENS	: High Transmittance Multi LED
WATT CURRENT / RATE VOLTAGE	: 80 Watt 12/24 Volt
CHIP LED	: Epistar
LUMENS	: 10.400 Lm
THE WEIGHT of LAMP	: 4.200 Gram
COLOUR TEMPERATURE	: 6.500 K / 4.500 K
DERAJAT PENYEBARAN CAHAYA	: 120° / 140°x 65°
WORKING LIFE TIME	: >50.000 Hr
BODY MATERIAL	: Die Cast Alumunium
SOLAR MODUL	: 300WP - 12 Volt Polycrystalline
BATTERAY	: 2x120 Ah MF-VRLA
BCU CONTROLLER	: 20 Amp - 12/24 Volt Smart PWM Auto Timer
BOX PANEL OUTDOOR	: 400 x 250 x 700mm Double Batt. Finish Powdercoating
KABEL MODUL (NYYHY)	: 2 x 4mm
KABEL LAMPU (NYYHY)	: 2 x 1,5mm
KABEL BATTERAY (NYYHY)	: 2 x (1 x 4mm)
STANDAR KETINGGIAN TIANG	: 8 Meter - 9 Meter, Galvanize Oktagonal Single Arm