

液压四轮装载机



AKS-OT1.8M

HYDRAULIC WHEEL LOADER W/ JOYSTICK CONTROL SYSTEM
(ENGINE HUA FENG POWER) MADE IN CHINA 中國制造

SPECIFICATION	AKS-OT1.8M
RATED LOAD	1800 kg
BUCKET CAPACITY	0.6 m ³
BUCKET DIMENSION	1760 x 440 x 760 mm
DUMPING HEIGHT	3650 mm
DISCHARGING DISTANCE	1100 mm
MIN TURNING RADIUS	5900 mm
LIFTING, LOWERING & DUMPING TIME	8.4 s
WHEEL BASE	2660 mm
DIA. PISTON ROD SWING ARM	45 mm
DIA. PISTON ROD BOOM ARM	45 mm

BOOM ARM PLATE THICKNESS	23 mm
STEERING TYPE	Hydraulic Steering
TIRE MODEL	16/70-20
WEIGHT (Menurut TIMBANG AKS)	3798 kg
OVERALL DIMENSION	5500 x 1850 x 2700 mm
ENGINE MODEL (HUA FENG POWER)	ZHBG41
RATED POWER	47 kw / 2300 Rpm
MAX. TORQUE / SPEED	145 kw / 1400 Rpm
NO. OF CYLINDER & BORE SIZE	4 Stroke 102 x 115 mm
DISPLACEMENT	3.76 L

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com



液压四轮装载机



AKS-OT1.8TG

HYDRAULIC WHEEL LOADER W/ GRASS GRAPPLE AND JOYSTICK CONTROL SYSTEM
(ENGINE HUA FENG POWER) MADE IN CHINA 中國制造

SPECIFICATION	TYPE	AKS-OT1.8TG
RATED LOAD		1800 kg
OPERATING WEIGHT		3680 Kg
WHEEL BASE		2130 mm
DUMPING HEIGHT		3800 mm
DUMPING REACH		1270 mm
MAX. TRAVELING SPEED		28 km/h
TIRE MODEL		16 / 70 -20
BREAKOUT FORCE		30 KN
HYDRAULIC SYSTEM PRESSURE		16 Mpa

HYDRAULIC CYCLE TIMES	<9 s
BOOM ARM PLATE THICKNESS	30 mm
MIN. TURNING RADIUS	4650 mm
OVERALL DIMENSION	6000 x 2000 x 2800 mm
WEIGHT	4515 Kg
ENGINE MODEL (HUA FENG POWER)	ZHBG41
RATED POWER	47 kw / 2400 Rpm
MAX. TORQUE / SPEED	145 kw / 1400 Rpm
NO. OF CYLINDER & BORE SIZE	4 Stroke 102 x 115 mm
DISPLACEMENT	3.76 L

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

液压四轮装载机

AKS-HK1.8TE45 HYDRAULIC WHEEL LOADER W/ JOYSTICK CONTROL SYSTEM (ENGINE HUAFENG POWER) MADE IN CHINA 中國制造



SPECIFICATION	AKS-HK1.8TE45
RATED LOAD	1800 kg
BUCKET CAPACITY	0.65 m ³
BUCKET DIMENSION	1960 x 470 x 800 mm
BUCKET PLAT THICKNESS	4 mm
DUMPING HEIGHT	5000 mm
DIA. PISTON ROD SWING ARM	60 mm
DIA. PISTON ROD BOOM ARM	50 mm

SPECIFICATION	AKS-HK1.8TE45
BOOM ARM PLATE THICKNESS	30 mm
STEERING TYPE	Hydraulic Steering
TIRE MODEL	16 / 70-20
WEIGHT (Menurut KATALOG PABRIK)	4400 kg
OVERALL DIMENSION	5500 x 1970 x 2980 mm
ENGINE MODEL (HUA FENG POWER)	ZHBG41
RATED POWER	47 kw / 2400 Rpm

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

液壓四輪裝載機

AKS-TO2T

HYDRAULIC WHEEL LOADER
W/ JOYSTICK CONTROL SYSTEM
(ENGINE HUA FENG POWER)
MADE IN CHINA 中國製造



SPECIFICATION	AKS-TO2T
RATED LOAD	2000 kg
BUCKET CAPACITY	0.8 m ³
BUCKET DIMENSION	1960 x 500 x 800 mm
BUCKET PLATE THICKNESS	4 mm
DUMPING HEIGHT	3800 mm
DISCHARGING DISTANCE	1320 mm
MIN TURNING RADIUS	4600 mm
LIFTING, LOWERING & DUMPING TIME	8.5 s
WHEEL BASE	2400 mm
DIA. PISTON ROD SWING ARM	50 mm
DIA. PISTON ROD BOOM ARM	45 mm
BOOM ARM PLATE THICKNESS	30 mm

STEERING TYPE	Hydraulic Steering
TIRE MODEL	16 / 70-20
WEIGHT (Menurut TIMBANG AKS)	4230 kg
OVERALL DIMENSION	5800 x 1950 x 2970 mm
ENGINE MODEL (HUA FENG POWER)	ZHBZG1 Turbo-charge
RATED POWER	65 kw / 2400 Rpm
MAX. TORQUE / SPEED	300 kw / 1600 Rpm
NO. OF CYLINDER & BORE SIZE	4 Stroke 102 x 115 mm
DISPLACEMENT	3.76 L

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

液壓四輪裝載機

**DUMPING
HEIGHT :
5000 mm**



AKS-OT2T45

**HYDRAULIC WHEEL LOADER W/ JOYSTICK CONTROL SYSTEM
(ENGINE HUA FENG POWER) MADE IN CHINA 中國制造**

SPECIFICATION	TYPE	AKS-OT2T45
RATED LOAD		2000 kg
BUCKET CAPACITY		0.85 m ³
BUCKET DIMENSION		2060 x 450 x 800 mm
MAX. BREAKOUT FORCE		kn
DUMPING HEIGHT		5000 mm
DUMPING DISTANCE		980 mm
DIA. PISTON ROD SWING ARM		50 mm
DIA. PISTON ROD BOOM ARM		50 mm

BOOM ARM PLATE THICKNESS	25 mm
WHEEL BASE	2300 mm
TIRE MODEL	16 / 70-20
STEERING TYPE	Hydraulic Steering
WEIGHT (Menurut TIMBANG AKS)	4743 kg
OVERALL DIMENSION	7000 x 2200 x 2950 mm
ENGINE MODEL (HUA FENG POWER)	ZHBZG1 Turbo-charge
RATED POWER	65 kw / 2400 Rpm
MAX. TORQUE / SPEED	---

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

全液压四轮装载机
含先导操纵



AKS-OT3T

HYDRAULIC WHEEL LOADER W/ JOYSTICK CONTROL SYSTEM
(ENGINE CUMMINS) MADE IN CHINA 中國制造

SPECIFICATION	TYPE	AKS-OT3T
RATED LOAD		3000 kg
BUCKET CAPACITY		1.8 m ³
BUCKET DIMENSION		2400 x 730 x 105 mm
DUMPING HEIGHT		3820 mm
DISCHARGING DISTANCE		900 mm
DIA. PISTON ROD SWING ARM		70 mm
DIA. PISTON ROD BOOM ARM		55 mm

LIFTING, LOWERING & DUMPING TIME	—
WHEEL BASE	2700 mm
TIRE MODEL	17.5-25
STEERING TYPE	Hydraulic Steering
ENGINE (CUMMINS)	6BT5.9-C125 Turbo-charge
RATED POWER	92 kw / 2400 Rpm
OVERALL DIMENSION	7000 x 2500 x 3200 mm
WEIGHT (Menurut TIMBANG AKS)	7800 kg

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com



全液压四轮装载机（夹木叉）
含先导操纵



AKS-WS3TL

HYDRAULIC WHEEL LOADER W/ LOG GRAPPLE & JOYSTICK CONTROL SYSTEM
(ENGINE CUMMINS) MADE IN CHINA 中國製造

SPECIFICATION	AKS-WS3TL
BUCKET CAPACITY	1.8 m ³
RATED LOAD	3200 kg
WEIGHT ★	10000 kg
DUMPING HEIGHT	4600 mm
DUMPING REACH	2600 mm
BREAKOUT FORCE	97 kn
TRACTION FORCE	100 kn
WHEEL BASE	2750 mm
TOTAL HYDRAULIC CYCLE TIME	10.3 s
FULL BUCKET LIFTING TIME	5.6 s
MIN. TURNING RADIUS	3576 mm
OVERALL DIMENSION	6970 x 2300 x 3286 mm

ENGINE	DIA. PISTON ROD BOOM ARM / SWING ARM	70 mm / 80 mm
	ENGINE	DONGFENG CUMMINS
	MODEL / POWER	6BT5.9-C130, 97 kw
	RATED SPEED	2200 Rpm
TRANSMISSION SYSTEM	MAX. TORQUE	460 - 560 N.m
	POWERED SPEED I & II	10.8 km/h & 32.5 km/h
	REVERSE SPEED	14.5 km/h
	AXLE TYPE	4-Wheel Drive
HYDRAULIC SYSTEM	TIRE SIZE	17.5-22-12 PR
	WORKING PRESSURE	JHP3100 = 16 Mpa
	STEERING SYS PRESSURE	CBY2050 = 10 Mpa
	LIFTING CYLINDER BORE	DF32 Ø125 x 816 mm
	LIFTING CYLINDER BORE	DF32 Ø140 x 553 mm

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com



全液压四轮装载机
含先导操纵



DISKON
SPESIAL
持價

AKS-LM5T

HYDRAULIC WHEEL LOADER
W/ JOYSTICK CONTROL SYSTEM
(ENGINE CUMMINS)
MADE IN CHINA 中國制造

SPECIFICATION	AKS-LM5T
BUCKET CAPACITY	3.0 m ³
RATED LOAD	5000 kg
DUMPING HEIGHT	3050 mm
DUMPING DISTANCE	1148 mm
BREAKOUT FORCE	160 kn
WHEEL BASE	3200 mm
TOTAL HYDRAULIC CYCLE TIME	11.48 s
STEERING TYPE	Hydraulic Steering
DIA. PISTON ROD SWING ARM	110 mm
DIA. PISTON ROD BOOM ARM	90 mm
OVERALL DIMENSION	7720 x 3030 x 3378 mm
WEIGHT ★	16700 kg

ENGINE	ENGINE	DONGFENG CUMMINS Turbo-charge
	MODEL	6CTAA8.3-C215
	POWER	160 kw
TRANSMISSION SYSTEM	RATED SPEED	2200 Rpm
	POWERED SPEED I & II	1100 Rpm
	REVERSE SPEED	8.3 L
HYDRAULIC SYSTEM	AXLE TYPE	38 km/h
	TIRE SIZE	Four-Wheel Drive
	WORKING PRESSURE	23.5" - 25" 16 PR
HYDRAULIC SYSTEM	STEERING SYS PRESSURE	12 Mpa
	LIFTING CYLINDER BORE	DF32 Ø165 x 757 mm
	LIFTING CYLINDER BORE	DF32 Ø200 x 540 mm

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com



全液压四轮装载机
含先导操纵

DISKON
SPECIAL
持價

AKS-LM6T
HYDRAULIC WHEEL LOADER
W/ JOYSTICK CONTROL SYSTEM
(ENGINE CUMMINS)
MADE IN CHINA 中國制造

SPECIFICATION	AKS-LM6T
BUCKET CAPACITY	3.2 m ³
RATED LOAD	6000 kg
WEIGHT ★	19000 kg
DUMPING HEIGHT	3160 mm
DUMPING REACH	1200 mm
BREAKOUT FORCE	200 kn
WHEEL BASE	3260 mm
TOTAL HYDRAULIC CYCLE TIME	11.48 s
FULL BUCKET LIFTING TIME	5.7 s
DIA. PISTON ROD SWING ARM	110 mm
DIA. PISTON ROD BOOM ARM	90 mm
OVERALL DIMENSION	8360 x 2950 x 3600 mm

ENGINE	ENGINE	DONGFENG CUMMINS Turbo-charge
	MODEL	6CTAB3-C240
	POWER	179 kw
	RATED SPEED	2200 Rpm
TRANSMISSION SYSTEM	POWERED SPEED I & II	1000 Rpm
	REVERSE SPEED	8.3 L
	AXLE TYPE	38 km/h
	TIRE SIZE	Four-Wheel Drive
HYDRAULIC SYSTEM	WORKING PRESSURE	26.5" - 25"
	STEERING SYS PRESSURE	17 Mpa
	LIFTING CYLINDER BORE	Ø160 x Ø80 x 815 mm
	LIFTING CYLINDER BORE	Ø180 x Ø80 x 529 mm

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com