

振动压路机



AKS-RD107J

WALK-BEHIND SINGLE DRUM ROAD ROLLER
(ENGINE GX390 HONDA)
MADE IN CHINA 中國制造

SPECIFICATION	AKS - RD107J
WALK SPEED	0 - 4 km/h
CLIMBING CAPACITY	30%
DRIVE TYPE	Hydraulic Station
VIBRATION MODEL	Automatic Clutch
STATIC LINEAR LOAD	50 N/cm
NOMINAL AMPLITUDE	0.5 mm
VIBRATION FREQUENCY	70 HZ
EXCITING FORCE	20 KN
WATER TANK	20 L
HYDRAULIC OIL	16 L
ENGINE MODEL	HONDA GX390
POWER	13 HP
STEEL WHEEL SIZE	Ø 560 x 700 mm
STARTING MODE	Hand & Electric
PACKING SIZE	1250 x 1150 x 1350 mm
WEIGHT	413 kg

振动压路机



AKS-RD260J

WALK-BEHIND DOUBLE DRUM ROAD ROLLER
(ENGINE GX390 HONDA)
MADE IN CHINA 中國制造

SPECIFICATION	AKS - RD260J
WALKING SPEED	0 - 4 km/h
DRIVE TYPE	Hydraulic Station
VIBRATION CONTROL	Automatic Clutch
EXCITING FORCE	20 KN
STEEL WHEEL SIZE	Ø 425 x 600 mm x 2
VIBRATION FREQUENCY	70 HZ
NOMINAL AMPLITUDE	0.5 mm
STATIC LINEAR LOAD	53 N / cm
WATER TANK	20 L
CLIMBING CAPACITY	30%
PACKING SIZE	1450 x 1100 x 1200 mm
WEIGHT	478 kg
ENGINE BRAND / MODEL	HONDA / GX390
ENGINE TYPE FOUR STROKE, SINGLE CYLINDER, AIR COOLED	
MAXIMUM POWER	13 HP / 3600 Rpm
OIL TANK VOLUME	3.5 L
STARTING MODE	Hand & Electric

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

振动压路机

AKS-RD1309H

HYDRAULIC VIBRATION
ROAD ROLLER

MADE IN CHINA 中國制造



ENGINE GX630
HONDA JAPAN

SPECIFICATION	AKS - RD1309H
WIDTH OF STEEL WHEEL	900 mm
DIA. OF STEEL WHEEL	560 mm
FORWARD / BACKWARD SPEED	0 - 126 m/min
GRADEABILITY	30%
OUTER TURNING RADIUS	2.8 m
NOMINAL AMPLITUDE	0.5 mm
VIBRATION FREQUENCY	60 Hz (3600VPM)
EXCITING FORCE	13 kN
WATER TANK VOLUME	100 L
OVERALL DIMENSION	2365 x 1020 x 2250 mm
WEIGHT	1160 kg
ENGINE BRAND / MODEL	HONDA GX630
ENGINE TYPE FOUR STROKE, SINGLE CYLINDER, AIR COOLED	
RATED POWER	20 Hp
DISPLACEMENT	30 L
ENGINE SPEED AT FULL LOAD	2800 Rpm
FUEL TYPE (TANK VOLUME)	Gasoline (25 L)
LUBRICANT	1.8 L
FUEL CONSUMPTION	4 L/hours
STARTING MODE	Electric (Battery 12 V)

振动压路机

AKS-RD3T



VIBRATORY ROAD ROLLER
(ENGINE CHANGCAI N390T)
MADE IN CHINA 中國制造

SPECIFICATION	AKS - RD3T
WALK SPEED	0 - 7.8 km/h
GRADEABILITY	20%
STATIC LINEAR LOAD	153 / 120 N/cm
NOMINAL AMPLITUDE	0.5 mm
EXCITING FORCE	30 kN
WATER TANK	200 Liter
VIBRATION FREQUENCY	50 Hz
ENGINE TYPE	CHANGCAI N390T
STEEL DRUM DIAMETER	780 mm
STEEL DRUM WIDTH	1090 mm
POWER	22 Kw
WORKING WEIGHT	2900 kg
STEERING TYPE	Hydraulic
OVERALL DIMENSION	2850 x 1300 x 2650 mm
WEIGHT	3050 kg

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com

振动压路机



AKS-JM12T

(12 Ton)

VIBRATORY ROAD ROLLER

(ENGINE CUMMINS)

MADE IN CHINA 中國制造



SPECIFICATION	AKS - JM12T
OPERATING WEIGHT	120 kn
FRONT DRUM (VIBRATORY DRUM)	53 kn
REAR DRUM (DRIVING DRUM)	67 kn
SIZE OF FRONT / REAR DRUM	Ø 1200 mm x 1700 mm
STATIC LINER PRESSURE (FRONT,REAR)	310, 380 mm
WHEEL BASE	3180 mm
MOVING SPEED I II III RANGE	2.4 / 4.8 / 8.4 km/h
TURNING RADIUS & GRADEABILITY	< 6000 & > 20%
FRAME GROUND CLEARANCE	380 mm
VIBRATION FREQUENCY PARAMETER	42 Hz
AMPLITUDE OF VIBRATION	0.45 / 0.70 mm
CENTRIFUGAL FORCE	85 / 98 kn
WATER BOX VOLUME (FRONT, REAR)	300 L x 2
OVERALL DIMENSION	4900 x 2080 x 2800 mm

SPECIFICATION	ENGINE SYSTEM
ENGINE BRAND	CUMMINS
ENGINE MODEL	4BT3.9-C100
ENGINE TYPE	DIESEL ENGINE
RATED POWER	75 kw / 2500 Rpm
MAX. TORQUE	410 n.m / 1500 Rpm
ADVERTISED POWER	74 kw / 2200 Rpm
NUMBER OF CYLINDER	in-line, 4 Cylinder, 4 Cycle Engine
CYLINDER BORE	102 mm
DISPLACEMENT	3.9 L
FUEL TANK VOLUME	160 L

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

www.aksjakarta.com