

AKS-BD1TM3  
AKS-BD2TM3



AKS-BD3TM3  
AKS-BD5TM3



AKS-BD10TM3



手拉葫芦



Moving Products From One Place To Another



Uprooting Tress



Installing Under-Water Pump



Laying Conduits and Pipelines

**AKS-BD1TM3, AKS-BD2TM3, AKS-BD3TM3, AKS-BD5TM3, AKS-BD10TM3**

MANUAL CHAIN HOIST

MADE IN CHINA 中國制造

SPECIFICATION	TYPE	AKS - BD1TM3	AKS - BD2TM3	AKS - BD3TM3	AKS - BD5TM3	AKS - BD10TM3
Capacity		1 Ton	2 Ton	3 Ton	5 Ton	10 Ton
Standard Lifting Height		3 m	3 m	3 m	3 m	3 m
Standards Of Load Chain		1	1	1	2	4
Load Chain		6 x 18 mm	8 x 24 mm	10 x 30 mm	10 x 30 mm	10 x 30 mm
Min Headroom		367 mm	470 mm	548 mm	688 mm	765 mm
Effort Required To Lift Rated Load		250 N	335 N	372 N	360 N	380 N
Running Test Load		12.5 KN	25 KN	37.5 KN	62.5 KN	125 KN
Packing Dimension		30 x 20 x 20 cm	34 x 23 x 20 cm	36 x 26 x 21 cm	43 x 34 x 24 cm	54 x 46 x 25 cm
Weight		11 kg	18 kg	22 kg	39 kg	68 kg

Gambar dan Spesifikasi Mesin tidak semua 100% sesuai

[www.aksjakarta.com](http://www.aksjakarta.com)