# **C911 Specifications**

# OKI



# A3 colour printer for professional quality output and unrivalled media flexibility

The C911 has been designed to meet the needs of the creative industries and is also well suited to general office applications, removing the need for two printers. Built to offer essential levels of high quality output, the C911 is robust and reliable, which are key requirements in these demanding markets.

#### Stunning high definition colour

The C911 uses digital LED technology and our Multi-Level ProQ technology to produce high definition printing in the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output

#### Lowest total cost of ownership

The C911 delivers significant cost savings against comparative printers, combining a highly competitive capital cost with ultra-high capacity toner cartridges.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges (38K) and drums (40K)
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage

#### Speed that you can rely upon

Highest printing speeds on the market with stunning high definition output that cannot be beaten.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)
- 2GB RAM and 1GHz processor for rapid throughput

#### Media flexibility to beat all others

The C911 beats the competition hands down when it comes to media flexibility, printing a complete range of media in-house.

- Widest paper handling A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Use a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility
- Duplex printing as standard

A3/A4	~
Colour/Mono	~
Prints A6 to 1321mm, up to 360gsm	~
1 - 30+ users	~



### CO11 - Colour and Mono Printer

Printer		OPERATOR PANEL	
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono	Display	10.9cm Colour Graphic LCD (480x272 dots)
Time to first print	8 seconds colour, 8 seconds mono		
Warm up time	50 seconds or less from power on	GENERAL FEATURES	
Processor speed	1 GHz	Memory	Standard RAM: 2GB; Maximum RAM: 2GB
			Optional Hard Disk Drive: 160GB
INTERFACE AND SOFTWARE			Operating temperature/humidity: 10°C to 32°C (17°C to 27°C
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T	Environment	
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF Print-		Storage temperature/ humidity: -10°C to 43°C, 10% to 90% RH
Finiter taliguages	ing (v1.7), XPS, SIDM	Power supply	
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: IPv4/v6, ICMP, ICMPv6, IGMP, IGMPv2, LPR, Port9100, IPP, IPPS, FTP, FTP over SSL, HTTP, HTTPS, TELNET, IPP, Auto IP, LLTD, BOOTP, DHCP, SNMPv1/v3, SNMP Trap, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, SMTP over SSL, POP3, SNTP, ICDP, FLDP, ODNSP, WSDPrint, WSD-Discovery, Web JetAdmin, NetBIOS over TCP, EtherTalk	Power consumption	Typical: 1100W; Max: 1600W; Idle: 40W (average); Power Save: <34W; Deep Sleep: <4W; Off Mode: <0.5W
		Noise level	<b>Operating:</b> 57dB(A); <b>Standby:</b> 34dB(A) or less; <b>Power save:</b> Inaudible
		Dimensions (HxWxD)	640 x 699 x 625mm
		Weight <sup>4</sup>	97.6kg
		Duty cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month
OS Compatibility <sup>1</sup>	Windows 7 (32-bit & 64-bit) / Windows 8 (32-bit & 64-bit) / Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server	Product order number	<b>C911dn:</b> 45530408
	2008 R2 (64-bit) / Server 2012 (64-bit); Mac OS9 / OS X 10.3.9 - 10.9	Accessories (Order Numbers)	
Advanced networking and security	IPv6, 802.1x authentication, SMTP Server Authentication,	2nd/3rd paper tray	
	SNMPv3, SSL3/TLS encryption, HTTPS encryption, Protocol On/Off, Protocol Port No. Change, MAC filtering, IP filtering, IP	2nd/3rd paper tray with castor	45530903
		High Capacity Feeder	45530803
		Hard Disk Drive	160GB: 44622302
Utility suite <sup>1</sup>	Print Job Accounting <sup>2</sup> , Print Job Accounting Enterprise <sup>2</sup> , Print Job Accounting Client, PrintSuperVision.net <sup>2</sup> , Template Manager <sup>2</sup> , Color Correct, Color Swatch <sup>2</sup> , Configuration Tool, PS Gamma Adjuster, Profile Assistant (Mac Only), PDF Direct Print	CONSUMABLES (ORDER NUMBE	ers)
		Toner cartridge* (38,000 pages)	
Typefaces		Toner cartridge* (24,000 pages)	

LIACLU		
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bit- map fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts	
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes	

#### PRINT QUALITY

Resolution	ProQ2400 Multi-level technology, 1200 x 1200dpi		
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect		

## PAPER HANDLING Paper capacity Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets of 80gsm

	005311		
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm		
Maximum paper capacity	2,950 sheets of 80gsm		
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6, Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B4, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), SRA4, A4, A5, A6, B4, B5, B6		
Paper weight	Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm; Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm		
Duplex	Standard		
Paper output	610 sheets face down tray, 300 sheets face up tray		

# Image drums\*\* Cyan: 45103733; Magenta: 45103732; Yellow: 45103731; (40,000 pages) Black: 45103734 Transfer Belt 45531213 (150,000 pages) Fuser Unit 45531113 (150,000 pages) Waste Toner Box

45531503 (40,000 pages)

\*Toner: Number of A4 pages @ ISO coverage. Printer shipped with toner for 10,000 pages @ ISO.
\*\*Drum: Average number of A4 pages printed.

<sup>1</sup>Check local OKI website for latest driver releases and OS compatibility; <sup>2</sup>Windows only; <sup>3</sup>HDD required; <sup>4</sup>Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI DATA (SINGAPORE) PTE LTD. 438A Alexandra Road #02-11/12, Lift Lobby 3 Alexandra Technopark Singapore 119967 Tel: (65) 6221 3722 WWW.OKI.COM.SG

Lifetim

OKI DATA (SINGAPORE) PTE LTD. Malaysia Rep Office Suite 21.03, 21st Floor Menara IGB, Mid Valley City 59200 Kuala Lumpur, Malaysia . Tel: (03) 2287 1177 : 1800 88 1177 (Toll Free) Fax: (03) 2287 1166 WWW.OKI.COM.MY

**OKI SYSTEMS (THAILAND) LTD.** 1168/81-82 Lumpini Tower, 27th Floor Rama IV Road Tungmahamek, Sathorn Bangkok 10120 Tel: (662) 679 9235 Fax: (662) 679 9243/245 WWW.OKISYSTHAI.COM

OKI DATA AUSTRALIA PTY LTD. Level 1 67 Epping Road, Macquarie Park NSW 2113, Australia Toll Free: 1800 800 140 Tel: (612) 8071 0010 WWW.OKI.COM.AU



© 2013 ODSP Version 1.0 9/2013. Specification subject to change without notice. All trademarks acknowledged.