B820n - Mono Printers

Printer		Турегасеѕ	
Print speed	A4: 35ppm; A3: 20ppm	Printer fonts	PCL: 87 scalable PCL and 3 bitmap font
Time to first print	5 seconds		LIEBE 7: P
Warm up time	Up to 19 seconds	Barcode	USPS Zip Barcode
Processor speed	PowerPC464FP 533MHz	PRINT QUALITY	
Interface and Software		Resolution	600 x 2400dpi, 600 x 1200dpi, 600 x 600dpi, 300 x 300dpi
Connectivity	10/100-TX Ethernet, USB 2.0 Hi-Speed, IEEE 1284 Bi-directional Parallel	GENERAL FEATURES	
Printer languages	PCL5e, SIDM (IBM-PPR, EPSON-FX)	Memory	Standard RAM: 128MB; Maximum RAM: 640MB
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMP, TCP, UDP, LPR, PORT9100, FTP, HTTP, HTTPS, IPP, SNMP v1/v3, TELNET, BOOTP, DHCP, DNS, DDNS, UPnP, Bonjour, WINS, SMTP, POP3, SNTP, WSDPrint, LLTD; NetWare 4.1//5]/6J with full NDS support:-PServer, RPrinter; EtherTalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP; IEEE802.1x; NetBEUI: SMB, NetBIOS; Other: EAP-TLS, PEAP, IPSec		Optional SDHC Memory Card ⁵ : 16GB
		Environment	Operating temperature/ humidity: 10°C to 32°C / 20% to 80% RH
			Storage temperature/ humidity: -10°C to 43°C / 10% to 90% RH
		Power supply	Single phase 220 to 240VAC +/- 10%, frequency 50/60Hz +/- 2%
		Power consumption	Typical: 550W; Max: 1200W; Idle: 75W; Power Save: 15W; Sleep mode: <1.2W
		Noise level	Operating: 54dB(A) or less Standby: 37dB(A) or less; Power save: Background level
Advanced networking & security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encryption, Secure Print ^{2/3} , Secure Erase ^{2/3} , Data Encryption ² , MAC filtering, IP filtering, IPSec	Dimensions (HxWxD)	373 x 485 x 450mm (max 575mm)
OS Compatibility¹	Windows XP / XP x64 / Server 2003 (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2; Mac OS X 10.3.9 - 10.6.4; Unix/Linux	Weight ⁶	24kg approx;
		Duty cycle	Maximum: 100,000 pages/month; Recommended: 20,000 pages per month
Utility suite ¹	Lusing PPD Configuration Tool², Driver Installer², Front End², OKI LPR², Network Card Setup, Network Extension², PrintSuperVision²/4, Template Manager², Print Control Server²/4, Print Control Client⁴, Print Control Report Tool²/4, Storage Device Manager², PDF Print Direct²/4, Web Driver Installer²/4	Product order number	44675903
		Accessories (Order Numbers)	
Stricy Suite		Duplex	44676204
		Memory	256MB: 44302203; 512MB: 44302207
PAPER HANDLING		SDHC Memory card ⁴	16GB: 44301003
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm	2nd paper tray	44676104
Paper capacity optional tray		CONSUMABLES (ORDER NUMBERS)	
Maximum paper capacity		Black print cartridge*	11707704
Paper sizes	Tray 1: A3, A4, A5, B4, B5; Tray 2: A3, A4, A5, B4, B5; Multipurpose tray: A3, A4, A5, B4, B5, A6; 10 Envelopes (Com-9, Com-10, DL, Monarch, C4, C5); Labels (A4), Custom size: Width 76-297mm Length 148-431.8mm; Duplex: A3, A4, A5, B4, B5; Custom size: Width 148.5-297mm Length 182-420mm	(6,000 pages)	44707701
		Black print cartridge* (15,000 pages)	44708001
		Image drum**	44707401
Paper weight	Tray 1/2: 60 to 176gsm; Multi-purpose tray: 60 to 200gsm; Duplex: 60 to 105gsm	(30,000 pages)	
Duplex	Optional	*Number of A4 pages yield compliant with ISO/ISC 19752. Printer shipped with toner for 6,000 pages yield compliant with ISO/IEC 19752.	
Paper output	250 sheets face down, 100 sheets face up, 80gsm	**Drum: Average number of A4 pages printed.	

¹Check local OKI Printing Solutions website for latest driver releases and OS compatibility; ²Windows only; ³SDHC memory Card required; ⁴Download from web only; ⁵Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ⁶Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI DATA (SINGAPORE) PTE LTD.

438A Alexandra Road #02-11/12 Alexandra Technopark Singapore 119967 Tel: (65) 6221 3722 WWW.OKI.COM.SG OKI DATA (SINGAPORE) PTE LTD.

Malaysia Rep Office

Suite 21.03, 21st Floor

Menara IGB, Mid Valley City

59200 Kuala Lumpur, Malaysia Tel: (03) 2287 1177 : 1800 88 1177 (Toll Free)

Fax: (03) 2287 1166 **www.oki.com.my** OKI SYSTEMS (THAILAND) LTD.

1168/81-82 Lumpini Tower, 27th Floor Rama IV Road Tungmahamek, Sathorn Bangkok 10120 Tel: (662) 679 9235 Fax: (662) 679 9243/245

WWW.OKISYSTHAI.COM

OKI SYSTEMS (HONG KONG) LTD.

Suite 1908, 19/F, Tower 3, China Hong Kong City 33 Canton Road, TsimShaTsui, Kowloon, Hong Kong Tel: (852) 3543 9288 Fax: (852) 3549 6040

WWW.OKIPRINTINGSOLUTIONS.COM.HK

OKI DATA AUSTRALIA PTY LTD

146 O'Riordan Street, Mascot NSW 2020 Toll Free: 1800 800 140 Tel: (61 2) 9667 7240

WWW.OKIPRINTINGSOLUTIONS.COM.AU







B820n Specifications





Transform your black and white documents with the B820, the A3 printer with the speed, versatility and footprint of an A4 device.
With sharper mono output, provided by OKI's innovative digital LED technology, the B820 brings A4 and A3 mono printing closer to your small to medium workgroup.

Gone are the days of having to decipher your spreadsheets and diagrams with a magnifying glass. The B820 provides the convenience of fast desktop A4 printing speeds of up to 35ppm with the capability to print your documents at a size that gives them and you a new perspective. The B820 is competitively priced when compared with many A4 printers and brings affordable, A4 and A3 mono printing, to every business, large or small.

The B820 is designed to offer low running costs with a low total cost of ownership that puts A3 printing in the reach of businesses and workgroups in every sector.

Fast, superior mono printing on your desktop

First page appears in just 5 seconds, the rest at an impressive 35ppm for A4 (20ppm for A3) and with the combination of 128MB RAM memory, fast 533MHz processing power and its 600 x 2400dpi print resolution, pin-sharp output is assured quickly every time — a must for all customer facing documents and output. Network ready with PCL built-in for maximum platform flexibility and application support.

Flexible media output and duplex printing

Able to handle a wide range of media from A6 to A3 and paper weights of up to 200gsm, the B820 is ideal for reducing costs through printing essential business documents in-house. In addition, the B820dn models offer duplex printing and the standard paper capacity of 630 sheets can be expanded up 1,160 sheets for a wider range of output.

Reduced running costs and lower TCO

The B820 has been designed to provide a cost effective printing resource that can sit on the desktop, closer to the workgroup. With a 15k

capacity print cartridge and an energy saving sleep mode of 1.2W, your power consumption is reduced, conserving energy, lowering your running costs and carbon footprint.

Packed full of value-added features

Putting you in control, the software utilities and features provide even more value for your money. Secure Print³ removes the risk of sensitive information falling into the wrong hands. Whilst PrintSuperVision provides remote monitoring and management of printers across your network and Print Control allows you to control your print costs and usage.

Combining reliable technology with minimal user intervention

The B820 is built on tried and tested digital LED technology, developed by OKI for over 20 years. The robust design and innovative technology not only deliver outstanding reliability but also the 100k duty cycle offer you consistently high quality prints over and over again, further reducing user intervention.

A4/A3	~
Range of media handling	~
Mono	~
Print	~
1-30 usors	

Variant available: B820n networked

