



**RELIABLE, SEAMLESS INTEGRATION
MAKES ALL THE DIFFERENCE.**

Increase service productivity and efficiency, while maintaining a low TCO, with Epson's powerful 24-pin PLQ-20 series passbook printers. Fast and versatile, with print speeds of up to 480 cps, these printers will get your customer lines moving like never before. Boasting a ribbon life of 5 million character yields, an MVBf of 7 million lines, an MTBF of 10,000 power-on hours and a print head life of 400 million strokes/wire, the power PLQ-20 series promises amazing performance even in the most bustling business environments. With built-in smart functions such as Auto Platen Gap/Sheet Adjustment, which accept a variety of media thickness and auto-align misfed documents, printing has never been easier.



Print



Platen Gap /
Sheet
Adjustment



Cost
Effective

IT'S IN THE DETAILS.

Blazing Fast Speeds

Accomplish more in less time with print speeds of up to 480cps and high-speed paper throughput.

Seamless Integration, Smart Functionality

Enjoy easy installation and fuss-free printing with multiple connection ports and a range of smart and user-friendly features.


Superior Versatility and Reliability

Built to last and designed to accommodate a wide variety of printing needs.

MODEL NUMBER	PLQ-20/20M	PLQ-20D/20DM
Printer Technology		
Printing Method	Impact dot matrix	
Number of Pins in Head	24 pins	
Colour	Black	
Print Direction	Bi-direction with logic seeking	
Control Code	PR2 emulation, ESC/P2, WNI 4915 emulation, IBM PPDS emulation, IBM 4722 emulation*	PR2 emulation, ESC/P2, WNI 4915 emulation, IBM PPDS emulation, IBM 4722 emulation
Printer Speed		
High Speed Draft	10 / 12 cpi	480 / 432 cps
Draft	10 / 12 cpi	360 / 360 cps
NLQ	10 / 12 cpi	180 / 180 cps
LQ	10 / 12 cpi	120 cps / 144 cps
Print Characteristics		
Character Sets	International, PC-437 International, OCR-A	
Barcode Fonts	PR2	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Coda bar (NW7), Industrial 2 of 5
	ESC/P	EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
Printable Columns		
Pitch	10 / 12 cpi	94 / 112 cpl
Paper Handling		
Paper Feeding	Friction Feed (Front manual)	
Paper Path	Manual Insertion (Front in, Front out / Front in, Rear out)	
Paper Size		
Passbook	Width	110 - 241.3 mm
	Length	Horizontal seam: 127 - 220 mm Vertical seam: 85 - 220 mm
	Total Thickness	Max. 2.6mm (open passbook)
	Weight	95 - 116 g/m ²
Cut Sheet (Single)	Width	65 - 245 mm
	Length	67 - 297 mm
	Thickness	0.065 - 0.19 mm
	Weight	52 - 157 g/m ²
Cut Sheet (Multi-part)	Width	65 - 245 mm
	Length	67 - 297 mm
	Copies	1 original + 6 copies
	Thickness	0.12 - 0.53 mm
	Weight (per sheet)	34 - 50 g/m ²
Line Spacing	4.23mm (1/6") PR2: Programmable in increments of 0.106mm (1/240") or 0.118mm (1/216") Other emulation: Programmable in increments of 0.0706mm (1/360")	
Acoustic Noise		
	53 dB(A) (w/o MSRW) 55 dB(A) (w/ MSRW)	
Input Data Buffer		
	64 KB	128 KB
Interface		
	Bi-directional Parallel 9-pin Serial USB 2.0 Full speed	9-pin Serial x 2 USB 2.0 Full speed
Ribbon Cartridge		
Standard	Fabric Ribbon Cartridge (Black)	
Ribbon Life	5 million characters (LQ 10cpi, 48 dots/character) 10 million characters (Draft 10cpi, 24 dots/character)	
Reliability		
Mean Print Volume Between Failure (MVBFB)	7 million lines	
Mean Time Between Failure (MTBF)	10,000 Power On Hours (POH)	
Print Head Life	400 million strokes/wire	
Environmental Conditions (Operating)		
Temperature	5 - 35 °C	
Humidity	10 - 80 % RH	
Electrical Specification		
Rated Voltage	AC 220 - 240 V	
Rated Frequency	50 - 60 Hz (49.5 - 60.5 Hz)	
Power Consumption		
Operating	Approx. 60W	
Sleep Mode	Approx. 5.5W	
Power Off	0W in powered off mode	

Dimensions & Weight

Weight: PLQ-20D Approx. 7.7 kg (16.97lbs)
PLQ-20DM Approx. 8.7 kg (19.18lbs)



Consumable

Ribbon (Black) C13S015592

Legend

cpi Characters per inch
(Characters per 25.4mm)
cps Characters per second

©2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

* This feature is not supported on standard out-of-the-box models and is available upon request.

Information correct as at March 2019