

PCS-H

Portable Hydraulic Pressure Calibrator



PCS-H is Portable pressure calibrator for hydraulic pressure calibration up to 100 MPa with pressure generation and precise control. Compared to other manufacture's equipment, PCS-H reduces calibration time and user fatigue because of easy and precise pressure generate and control for a large amount of on-site calibration.

PCS-H has a built-in lever type pump for internal deaeration and priming. Lever type priming pump can generate primary pressure up to 20 MPa and screw type hand pump can generate and precise pressure control easily and quickly up to 100 MPa use with very small torque.

PCS-HC is portable instrument that can generate up to 100 MPa which is the best portable hydraulic pressure generator/controller in the world. Upper side of PCS-HC equipped quick connectors and adaptors for quick and easy to connect DUT. PCS-HC using special O-Ring by PDK's own high pressure technology, therefore it can be used semi-permanently without failure.

Use

- Potable pressure calibration
- Simple calibration for common calibration lab
- Calibrate pressure gauge for pressure measuring instruments retail business
- Pressure generating and controlling for pressure test lab
- Pressure calibration for laboratory
- For hydraulic high pressure calibration
- Pressure switch test

Feature

- Built-in lever type priming pump
- Up to 100 MPa pressure generate and control
- Accuracy 0.025% F.S
- Supply the power to Pressure Transmitter and measure output
- High pressure generate and control with very small torque
- Excellent stabilization of the pressure
- Include fitting adaptor set & High pressure tube

PCS-H

Portable Hydraulic Pressure Calibrator



Specification

Pressure Range	0 to 20, 35, 70, 100 MPa
Accuracy	±0.025% F.S
Electronic Measurement and Source	±30 V.dc,, ±30 mA.dc, Accuracy ±(0.02%RD+0.003%FS),
Display	Max 6 digits LCD
Power	Use 10V.dc Power Adaptor, Rechargeable Battery, 4 hours charge can use 40 hours
Communication	RS232 Serial Communication
Workable Temperature	-10°C to 50°C (Storage Temperature -20°C to 70°C)
Pressure Unit	kg/cm2, kPa, MPa, psi, bar, mbar, inH2O, mmH2O, inHg, mmHg
Control Precision	1 kPa
Primming Pump	Max 20 MPa
Test Port	Quick Connection Body
Test Adaptor	1/2" PF(1), 3/8" PF(1), 1/4" PF(2), 1/4" NPT(1), 1/8" PT(1)
Weight	9 kg
Size	450 mmW x 360 mmD x 170 mmH

Order Information

Model	Description
PCS - H - Range 20 MPa 35 MPa 70 MPa 100 MPa	Portable Hydraulic Pressure Calibrator

Accessories

1.2 m High pressure flexible tube, Oil 1 liter, Syringe, Test Adaptor, Power Adaptor

PDK CO., LTD.



CV KALINDRA MITRA NIAGA

Phone : 021-5541468
HP : 0816-110-5088
Email : suhadi@kalindramini.com
Website : www.kalindramini.com