

TP 17 650 M



Technical data		
Type	TP 17 650 M	
Control sensor	Internal	
Dry block		
Temperature range*	RT...650 °C	RT...1202 °F
Accuracy	±1 °C	±1.8 °F
Stability	±0.1 °C	±0.2 °F
Measurement zone	110...150 mm	4.3...5.91 in
Block dimensions		
→ Diameter	Ø 28 mm	Ø 1.10 in
→ Depth	150 mm	5.91 in
Display unit		
Display	2-line, 4-digit display Red / green, unit °C / °F	
Display range	0...650 °C	32...1202 °F
Resolution	1 °C	1 °F
General data		
Dimensions		
→ Width	150 mm	5.91 in
→ Height	330 + 70 mm	12.99 + 2.76 in
→ Depth	270 mm	10.63 in
Weight	Approx. 7.5 kg	Approx. 16.53 lbs
Power supply	230 / 240 VAC, 50 / 60 Hz, optional 100...115 VAC, 50 / 60 Hz optional 100...240 VAC, 50 / 60 Hz	
Power consumption	Approx. 1000 W	

* At an ambient temperature of 20 °C / 68 °F

Scope of delivery

- Test certificate
- Mains cable
- Insert exchange tool
- Operating manual

Accessories

- Transport case
- Service transport bag
- Adapter sleeve
- DAkkS certificate
- Works certificate



CV KALINDRA MITRA NIAGA

Phone : 021-5541468
 HP : 0816-110-5088
 Email : suhadi@kalindramini.com
 Website : www.kalindramini.com
 www.kalindramitra.com