

## TP M 165 S



**Type** TP M 165 S

### Scope of delivery

- Test certificate
- Mains cable
- Operating manual
- Sensor basket, suction pump, transport cover
- Magnetic stirrer with magnet lifter
- Sensor lid with 5 silicone plugs

### Accessories

- Calibration liquid
- Transport case
- Tube insert
- PC software
- PC cable
- DAkkS certificate
- Works certificate

### Technical data

<b>Type</b>	TP M 165 S	
<b>Control sensor</b>	Internal	
<b>Micro Bath</b>		
<b>Temperature range*</b>	-35...165 °C	-31...329 °F
<b>Accuracy</b>	±0.1 °C	±0.18 °F
<b>Stability</b>	±0.05 °C	±0.09 °F
<b>Measurement zone</b>	110...150 mm	4.33...5.91 in
<b>Block dimensions</b>		
→ Diameter	Ø 60 mm	Ø 2.36 in.
→ Depth	170 mm	6.69 in.
<b>Display unit</b>		
<b>Display</b>	2-line, 4-digit display Red / green, unit °C / °F	
<b>Display range</b>	-50...165 °C	-58...329 °F
<b>Resolution</b>	0.01 °C between -9.99...99.99 °C, else 0.1 °C	0.01 °F between -9.99...99.99 °F, else 0.1 °F
<b>General data</b>		
<b>PC interface</b>	RS485, RS232 or USB (optional)	
<b>Dimensions</b>		
→ Width	210 mm	8.27 in
→ Height	380 + 50 mm	14.96 + 1.97 in
→ Depth	300 mm	11.81 in
<b>Weight</b>	Approx. 12.5 kg	Approx. 27.56 lbs.
<b>Power supply</b>	100...240 VAC, 50 / 60 Hz	
<b>Power consumption</b>	Approx. 375 W	

\* At an ambient temperature of 20 °C / 68 °F