

# TP 17 650 S



Technical data		
Type	TP 17 650 S	
Control sensor	Internal	
Dry block		
Temperature range*	RT...650 °C	RT...1202 °F
Accuracy	±0.4 °C	±0.72 °F
Stability	±0.05 °C	±0.09 °F
Measurement zone	110...150 mm	4.3... 5.91 in.
Block dimensions		
→ Diameter	Ø 28 mm	Ø 1.10 in.
→ Depth	150 mm	5.91 in.
Display unit		
Display	2-line, 4-digit display Red / green, unit °C / °F	
Display range	0...650 °C	32...1202 °F
Resolution	0.01 °C between RT...99.99 °C, else 0.1 °C	0.01 °F between RT...99.99 °F, 0.1 °F between 100.0...999.9 °F, else 1 °F
General data		
PC interface	RS485, RS232 or USB (optional)	
Dimensions		
→ Width	150 mm	5.91 in.
→ Height	330 + 70 mm	12.99 + 2.76 in.
→ Depth	270 mm	10.63 in.
Weight	Approx. 7.5 kg	Approx. 16.53 lbs.
Power supply	230 / 240 VAC, 50 / 60 Hz, optional 100...115 VAC, 50 / 60 Hz optional 100...240 VAC, 50 / 60 Hz	
Power consumption	Approx. 1000 W	

\* At an ambient temperature of 20 °C / 68 °F

### Scope of delivery

- Test certificate
- Mains cable
- Insert exchange tool
- Operating manual

### Accessories

- Transport case
- Service transport bag
- Adapter sleeve
- PC software
- PC cable
- DAkkS certificate
- Works certificate



## CV KALINDRA MITRA NIAGA

Phone : 021-5541468  
 HP : 0816-110-5088  
 Email : suhadi@kalindramini.com  
 Website : www.kalindramini.com  
 www.kalindramitra.com