

TP ZERO

Technical data		
Type	TP ZERO	
Control sensor	Internal	
Dry block		
Temperature range*	-10...100 °C	14...148 °F
Accuracy	±0.05 °C at 0 °C	±0.09 °F at 32 °F
Stability	±0.05 °C at 0 °C	±0.09 °F at 32 °F
Measurement zone	110...150 mm	4.3... 5.91 in.
Block dimensions		
→ Diameter	7 drillings with Ø 6.5 mm	7 drillings with Ø 0.26 in.
→ Depth	150 mm	5.91 in.
Display unit		
Display	1-line, 4-digit display Red, unit °C (°F optional)	
Display range	-10...100 °C	14...212 °F
Resolution	0.1 °C	0.1 °F
General data		
Dimensions		
→ Width	160 mm	6.3 in.
→ Height	320 + 50 mm	12.6 + 1.97 in.
→ Depth	230 mm	9.06 in.
Weight	Approx. 7 kg	Approx. 15.43 lbs.
Power supply	100...240 VAC, 50 / 60 Hz	
Power consumption	Approx. 225 W	

* At an ambient temperature of 20 °C / 68 °F

Type TP ZERO



Scope of delivery

- Test certificate
- Mains cable
- Operating manual

Accessories

- Transport case
- PC software
- PC cable
- DAkkS certificate
- Works certificate



CV KALINDRA MITRA NIAGA

Phone : 021-5541468
 HP : 0816-110-5088
 Email : suhadi@kalindramini.com
 Website : www.kalindramini.com
 www.kalindramitra.com



The TP ZERO temperature calibrator is ideal for creating the ice point.