




6xFi(29)+IWRC




6xWS(31)+IWRC



6xWS(36)+IWRC



6xWS(41)+IWRC



6xSeS(37)+IWRC

Diameter of Rope mm	Minimum Breaking Load								Approx Weight per Meter kg / m
	A & BG (165 kg/mm ²)		B & CG (180 kg/mm ²)		C(200 kg/mm ²)		SC(220 kg/mm ²)		
	kN	Tonnef	kN	Tonnef	kN	Tonnef	kN	Tonnef	
8.0	39.7	4.1	42.8	4.4	42.2	4.3	46.4	4.7	0.282
9.0	50.2	5.1	54.1	5.5	53.3	5.4	58.6	6.0	0.367
9.5	56.0	5.7	60.3	6.2	59.4	6.1	65.3	6.7	0.398
10.0	62.1	6.3	66.8	6.8	65.8	6.7	72.4	7.4	0.441
11.2	77.9	7.9	83.8	8.6	82.6	8.4	90.8	9.3	0.553
12.0	78.5	8.0	83.4	8.5	92.2	9.4	100.0	10.2	0.635
12.5	85.3	8.7	90.2	9.2	100.0	10.2	107.9	11.0	0.689
14.0	106.9	10.9	113.8	11.6	125.5	12.8	136.3	13.9	0.864
16.0	139.3	14.2	149.1	15.2	164.8	16.8	177.5	18.1	1.130
18.0	175.5	17.9	188.3	19.2	207.9	21.2	224.6	22.9	1.430
19.1	199.1	20.3	211.8	21.6	234.4	23.9	253.0	25.8	1.610
20.0	217.7	22.2	232.4	23.7	256.0	26.1	276.5	28.2	1.760
22.4	272.6	27.8	291.3	29.7	321.7	32.8	347.2	35.4	2.210
24.0	313.8	32.0	334.4	34.1	369.7	37.7	417.8	42.6	2.540
25.0	340.3	34.7	362.8	37.0	411.9	42.0	453.1	46.2	2.760
26.0	367.7	37.5	392.3	40.0	445.2	45.4	490.3	50.0	2.980
28.0	426.6	43.5	455.0	46.4	516.8	52.7	567.8	57.9	3.460
30.0	500.1	51.0	531.5	54.2	592.3	60.4	652.1	66.5	3.970
31.5	551.1	56.2	586.4	59.8	653.1	66.6	717.8	73.2	4.370
32.0	568.8	58.0	605.1	61.7	673.7	68.7	741.4	75.6	4.510
33.5	623.7	63.6	662.9	67.6	738.4	75.3	813.0	82.9	5.100
35.5	700.2	71.4	745.3	76.0	829.6	84.6	-	-	5.560
37.5	781.6	79.7	831.6	84.8	924.8	94.3	-	-	6.710
38.0	802.2	81.8	853.2	87.0	950.3	96.9	-	-	6.200
40.0	889.5	90.7	945.4	96.4	1052.3	107.3	-	-	6.370
42.0	985.6	100.5	1029.7	105.0	1187.6	121.1	-	-	7.050
42.5	1000.3	102.0	1068.9	109.0	1196.4	122.0	-	-	7.780
44.0	1078.7	110.0	1147.4	117.0	1270.9	129.6	-	-	7.960
									8.530
									8.930

IND STRAND
Technology from Italy

BRITISH STANDARD **DIN**

PALITOTTA WIRE AND WIRE PRODUCTS