

TELAH LULUS UJI LAB DAMKAR, SESUAI STANDAR NFPA 10
 RAMAH LINGKUNGAN, BUBUK ABC 70%
 CE APPROVAL, GARANSI 3TH TAHUN

ZEKI



POWDER (CONTENT : MAP 70%)



MODEL	ZT-10P	ZT-25P	ZT-35P	ZT-45P	ZT-60P	ZT-90P
Capacity	1 kg	2,5 kg	3,5 kg	4,5 kg	6,0 kg	9,0 kg
Overall Height	260 mm	330 mm	390 mm	400mm	400 mm	470 mm
Body Diameter	90mm	130 mm	120 mm	135mm	160 mm	175 mm
Working Pressure	12 BAR	12 BAR	12 BAR	12 BAR	12 BAR	12 BAR
Test Pressure	24 BAR	24 BAR	24 BAR	24 BAR	24 BAR	24 BAR
Approx • Discharge Time	15 sec	15 sec	15 sec	17 sec	19 sec	22 sec
Approx • Discharge Range	2-4 m	2-4 m	5-6 m	5-7 m	6-7 m	6-7,5 m
Propellant	Nitrogen (N ₂)	Nitrogen (N ₂)	Nitrogen (N ₂)	Nitrogen (N ₂)	Nitrogen (N ₂)	Nitrogen (N ₂)
Fire Rating	2A:10B	8A:34B	8A:55B	13A:70B	21A:113B	21A:144B

* For ABC Class Fire

CO2



MODEL	ZCO-5	ZCO-7	ZCO-10	ZCO-15	ZCO-50
Capacity	2,3 kg	3,2 kg	4,6 kg	6,8 kg	23 kg
Media	Carbon Dioxide (CO ₂)	Carbon Dioxide (CO ₂)	Carbon Dioxide (CO ₂)	Carbon Dioxide (CO ₂)	Carbon Dioxide (CO ₂)
Overall Height	470 mm	660 mm	650 mm	800 mm	1210 mm
Cylinder Diameter	110 mm	110 mm	150 mm	150 mm	220 mm
Working Pressure (@20°C/@60°C)	56 BAR/169,3 BAR	56 BAR/169,3 BAR	56 BAR/169,3 BAR	56 BAR/169,3 BAR	56 BAR/169,3 BAR
Test Pressure	250 BAR	250 BAR	250 BAR	250 BAR	250 BAR
Approx • Discharge Time	7 sec	12 sec	15 sec	16 sec	22 sec
Fire Rating	13 B	16 B	21 B	25 B	34 B

* For BC Class Fire

Fire Classifications:

Class A - Fires in ordinary combustible materials such as wood, cloth, paper, rubber and many plastics.

Class B - Fires in flammable liquids, oils, greases, tars, oil-based paints, etc., and flammable gasses.

Class A - Fires involving "live" electrical equipment such as computer.