



Ritrama S.p.A. Caponago Tel. +39 02 955 459 1  
info@ritrama.it  
Ritrama S.p.A. Fabriano Tel. +39 0732 97061  
info@ritrama.it  
Ritrama Ltd. (UK) Tel. +44 161 786 1760  
sales@ritrama.co.uk  
Coating Ricofin S.r.l. Tel. +39 02 9210 6310  
info@ricofin.it

Ritrama S.A. Tel +34 93 729 4998  
info@ritrama.es  
Ritrama Inc. Minneapolis (USA) Tel. +1 612 378 2277  
rdi@ritrama.com  
Ritrama Inc. Cleveland (USA) Tel. +1 216 851 2300  
rdi@ritrama.com  
Web site: [www.ritrama.com](http://www.ritrama.com)

## Ri-Mark Series

**Spec. No.: RM01**

**Date of Issue : 21-11-00**

**Supersedes: 15/05/00**

**L100 Series** Available Colours: 34  
*3 year 70 mic Sign Vinyl - Glossy Finish*

**Face Material:**

Face Caliper: 70 mic

Weight: 95 gsm

Film Type: Monomeric

Dimensional Stability (DIN 53479): <1.0%

Conformability: Very Good

Flammability (DIN 752000): Self Extinguishing

Resistance against chemicals and solvents (DIN 51958):

- Distilled water/32°C @ 150 hours - No change
- Diesel oil / normal climate @ 24 hrs - No change
- Hydraulic oil / normal climate @ 24 hours - No change
- Cold cleaning agent mixture @ 8 hours - No change
- Soap / 65°C @ 8 hours - No change

**Adhesive:**

Adhesive Code: RI-AVM

Adhesive Type: Permanent Acrylic

Resistance to Sunlight: Very Good

Tack: Medium

Cohesive Strength: High

Min Application Temp.: +5°C

Service Temp.: -30 to +80°C

Initial Adhesion to SS: 900 g/25 mm

48 Hr Adhesion to SS: 1400+ g/25 mm

**Release:**

Release type: Kraft - single side siliconised

Colour: White

Backprint: Printed 'L&M'

Release Weight: 120 gsm

Release Caliper: 108 mic

Available Width: 1.22m

Typical Usages: Medium term sign applications