



BMD-450C

BS-400LA

主要技术参数 Technical data		BS-400LA
封切形式	Sealing type	L型全封闭式 L-sealing by means of L-bar
电 源	Power supply	380V/50-60Hz/3phase
最高速度	Max packing capacity	35包/分 35 packs per minute (depends on product size)
包装高度	Sealing height	≤125 mm
包装宽度	Packing width	≤350 mm
包装尺寸	Product size	宽度-高度 ≤400 mm width+height ≤400 mm 长度-高度 ≤480 mm length+height ≤480 mm
使用薄膜	Film type	POF对折膜 center-folded polyolefin (POF) film
最大膜线	Max film size	530mm(宽) x 280mm(外径) 530mm (width) x 280mm(outer diameter)
总 功 率	Power consumption	1.5 kW
平台高度	Working height	780-850 mm
气 压	Air pressure	≤0.5MPa (5 bar)
封切系统	Sealing system	恒温加热系统, 容易更换切刀, 封切不冒烟无臭味 permanently heated seal bar coated with Teflon
主要材质	Machine material	碳钢 carbon steel
整机重量	Weight	300kg

主要技术参数 Technical data		BMD-450C
电 源	Power supply	380V/50-60Hz/3phase
炉体尺寸	Oven size	1200mm(L), 炉口 Entrance 450(W) x 220(H) mm
输送速度	Conveyor speed	可调, 40米/分 variable, 40 m/min
输 送 带	Conveyor	链式输送带, 滚轴套硅胶管 chains with rotating silicon coated rods
总 功 率	Power consumption	7kW
平台高度	Working height	780-850 mm
主要材质	Machine material	碳钢 carbon steel
整机重量	Weight	160kg

产品参数仅作参考, 可按客户要求设计制作。  
Specifications on all machines can be changed upon request.

### BS-400LA + BMD-450C L型全自动热收缩包装机 (全封闭式) Automatic L-bar Sealing & Shrink Packing Machine

L型全封闭式



#### 适用范围

制药、食品、饮料、文具、印刷品、化妆品、礼品、电子产品、玩具、汽车配件、餐具等产品的单体或集体包装。

#### Applicability

Single and group products of medicine, food, drinking, stationery, printings, cosmetic, electronic products, toys, auto parts, tableware, etc.

