

**\*Features.**

- Compact construction, high efficiency
- The use of infra-red Quartz heater tube results in lower the power consumption
- Great air-flow provides excellent heat distribution for an even shrink
- Temperature meter control temperature
- Automatic temperature control : the system features automatic temperature variation for convenient operation.
- Variable speed live-roller (mesh) conveyor is easily adjusted

# THERMAL-SHRINK PACKING MACHINE



**BSD-200**

Model	BSD-200
Power supply	220 V-240 V/50 Hz
Heater power	5.0 KW Adjustable
Conveyor speed	0-10 m/min.
Tunnel size	700x200x150 mm
Shink product size	150x100 mm
Conveyor loading	5 kg Maximum
Machine size	1040x400x1050/1250 mm
Machine weight	70 kg



**BSE-4535LA**

Model	BSE-4535 LA
Power supply	3 Phase 220 V, 380/50 220/60
Heater power	9.6 KW Adjustable
Conveyor speed	0-10 m/min.
Tunnel size	1200x450x(500-350) mm
Conveyor loading	25 kg Max
Machine size	1600 x 6500 x 1200 mm
Machine weight	120 kg

**BSD-350/400/450**



Model	BSD-350	BSD-400	BSD-450
Power supply	220-240 V/50 Hz		
Heater power	6.5 KW Adjustable	6.5 KW Adjust.	8 KW Adjust.
Conveyor speed	0-10 m/min.	0-10 m/min.	0-10 m/min.
Tunnel size	830x350x150 mm	830x400x200 mm	830 x 450 x 250 mm
Shink product size	300x150 mm	350x150 mm	400 x 200 mm
Conveyor loading	5 kg Maximum	5 kg Maximum	10 kg Maximum
Tunnel temperature	200°C Maximum		
Machine size	1050x550x1100	1200x600x1150	1200x690x1200 mm
Machine weight	75 kg	90 kg	100 kg

**BSD-350B/400B/450B**



Model	BSD-400B	BSD-450B
Power supply	220 V-240 V/50 Hz	380-415 V / Hz
Heater power	6.5 KW Adjustable	8 KW Adjustable
Conveyor speed	0-10 m/min.	0-10 m/min.
Tunnel size	830x400x200 mm	830x450x250 mm
Shink product size	350x150 mm	400x200 mm
Conveyor loading	5 kg Maximum	10 kg Maximum
Machine size	1200x640x1240 mm	1200x690x1290 mm
Machine weight	80 kg	100 kg

**BSD-3520A/4020A/4525A**



Model	BSD-3520A	BSD-4020A	BSD-4525A
Power supply	110, 220-240 V/50-60 Hz 1 Ø	380 V/50 Hz 3 Ø	
Heater power	7 KW Adjustable	6.5 KW Adjustable	8 KW Adjustable
Conveyor speed	0-15 m/min.	0-15 m/min.	0-15 m/min.
Tunnel size	800x350x200 mm	1000x400x200 mm	1000x450x250 mm
Shink product size	300x160mm	350x160 mm	400x210 mm
Conveyor loading	15 kg Maximum	25 kg Maximum	25 kg Maximum
Machine size	1050x610x1320 mm	1250x660x1320 mm	1250 x 710 x 1370 mm
Machine weight	80 kg	90 kg	120 kg
Shrink film	POF,PVC,PP		