

---

## Automatic Candy Packaging Machine



### Main performance and structural features

1. Double transducer control, flexible bag length cutting, operator need not to adjust, humanized operation automatically prompts, saving time and film;
  2. The control circuit adopts imported chip, HMI, inverter control, convenient parameter setting, the operation focused on intuitive and full realization of humane automatic operation control;
  3. Digital fault self-diagnosis function, fault diagnosis at a glance;
  4. Packing speed and length of bag dual frequency conversion control, digital input cut position, sealing and cutting precise location, beautiful, strong;
  5. High sense photocell accurately track;
  6. Positioned stop function, without sticking knife or cutting, or wasting film;
  7. Double-conversion simple mechanical structure, less wear, easy maintenance, long life;
  8. The sealing temperature, PID control for a variety of packaging materials;
  9. All controlled by the software can be installed intermittent pneumatic devices and alcohol spray device, real-time adjustments to achieve functional and technical upgrading never backward.
-

---

## Technical Parameter

Name	Automatic Candy Packing Machine	
Model	PLZB-250S (three cutter)	
Bag size	L	50—115mm
	W	30—80mm
	H	5—35mm
Film width	90--180mm	
Capacity	60—200bag/min	
Motor power	0.6Kw.	
Heater power	2.1Kw.	
Voltage	AC220V, 50Hz.	
G. W.	700Kg.	
Dimension	L3770*W670*H1450mm	
Usage	the scope for biscuit, moon cake, candy, small French bread, chocolate, insulating tape, paper towels, cartoons, mosquito coils, dates and other solid rules of product packaging	

---