

SUNPACK

XUTIAN PACKING MACHINE

Xutian is a group company with 3 branches in different cities. We dedicate to end of line package development for years. We have more than 30 staff in our RND department. Provide our customers with the best quality products and serve our customers with our best effort, it is our main goal. We carry banding machine, strapping machine, pallet wrapper, case sealer and manual strapping tool in our range.

Dongguan Xutian Packing Machine Co.,Ltd
东莞市旭田包装机械有限公司

ADD: NO.951 Songfo Road, Dalang Town, Dongguan, Guangdong, China
地址: 广东省东莞市大朗镇松佛路951号

Web: www.xutianpack.com www.xutian-china.com
Tel: +86-769-83123335 / 83131314/83131315
Fax: +86-769-83131818

Taizhou Xutian Packing Machine Co.,Ltd
台州旭田包装机械有限公司

ADD: NO.389-1 Haizheng Road, Jiaojiang District, Taizhou, Zhejiang, China
地址: 浙江省台州市椒江区海正大道389-1

Tel: +86-576-88833688 / 88833689
Fax: +86-576-88833690

Shanghai Xutian Packing Machine Co.,Ltd
上海旭田包装机械有限公司

ADD: NO.258, Jiamei Road, Jiading District, Shanghai, China
地址: 上海市嘉定区嘉美路258

Tel: +86-21-66112777 / 56061188
Fax: +86-21-56061188

国际
International
<http://www.xutianpack.com>
E-mail: joanna@xutian-china.com

国内
<http://www.xutian-china.com>
E-mail: lois@xutian-china.com



DONGGUAN XUTIAN PACKING MACHINE CO.,LTD

东莞市旭田包装机械有限公司

SUNPACK
PACKING MACHINE

XUTIAN®
旭田
PACKING MACHINE

东莞市旭田包装机械有限公司

DONGGUAN XUTIAN PACKING MACHINE CO.,LTD
www.xutianpack.com www.xutian-china.com

SUNPACK
PACKING MACHINE

XUTIAN
PACKING MACHINE

Xutian is a group company with 3 branches in different cities. We dedicate to end of line package development for years. We have more than 30 staff in our RND department. Provide our customers with the best quality products and serve our customers with our best effort, it is our main goal. We carry banding machine, strapping machine, pallet wrapper, case sealer and manual strapping tool in our range.

BETTER QUALITY & BETTER PRICE & BETTER SERVICE

WELCOME TO

SUNPACK

旭田欢迎您...



PROFILE 关于旭田

Xutian is dedicated to provide worldwide users with professional packaging solutions and focus on production of variety of packaging machinery. Xutian has decades of experience in packaging industry. With plants in different area, we can serve all our customers with fast and most convenient delivery. We delivered our machines to all over the world since we set up in 1997. Our RND department always follow up the world class technology and upgrade our products.

旭田包装致力于提供全球买家最先近的包装解决方案. 旭田有着丰富的包装行业的经验. 我们在浙江台州和广东东莞的工厂, 以及上海的办公室, 都让我们为客户提供好的服务提供了条件. 自从1997年建厂以来, 我们把旭田的产品卖到了全球各地. 我们的研发部门紧跟世界先进科技水平, 以及及时的改进我们的产品. 我们将致力于为我们客户提供更高质量的产品, 更快的服务, 最好的价格.





TO PROVIDE OUR CUSTOMERS
WITH THE HIGHEST QUALITY PRODUCTS AND BEST SERVICE
IS OUR ULTIMATE GOAL

EXHIBITION
国际展会



PRODUCTION WORKSHOP
生产车间



WAREHOUSE
仓储物流



WK02-20/30 Table top banding machine 桌上型束带机



WK02-20/WK02-30

FEATURES 特性

Banding machines have been a cost and labor saving solution for many industries across the world, such as pharmacy, printing, graphic, dairy products, currency industries. This banding machine uses a heat sealing system to bond the material together to form a nice tidy seal around the item.

束带机为世界上许多行业节约成本和人力提供了解决方案,广泛应用于医药,印刷,银行等行业,纸带和膜带的热熔方式使得产品美观大方.



■ SPECIFICATION 技术参数

Model No 型号	WK02-20	WK02-30
Tape specification 带子规格	19.2-19.6mm W X 100-130MIC (Thickness)	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape	Opp film or Paper tape
Arch size 框架尺寸	470 X 200mm	470 x 200mm
Roll size 带卷规格	40MM Diameter X 150M L	40MM Diameter x 150M L
Banding size 打包尺寸	Max 460 X 200mm; Min30 X 10mm	Max 460 x 200mm;Min 30 x 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PCB	PCB
Banding speed 打包速度	25PCS/M	25PCS/M
Net weight 净重	32KG	32kg
Welding method 粘合方式	Heat sealing	Heating sealing
Banding tension 捆紧力	5-40N	5-40N
Outline size 外形尺寸	L621xW364xH474mm	L621xW364xH474mm

WK02-30B High table banding machine 高台束带机



WK02-30B



WK02-30B-60



■ SPECIFICATION 技术参数

Model No 型号	WK02-30B	WK02-30B-60
Tape specification 带子规格	29.2-29.6mm W X 100-130MIC (Thickness)	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape	Opp film or Paper tape
Arch size 框架尺寸	470 X 200mm	600 x 600mm
Roll size 带卷规格	40MM Diameter X 800M L	40MM Diameter x 800M L
Banding size 打包尺寸	Max 460 X 200mm; Min30 X 10mm	Max 600 x 600mm;Min 30 x 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PCB	PCB
Banding speed 打包速度	25PCS/M	25PCS/M
Net weight 净重	72KG	80kg
Welding method 粘合方式	Heat sealing	Heating sealing
Banding tension 捆紧力	5-40N	5-40N
Outline size 外形尺寸	L621xW430xH1214mm	L621xW430xH1214mm
Table height 台面高度	980mm(可定做850mm)	980mm(可定做850mm)

WK03/04-30 High speed banding machine 高速束带机

FEATURES 特性

1. Can use 60-80mu Plastic tape
2. with Pause function
3. High speed up to 31 bands/min
4. with counter
5. High tension
6. Touch screen control box
7. Precise tension adjustment
8. Step control to clear tape jam
9. Heat sealing
10. New arch guide design
11. photo eye on table top



可用60-80MU的膜带节约材料
带暂停功能、空打不会卡带
带计数器
加大拉紧力
速度快31条/分钟
PLC施耐德触摸屏控制
中空带槽设计、进带更顺



SPECIFICATION 技术参数

Model No 型号	WK03-30	WK04-30
Tape specification 带子规格	Plastic film: 29.4 mm W X80-100MIC (Thickness) Paper film: 29.4mm W x 80-120MIC(Thickness)	Plastic film: 29.4 mm W X60-100MIC (Thickness) Paper film: 29.4mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film , Paper tape,kraft paper	Opp film , Paper tape,kraft paper
Arch size 框架尺寸	430 X 200mm	430 X 200mm
Roll size 带卷规格	Plastic film: 40MM Diameter X 150-300M L Paper tape: 40MM diameter x 150-180M L	Plastic film: 40MM Diameter X 150-300M L Paper tape: 40MM diameter x 150-180M L
Banding size 打包尺寸	Max 420 X 200mm; Min30 X 10mm	Max 420 X 200mm; Min30 X 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase	220V/110V 50HZ/60HZ 1Phase
Control system 控制系统	PLC+Touch screen control	PLC+Touch screen control
Banding speed 打包速度	26PCS/M	33PCS/M
Net weight 净重	34KG	34KG
Welding method 粘合方式	Heat sealing	Heat sealing
Banding tension 捆紧力	5-40N	5-40N
Outline size 外形尺寸	L607xW347xH509mm	L607xW347xH509mm

WK04-30B High table banding machine 高台高速束带机

FEATURES 特性

1. Can use 60mu Plastic tape
2. with Pause function
3. High speed up to 33 bands/min
4. with counter
5. High tension
6. Touch screen control box
7. Precise tension adjustment
8. Step control to clear tape jam
9. Heat sealing
10. New arch guide design
11. photo eye on table top
12. Adjustable table height

可用60MU的膜带节约材料
带暂停功能、空打不会卡带
带计数器
加大拉紧力
速度快 33条/分
PLC 触摸屏控制
中空带槽设计、进带更顺
桌面高度可调



SPECIFICATION 技术参数

Model No 型号	WK04-30B
Tape specification 带子规格	Plastic film: 29.4 mm W X60-100 MIC (Thickness) Paper film: 29.4mm W x100-130MIC(Thickness)
Tape type 适用材料	Opp film , Paper tape,kraft paper
Arch size 框架尺寸	430 X 200mm
Roll size 带卷规格	Plastic film: 76MM Diameter X 1250M L Paper tape: 76 MM diameter x 500M L
Banding size 打包尺寸	Max 420 X 200mm; Min30 X 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase
Control system 控制系统	PLC+Touch screen control
Banding speed 打包速度	33 PCS/M
Net weight 净重	75 KG
Welding method 粘合方式	Heat sealing
Banding tension 捆紧力	5-40N

WK02-20ABS Automatic banding machine 在线式束带机



In-line model

FEATURES 特性

Photo eye or foot pedal operation
Digital screen control
Either paper or film tape can be used
Adjustable feeding tension and banding tension
Band package as small as 30 x 10mm and up to 460 x 200mm
Enter button to clear tape jam
Make 3 bands

可采用电眼或者脚踏开关操作
数码显示操作面板
纸带和膜带均可使用
送带力度和捆紧力度都可调整
可包装最小30*10MM, 最大460*200的物体
按ENTER 键就可清除卡带
可打3条带



■ SPECIFICATION 技术参数

Model No 型号	WK02-20ABS
Tape specification 带子规格	19.2-19.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape
Arch size 框架尺寸	470 x 200mm
Roll size 带卷规格	40MM Diameter x 500M L
Banding size 打包尺寸	Max 460 x 200mm; Min 30 x 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PLC
Banding speed 打包速度	20PCS/M
Net weight 净重	85KG
Welding method 粘合方式	Heating sealing
Banding tension 捆紧力	5-40N

WK02-30A Automatic banding machine 在线式束带机

In-line model

FEATURES 特性

Photo eye or foot pedal operation
Digital screen control
Either paper or film tape can be used
Adjustable feeding tension and banding tension
Band package as small as 30 x 10mm and up to 460 x 200mm
Enter button to clear tape jam

可采用电眼或者脚踏开关操作
数码显示操作面板
纸带和膜带均可使用
送带力度和捆紧力度都可调整
可包装最小30*10MM, 最大460*200的物体
按ENTER 键就可清除卡带



WK02-30A



WK02-30AB

■ SPECIFICATION 技术参数

Model No 型号	WK02-30A	WK02-30AB
Tape specification 带子规格	29.2-29.6mm W X 100-130MIC (Thickness)	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape	Opp film or Paper tape
Arch size 框架尺寸	470 X 200mm	470 x 200mm
Roll size 带卷规格	40MM Diameter X 150M L	40MM Diameter x 800M L
Banding size 打包尺寸	Max 460 X 200mm; Min 30 X 10mm	Max 460 x 200mm; Min 30 x 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PCB	PCB
Banding speed 打包速度	20PCS/M	20PCS/M
Net weight 净重	42KG	72kg
Welding method 粘合方式	Heat sealing	Heating sealing
Banding tension 捆紧力	5-40N	5-40N
Outline size 外形尺寸	L648xW525xH505mm	

GB-HD 250

20/30/40/50MM

Banding Machine 束带机

APPLICATION 应用

GB-HD 250 Banding Machine is specially designed for banding of all kind of small and sensitive products to bundles or stacks in the packaging field as well in the money handling field for banding of banknotes. The Bander is for use of PE-coated paper rolls (thermoband / craft paper) and PP film tape (polypropylene) without any changes. Banders are available for the widths of 20 mm, 30 mm, 40 mm and 50 mm. Banders with special widths will be manufactured on request.

GB-HD 250 束带机
专门设计用来打包各种小的和敏感的产品成捆或成堆
应用于包装领域和现金处理领域用来打包钞票
此束带机可使用没有任何更改的PE覆膜纸卷(牛皮纸)和PP膜带(聚丙烯)
此束带机适用于带宽20毫米, 30毫米, 40和50毫米
特殊的带宽可以根据要求定制

FEATURES 特性

Compact heavy duty design
Solid precise mechanical construction
Operation manually or automatically
Closing the band by heat sealing
Adjustable sealing temperature
Adjustable band guides depend to the product size
Adjustable band loop depend to the product size
Continuously adjustable banding tension
Foot switch (optional)

重型紧凑设计
机芯精确结实
手动或自动操作
热烫粘合
粘合温度可调
带轨可调根据产品尺寸
带圈可调根据产品尺寸
捆紧力可调
脚踏开关(可供选择)



GB-S 200

20/30/40MM

Banding Machine 束带机

APPLICATION 应用

GB-S 200 Banding Machine is specially designed for banding of all kind of small and sensitive products to bundles or stacks in the packaging field as well in the money handling field for banding of banknotes. The Bander is for use of PE-coated paper rolls (thermoband/craft paper) and PP film tape (polypropylene) without any changes. Banders are available for the widths of 20mm, 30mm and 40mm. Special widths will be manufactured on request.

GB-S 200 束带机
专门设计用来打包各种小的和敏感的产品成捆或成堆
应用于包装领域和现金处理领域用来打包钞票
此束带机可使用没有任何更改的PE覆膜纸卷(牛皮纸)和PP膜带(聚丙烯)
此束带机适用于带宽20毫米, 30毫米和40毫米
特殊的带宽可以根据要求定制

FEATURES 特性

Compact design
Solid precise mechanical construction
Operation manually or automatically
Closing the band by heat sealing
Adjustable sealing temperature
Adjustable band guides depend to the product size
Adjustable band loop depend to the product size
Continuously adjustable banding tension

结构紧凑
机芯结实精确
手动或自动操作
热烫粘合
粘合温度可调
带轨可调根据产品尺寸
带圈可调根据产品尺寸
捆紧力可调



SPECIFICATION 技术参数

Model No 型号	GB-S 200
Product dimension 产品尺寸	width 宽度 25 to 200 mm / height 高度 5 to 150 mm
Band guides adjustable between 带轨可调范围	120 to 200mm
Working speed 打包速度	25 bundles /min. (捆/分钟)
Power supply 电压	220V/230V 50HZ 200VA, 1 phase; 110V 60HZ, 180VA, 1 phase different power supply on request 不同的电压可以定制
Machine dimension L*W*H 机器尺寸长*宽*高	410X320X350 mm (including band guides)(包括带轨)
Machine weight 机器重量	24KG
GB-S 200 is in accordance with GB-S 200符合	EC-as well RoHS-Regulations CE和RoHS标准

WK02-30ABE

Straight line banding machine
一字流水束带线



■ SPECIFICATION 技术参数

Model No 型号	WK02-30ABE
Tape specification 带子规格	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape
Banding size 适用尺寸	100-150mm L x 60-150mm W x 20-150mm H
Roll size 带卷规格	40MM Diameter x 500M L
Table height 台面高度	950mm
Power supply 电压	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PLC
Banding speed 打包速度	21PACKS/M (50pcs/pack)
Net weight 净重	185KG
Welding method 粘合方式	Heating sealing
Air 气源	0.6-0.8kg
Banding tension 捆紧力	5-40N

WK02-30AM10

Pharmacy box banding machine
药盒翻包束带线



■ SPECIFICATION 技术参数

Model No 型号	WK02-30AM10
Tape specification 带子规格	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape
Banding size 适用尺寸	100-150mm L x 50-120mm W x 15-30mm H
Roll size 带卷规格	40MM Diameter x 500M L
Table height 台面高度	950mm
Power supply 电压	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PLC
Banding speed 打包速度	12PACKS/M
Net weight 净重	170KG
Welding method 粘合方式	Heating sealing
Air 气源	0.6-0.8kg
Banding tension 捆紧力	5-40N

WK02-30A4 Auto banding system for printing material 印刷业自动束带流水线



■ SPECIFICATION 技术参数

Model No 机器型号	WK02-30A4
Tape specification 带子规格	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 带子种类	Opp film, Paper tape, kraft paper
Arch size 框架尺寸	470 X 200mm
Roll size 带卷规格	40MM Diameter X 150-180M L
Banding size 束带尺寸	L 280-320mm x W 180-220mm x H </=100mm
Loading weight 承重	</=5kg
Power 功率	1000w
Power supply 电源	220V/110V 50HZ/60HZ 1Phase
Control system 控制系统	PLC+Touch screen control
Banding speed 束带速度	10PCS/M
Net weight 机器净重	280KG
Welding method 粘合方式	Heat sealing
Banding tension 捆紧力	5-40N
Machine dimension 机器尺寸	L 1500 x W1450 x H 1690mm

WK02-30-1032 Banding machine 大框架束带机

■ SPECIFICATION 技术参数

Model No 型号	WK02-30B-1032
Tape specification 带子规格	29.2-29.6mm W x 100-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape
Arch size 框架尺寸	1000 x 320mm
Roll size 带卷规格	40MM Diameter x 800M L
Banding size 打包尺寸	Max 1000 x 300mm; Min 30 x 10mm
Power supply 电压	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PCB
Banding speed 打包速度	20PCS/M
Net weight 净重	80kg
Welding method 粘合方式	Heating sealing
Banding tension 捆紧力	5-40N



WK02-30B-1032

WK02-DZ Banding machine dispenser 束带机储带桌

■ SPECIFICATION 技术参数

Model No 型号	WK-DZ01	WK-DZ02
Tape specification 带子规格	30mm W X 50-130MIC (Thickness)	30mm W x 50-130MIC(Thickness)
Tape type 适用材料	Opp film or Paper tape	Opp film or Paper tape
Table height 桌面高度	755mm	550-750mm adjustable
Roll size 带卷规格	76MM Diameter X 500-800M L	76MM Diameter x 800-1200M L
Connection 连接方式	Parallel connection 并联	Series connection 串联
Power supply 电压	220V/110V 50HZ/60HZ 1Phase	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PLC	PLC
Power 功率	60W	60W
Net weight 净重	40KG	45kg
Machine dimension 机器尺寸	614 x 430 x 755mm	614 x 430 x 550-750mm



WK-DZ01



WK-DZ02

TD-88 Semi-automatic strapping machine-2 DC motor

半自动打包机-双电机

New design



TD-88

FEATURES 特性

Two motors semi-automatic strapping machine is specially designed for soft industries. It uses PP strap to bond the item tightly. After insert strap to the guide, it will take only 2.0 seconds to finish strapping automatically. It can save your cost and labor. Strapping tension, strap length and heating temperature are adjustable from the control panel. It is very easy for operation and maintenance. No tape jam. Fixed length function.

瞬间加热:打开电源后5秒即可打包
可适用各种规格的PP带5-15MM 宽
节电功能:机器闲置运行马上自动断电,节约能源
结构简单,维护简单
能用薄带,窄带,节约耗材
热熔捆扎,粘合准确,牢固
不会卡带,定长功能



TD-88A

SPECIFICATION 技术参数

Model No 型号	TD88/TD-88A
Tape specification 带子规格	5-15mm W x 0.5-0.8mm
Tape type适用材料	PP strapping band
Power 功率	350W
Roll size 带卷规格	200mm Core X 40mm High
Strapping size 打包尺寸	Max:No limit; Min : 60 x 30mm
Power supply 电压	220V/110V 50HZ/60HZ 1Phase
Control system 控制系统	PCB
Strapping speed 打包速度	<= 2.5 seconds/strap
Net weight 净重	85KG/80KG
Welding method 粘合方式	Heat sealing
Strapping tension 捆紧力	1-500N
Outline size 外形尺寸	L785xW555xH750mm

TD-88 Semi-automatic strapping machine-2 DC motor

半自动打包机-双电机

New design

Two motors semi-automatic strapping machine is specially designed for soft industries. It uses PP strap to bond the item tightly. After insert strap to the guide, it will take only 2.0 seconds to finish strapping automatically. It can save your cost and labor. Strapping tension, strap length and heating temperature are adjustable from the control panel. It is very easy for operation and maintenance. No tape jam. Fixed length function.

瞬间加热:打开电源后5秒即可打包
可适用各种规格的PP带5-15MM 宽
节电功能:机器闲置运行马上自动断电,节约能源
结构简单,维护简单
能用薄带,窄带,节约耗材
热熔捆扎,粘合准确,牢固
不会卡带,定长功能



TD-88AL

SPECIFICATION 技术参数

Model No 型号	TD-88AL
Tape specification 带子规格	5-15mm W x 0.5-0.8mm
Tape type适用材料	PP strapping band
Power 功率	350W
Roll size 带卷规格	200mm core X 40mm high
Strapping size 打包尺寸	Max: No limit; Min: 60 x 30mm
Power supply 电压	220V/110V 50HZ/60HZ 1 Phase
Control system 控制系统	PCB
Strapping speed 打包速度	<= 2.5 seconds/strap
Net weight 净重	75kg
Welding method 粘合方式	Heating sealing
Strapping tension 捆紧力	1-500N
Outline size 外形尺寸	L1500xW555xH450mm

Q6000 Automatic strapping machine 全自动打包机

High speed up to 60 straps/min

FEATURES 特性

High speed automatic strapping machine can make 60 straps/min
Manual and Auto model operation
Loop ejecting function and refeed function
Rigid structure design
Built for 24 hours continuous operation
Tension adjustment: Very easy from control panel
Easy strap loading and unloading
Can be used for 5mm strap, save your cost
Use Germany Dunker motor DC 24V

一分钟可打60条带, 可选择自动或者手动模式, 设有跳带和二次送带功能, 不会卡带, 结构牢固, 美观大方, 可24小时连续工作, 从操作面板上即可调整捆紧力, 装和拆打包带卷都非常方便快捷, 可以用于5MM宽的打包带, 使用德国DUNKER电机



SPECIFICATION 技术参数

Model No 型号	Q6000
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W600XH400mm, W800XH500mm, W1000XH500mm, W1250XH500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PCB
Strapping speed 捆扎速度	60 straps/M
Strapping tension 捆紧力	50-300N
Net weight 净重	110kg

Q6000P Automatic strapping machine with press-top 高速加压全自动打包机

High speed up to 50 straps/min

FEATURES 特性

High speed automatic strapping machine can run 50 straps/min
Manual and Auto model operation
With auto feeding function
Rigid structure design
Heat sealing
Built for 24 hours continuous operation
Tension adjustment: Very easy from control panel
Easy strap loading and unloading
Can be used for 5mm strap, save your cost
Especially designed for corrugated industry

一分钟可打50条带, 可选择自动或者手动模式, 采用热熔方式粘带, 设有二次送带功能, 不会卡带, 结构牢固, 美观大方, 可24小时连续工作, 从操作面板上即可调整捆紧力, 装和拆打包带卷都非常方便快捷, 可以用于5MM宽的打包带, 节约耗材, 特别适用于纸箱生产企业



SPECIFICATION 技术参数

Model No 型号	Q6000P
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm inner core X 420mm external core X 190mm W
Power 功率	850N
Arch size 框架尺寸	W1000XH500mm - W1250XH500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PCB
Strapping speed 捆扎速度	50 straps/M
Strapping tension 捆紧力	5-300N
Net weight	400kg

Q6000A Automatic strapping machine with power roller 高速无人化全自动打包机

High speed up to 30 straps/min

FEATURES 特性

High speed automatic strapping machine can make 30 straps/min
Manual and Auto model operation
Loop ejecting function and refeed function
Rigid structure design
Built for 24 hours continuous operation
Tension adjustment: Very easy from control panel
Easy strap loading and unloading
Can be used for 5mm strap, save your cost
Use Germany Dunker motor DC 24V

一分钟可打30条带。可选择自动或者手动模式。设有跳带和二次送带功能。不会卡带。结构牢固。美观大方。可24小时连续工作。从操作面板上即可调整捆紧力。装和拆打包带都非常方便快捷。可以用于5MM宽的打包带。使用德国DUNKER电机。



SPECIFICATION 技术参数

Model No 型号	Q6000A
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W600XH400mm/W800XH500mm/W1000XH500mm /W1250XH500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	30 straps/M
Strapping tension 捆紧力	50-300N
Net weight	230kg

Q6000AD Automatic strapping machine with power roller 双带盘高速无人化全自动打包机

High speed up to 30 straps/min

FEATURES 特性

High speed automatic strapping machine can ran 30 straps/min
Manual and Auto model operation
With auto feeding function
Rigid structure design
Heat sealing
Built for 24 hours continuous operation
Tension adjustment: Very easy from control panel
Easy strap loading and unloading
Can be used for 5mm strap, save your cost
Especially designed for corrugated industry

一分钟可打30条带。可选择自动或者手动模式。采用热熔方式粘带。设有二次送带功能。不会卡带。结构牢固。美观大方。可24小时连续工作。从操作面板上即可调整捆紧力。装和拆打包带都非常方便快捷。可以用于5MM宽的打包带。节约耗材。特别适用于纸箱生产企业。



SPECIFICATION 技术参数

Model No 型号	Q6000AD
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm inner core X 420mm external core X 190mm W
Power 功率	850W
Arch size 框架尺寸	W800X500mm 、 W1000XH500mm、 W1250XH500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	30 straps/M
Strapping tension 捆紧力	
Net weight	400kg

Q6000AP Automatic strapping machine with press-top 高速加压全自动打包机

High speed up to 20 straps/min

FEATURES 特性

High speed automatic strapping machine can ran 50 straps/min
Manual and Auto model operation
With auto feeding function
Rigid structure design
Heat sealing
Built for 24 hours continuous operation
Tension adjustment: Very easy from control panel
Easy strap loading and unloading
Can be used for 5mm strap, save your cost
Especially designed for corrugated industry

一分钟可打50条带,可选择自动或者手动模式,采用热熔方式粘带,设有二次送带功能,不会卡带,结构牢固,美观大方,可24小时连续工作,从操作面板上即可调整捆紧力,装和拆打包带都非常方便快捷,可以用于5MM宽的打包带,节约耗材,特别适用于纸箱生产企业。



SPECIFICATION 技术参数

Model No 型号	Q6000AP
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm inner core X 420mm external core X 190mm W
Power 功率	840W
Arch size 框架尺寸	W1000X500mm/ W1250X500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	30 straps/M
Strapping tension 捆紧力	50-300N
Net weight	400kg

Q6000AP+XT-AF01 Automatic corrugate box squeezer 高速纸箱整列打包一体机

High speed up to 17 bundles/min

FEATURES 特性

High speed automatic strapping machine can make 30straps/min
With power roller table and press-top
With auto feeding
Heat sealing
Rigid structure design
Built for 24 hours continuous operation
Can use 5mm wide strap to save material
Easy strap loading and unloading

专门针对瓦楞纸打包而设计的全自动型打包机,同样也适用其它纸箱类的捆扎打包,该机最大特点是可以使用5mm宽的PP带,大大节省了企业的生产成本,该机工作台面配有动力辊筒,对打包物进行输送,可实现自动传动,自动检测,自动打包,同时具有上压功能,可将蓬松的纸捆进行压缩后捆包,从而使捆包物更加牢固结实。

纸箱整理流水线采用动力辊筒输送,气缸驱动的方式进行,自动对纸箱前后左右四个方位进行整理,并输送到打包机上,该机结构紧凑,功能完善,自动化程度高,操作及维修简单等优点,是纸箱厂家优选的一种产品。

SPECIFICATION 技术参数

Model No 型号	Q6000AP+XT-AF01
Material type 适用材料	PP strapping band
Strap size 带子规格	5mm/6mm/ 9mm/12mm W X0.35-0.65mm thickness
Roll size 带卷规格	200mm inner core X 420mm external core x 190mm W
Power 功率	1500W
Arch size 框架尺寸	W1000X500mm/ W1250X500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	17 bundles/M
Strapping tension 捆紧力	50-300N
Net weight	450kg

ZQ-06 Automatic strapping machine

快速全自动打包机

High speed up to 40 straps/min

FEATURES 特性

High speed automatic strapping machine can make 43 straps/min
Manual and Auto model operation
Rigid structure design
Tension adjustment: Very easy from control panel
220V single phase power, low noise

一分钟可打43条带,可选择自动或者手动模式,结构牢固,美观大方,
从操作面板上即可调整捆紧力,装和拆打包带卷都非常方便快捷。
220V 单相电,噪音低,二次进带功能



SPECIFICATION 技术参数

Model No 型号	ZQ-06
Material type 适用材料	PP strapping band
Strap size 带子规格	12mm X0.5-0.75mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 600 x H 500mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PCB
Strapping speed 捆扎速度	43 straps/M
Strapping tension 捆紧力	50-300N
Net weight	150kg
Outline size 外形尺寸	L1250xW600xH1400mm

ZQ-08 Automatic strapping machine

快速全自动打包机

High speed up to 40 straps/m

FEATURES 特性

High speed automatic strapping machine can make 40 straps/min
Manual and Auto model operation
Rigid structure design
Tension adjustment: Very easy from control panel
220V single phase power, low noise

一分钟可打40条带,可选择自动或者手动模式,结构牢固,美观大方,
从操作面板上即可调整捆紧力,装和拆打包带卷都非常方便快捷。
220V 单相电,噪音低,二次进带功能



SPECIFICATION 技术参数

Model No 型号	ZQ-08
Material type 适用材料	PP strapping band
Strap size 带子规格	12mm X0.5-0.75mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 800 x H 600mm
Power supply 电源	220V/110V 50HZ/60HZ
Control system 控制系统	PCB
Strapping speed 捆扎速度	40 straps/M
Strapping tension 捆紧力	50-300N
Net weight	180kg
Outline size 外形尺寸	L1450xW610xH1500mm

XT-201 Automatic strapping machine 全自动打包机

XT-201 Full Automatic Model 全自动

Model No 型号	XT-201
Material type 适用材料	PP strapping band
Strap size 带子规格	9mm/12mm/15mm X0.6-1.0mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 800 x H 600mm
Power supply 电源	380V/220V/50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	26 straps/M
Strapping tension 捆紧力	5-80kg
Net weight	210kg



XT-201Y Full Automatic Model 全自动

Model No 型号	XT-201Y
Material type 适用材料	PP strapping band
Strap size 带子规格	9mm/12mm/15mm X0.6-1.0mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 600 x H 800mm
Power supply 电源	380V/220V/50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	26 straps/M
Strapping tension 捆紧力	5-80kg
Net weight	210kg



XT-201A 无人化全自动打包机 Automatic strapping machine

XT-201A Full Automatic Model 全自动

Model No 型号	XT-201A
Material type 适用材料	PP strapping band
Strap size 带子规格	9mm/12mm/15mm X0.6-1.0mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 800 x H 600mm
Power supply 电源	380V/220V/50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	26 straps/M
Strapping tension 捆紧力	5-80kg
Net weight	315kg



XT-201AL Full Automatic Model 全自动

Model No 型号	XT-201AL
Material type 适用材料	PP strapping band
Strap size 带子规格	9mm/12mm/15mm X0.6-1.0mm
Roll size 带卷规格	200mm core X 400mm W
Power 功率	850W
Arch size 框架尺寸	W 800 x H 600mm
Power supply 电源	380V/220V/50HZ/60HZ
Control system 控制系统	PLC
Strapping speed 捆扎速度	26 straps/M
Strapping tension 捆紧力	5-80kg
Net weight	315kg



XT-4505 Pallet wrapper

自动托盘缠绕机

PLC control system,Go back to home position,Photo eye detect pallet height,5 Pre-set programs
Delay time setting to wrap overhead,Pre-stretch rate 200%, Front and rear forklift access points
Easy installation, just one person can do, Soft start and soft stop, Double tower chain
Top sheet function, Middle enforce function

PLC控制系统,自动归零位,电眼侦测包装高度,预存 5 套程序,越顶包装,预拉伸比250%,前后都备有叉车位
安装简单,一个人可组装,缓启动,缓停止,主柱双链条保护,覆顶功能中部加强功能



XT-4505-1



XT-4505-3

SPECIFICATION 技术参数

Model No 型号	XT-4505-1	XT-4505-3
Turntable diameter 转盘直径	1500mm (1200 x 800mm)	1500mm (1200 x 800mm)
Pallet height 托盘高度	700-2100mm	700-2100mm
Pallet weight 托盘重量	2000KG	2000KG
Turntable height 转盘高度	80mm	80mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC	PLC
Film carriage 膜架	Brake Tension 150%	Pre-stretch 250%
Turntable speed 转盘速度	0-12R/M	0-12R/M
Net weight 机器净重	400kg	450kg

XT-4550/4510

Robot pallet wrapper 机器人缠绕机 / 自走式缠绕机

Mobile robot for wrapping in less than one minute palletized loads of any shape, weight and dimension with stretch film.


Adjustable functions by control panel:
Top wrapping time cycle 0-9
Bottom wrapping cycle 0-9
Carriage ascent/descent speed adjustment
Robot rotation speed adjustment
Emergency Stop button
External plug for battery charger
Battery charge indicator
Acoustic/lighting signal
Max. rotation speed: 60m/min.
Charging loop count 350

采用拉伸缠绕机膜,适用于任何形状,任何重量,任何尺寸的托盘打包

可从操作面板上调整以下参数
顶部缠绕圈数,底部缠绕圈数,来回缠绕圈数
膜架上升下降的速度,机器人的行走速度
急停开关,暂停开关,电量显示
膜架出膜速度及张力从膜架上的旋钮调整
充电插头位于机器外部,方便对接
机器运转提示信号灯
最大行走速度60M/分钟
充电循环次数350



XT-4550



XT-4510

■ SPECIFICATION 技术参数

Model No 型号	XT-4550	XT-4510
Battery 电池	100AH(12V) x 2 pcs	100AH(12V) x 2 pcs
Pallet height 托盘高度	700-1900mm	700-2100mm
Pallet weight 托盘重量	Max: No limit, Min 100KG	Max: No limit, Min 100KG
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC	PLC
Film carriage 膜架	Pre-stretch 300%	Pre-stretch 300%
Charging time 充电时间	10-12 hours	10-12 hours
Running time 工作时间	10-12 hours	10-12 hours
Running time 工作速度	60M/Minute	60M/Minute


XT-4512 Forklift pallet wrapper 叉车缠绕机

We provide you a new solution for small pallet. With our forklift pallet wrapper, it becomes easier to move your pallets every where.

Adjustable functions by control panel:
Top wrapping time cycle 0-9
Bottom wrapping cycle 0-9
Carriage ascent/descent speed adjustment
Arm rotating speed adjustment
Emergency Stop button
External plug for battery charger
Battery charge indicator
Alarm lighting signal
Fork width: 155mm, forklift width: 530mm, fork length: 1500mm

为轻小托盘的缠绕打包和移动提供了二合一的解决方案。

可从操作面板上调整以下参数
顶部缠绕圈数,底部缠绕圈数,来回缠绕圈数
膜架上升下降的速度,机器人的行走速度
急停开关,暂停开关,电量显示
充电插头位于机器外部,方便对接
机器运转提示信号灯
叉板宽:155mm, 叉车宽:530mm, 叉板长:1500mm



■ SPECIFICATION 技术参数

Model No 型号	XT-4512
Battery 电池	20AH (12V) x 4 pcs
Pallet height 托盘高度	1600mm
Pallet weight 托盘重量	Max: 1500KG
Pallet size 托盘尺寸	1200 x 800mm or 1000 x 1000mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC
Film carriage 膜架	Brake
Charging time 充电时间	10-12hours
Running time 工作时间	10-12hours
Running speed 工作速度	12R/M

XT-4503 Pallet wrapper 自动缠绕机

PLC control system with more stable operation. Heavy duty design with rigid machine body.
Soft start and soft stop, safety device. After every wrapping working, turntable goes back to home position.
Photo cell detects pallet height. You can set delay time to get more overhead wrapping.
Faults display panel, it makes you an easier job for maintenance.
Front and rear forklift access points to move machine easily.

PLC 控制系统性能更稳定,操作简单,结实牢固的外观设计,经久耐用。
机器设有慢启动和慢停止,每次包装完成,转盘自动归零位。
电眼自动检测托盘高度,可以设定延迟时间以达到顶部包装。
故障显示板,可以轻松快速的发现机器故障位置,及时解决问题。
底座前后都设有叉车位,可以方便地移动机器。
客户尺寸可定制。



XT-4503-2



XT-4503A

■ SPECIFICATION 技术参数

Model No 型号	XT-4503-2	XT-4503A
Turntable diameter 转盘直径	1500mm	1500mm
Pallet height 托盘高度	700-2100mm	700-2100mm
Pallet weight 托盘重量	2000KG	2000KG
Turntable height 转盘高度	80mm	80mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC (Schneider)	PLC (Schneider)
Film carriage 膜架	Pre-stretch 300%	Pre-stretch 300%
Turntable speed 转盘速度	0-12R/M	0-12R/M
Net weight 机器净重	487kg	508kg

XT-4503 Pallet wrapper 自动缠绕机

PLC control system with more stable operation. Heavy duty design with rigid machine body.
Soft start and soft stop, safety device. After every wrapping working, turntable goes back to home position.
Photo cell detects pallet height. You can set delay time to get more overhead wrapping.
Faults display panel, it makes you an easier job for maintenance.

PLC 控制系统性能更稳定,操作简单,结实牢固的外观设计,经久耐用。
机器设有慢启动和慢停止,每次包装完成,转盘自动归零位。
电眼自动检测托盘高度,可以设定延迟时间以达到顶部包装。
故障显示板,可以轻松快速的发现机器故障位置,及时解决问题。

XT-4503M With M turntable M型底座缠绕机

Model No	XT-4503M
Turntable diameter 转盘直径	1500mm
Pallet height 托盘高度	700-2100mm
Pallet weight 托盘重量	1500KG
Turntable height 转盘高度	80mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC (Schneider)
Film carriage 膜架	Pre-stretch 300%
Turntable speed 转盘速度	0-12R/M



XT-4503S With Scale 带称缠绕机

Model No	XT-4503S
Turntable diameter 转盘直径	1500mm
Pallet height 托盘高度	700-2100mm
Pallet weight 托盘重量	2000KG
Turntable height 转盘高度	80mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Control system 控制系统	PLC (Schneider)
Film carriage 膜架	Pre-stretch 300%
Turntable speed 转盘速度	0-12R/M



XT-55 Semi-Automatic case sealer 半自动封箱机

Top and bottom driving belts & Side belts; 2 inch or 3 inch tape head, top overlap length width adjustable from 30-70mm; Tape holder, then tape won't fall anytime; Blade cover for safety purpose; Crank handle adjustment for height and width; Table height is adjustable from 580-780mm; Double tower screw to make a stronger machine; 120W strong motor is more durable and faster.

有上下皮带和左右皮带驱动的机型; 可选用2寸或者3寸的贴带器; 封箱的带尾长度可调: 30-70mm; 封箱胶带卡扣以防掉带; 手动把手调整封箱高度和宽度; 台面高度可调范围: 580-780mm; 双导杆结构; 机器可结实牢固; 电机功率120W, 更经久耐用, 提高了封箱速度

XT-551TB

Top&bottom belts
上下驱动

Model No型号	XT-551TB
Carton size 纸箱尺寸	L 170~ x W170-500 xH 150-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	120W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	128kg



XT-553RL

Side belts
左右驱动

Model No型号	XT-553RL
Carton size 纸箱尺寸	L 170~ x W120-500 xH 120-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	120W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	127kg



XT-55 Semi-Automatic case sealer 半自动封箱机

Top and bottom driving belts & Side belts; 2 inch or 3 inch tape head, top overlap length width adjustable from 30-70mm; Tape holder, then tape won't fall anytime; Blade cover for safety purpose; Crank handle adjustment for height and width; Table height is adjustable from 580-780mm; Double tower screw to make a stronger machine; 120W strong motor is more durable and faster.

有上下皮带和左右皮带驱动的机型; 可选用2寸或者3寸的贴带器; 封箱的带尾长度可调: 30-70mm; 封箱胶带卡扣以防掉带; 手动把手调整封箱高度和宽度; 台面高度可调范围: 580-780mm; 双导杆结构; 机器可结实牢固; 电机功率120W, 更经久耐用, 提高了封箱速度

XT-554TS

Top&Side belts
上加左右驱动

Model No型号	XT-554TS
Carton size 纸箱尺寸	L 170~ x W120-500 xH 120-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	120W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	141.5kg



XT-553TSBS

Top& bottom side belts
4驱封箱机

Model No型号	XT-553TSBS
Carton size 纸箱尺寸	L 170~ x W120-500 xH 200-800mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	120W x 4pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	128kg



XT-558 Flap close case sealer 折盖封箱机

XT-558FD Semi-auto fold case sealer 半自动折盖

Model No型号	XT-558FD
Carton size 纸箱尺寸	L 200-500 x W130-500 x H150-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	20M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 2pcs
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	200kg



XT-558AF Auto fold case sealer 全自动折盖

Model No型号	XT-558AF
Carton size 纸箱尺寸	L 200-500 x W130-500 x H150-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	20M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 2pcs
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	250kg



XT-553ARL Random case sealer 自动封箱机

Model No型号	XT-553ARL
Carton size 纸箱尺寸	L 170~ x W130-500 x H 130-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	120W x 2pcs
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	182kg



XT-55 Combination packaging machine 封箱打包一体机

XT-553RLL + XT201F

Combination packaging machine 封箱打包一体机

Model No型号	XT-553RLL+XT201F
Carton size 纸箱尺寸	L 200-600 x W150-500 xH 150-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	6 Cartons/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 马达功率	1000W
Tape width 胶带尺寸	2" or 3"
Strap size 带子规格	7mm/9mm/12mm x 0.45-1.0 mm
Net weight 净重	400kg



XT-558FDL + XT201F

Combination packaging machine 封箱打包一体机

Model No型号	XT-558FDL + XT 201F
Carton size 纸箱尺寸	L 200-600 x W150-500 xH 150-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	6 Cartons/min
Table height 台面高度	580-780mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 马达功率	1200W
Tape width 胶带尺寸	2" or 3"
Strap size 带子规格	7mm/9mm/12mm x 0.45-1.0 mm
Air 气源	0.6mpa
Net weight 净重	500kg



XT-556 Edge case sealer 角边封箱机

XT-556SC

Semi-auto
半自动型

Model No 型号	XT-556SC
Carton size 纸箱尺寸	L 320-500x W200-500 x H 180-500mm
Carton Weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	600-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 5pcs
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	450kg



XT-556AC

Auto model
全自动型

Model No 型号	XT-556AC
Carton size 纸箱尺寸	L 320-500x W200-500 x H 180-500mm
Carton weight 纸箱重量	1-40kg
Sealing speed 封箱速度	18M/min
Table height 台面高度	600-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 5pcs
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	500kg



XT-40 Carton erector 开箱机

Vertical storage, for which carton blanks can be added at any time without stopping the machine;
It's suitable for forming and sealing cartons of the uniform size. If carton size need to be changed,
the operator should adjust the machine manually(finishing in 2-3minutes);
It's rationally designed so that the forming, folding and sealing process are accomplished simultaneously;
All the parts are precise and durable, without causing any vibration in running. Running steadily with long life;
Light in weight, high performance and speed.

立式存箱,存量多,减少加箱时间,适用于统一规格的纸箱的成型工作.当纸箱尺寸有所调整时,需要人工手动调整.
只需2-3分钟,即可完成调整工作. 开箱的同时完成底部封箱.



Model No 型号	XT-40
Carton size 箱子尺寸	L 250-450x W 150-400 x H 100-400mm
Air Pressure 气压	0.6mpa
Working speed 开箱速度	12cartons/min
Table height 台面高度	600-720mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	200W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	450kg

XT-55 Combination case sealer 工字型封箱机

XT-553RL+XT-556SC

Model No型号	XT-553RL+XT-556SC
Carton size 纸箱尺寸	L 320-500 x W200-500 x H180-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	480-600pcs/hour
Table height 台面高度	500-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 功率	2000W
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	500kg



XT-553ARL+XT-556SC

Model No型号	XT-553ARL+XT-556SC
Carton size 纸箱尺寸	L 320-500 x W200-500 x H180-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	480-600pcs/hour
Table height 台面高度	500-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 功率	2000W
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	550kg



XT-55 Combination case sealer 工字型封箱机

XT-558F+XT-556SC

Model No型号	XT-558F+XT-556SC
Carton size 纸箱尺寸	L 320-500 x W200-500 x H180-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	300-360 cartons/hour
Table height 台面高度	500-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 功率	2000W
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	7300kg



XT-558AF+XT-556AC

Model No型号	XT-558AF+XT-556AC
Carton size 纸箱尺寸	L 320-500 x W200-500 x H180-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	300-360 cartons/hour
Table height 台面高度	500-750mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Power 功率	2500W
Tape width 胶带尺寸	2" or 3"
Air 气源	0.6mpa
Net weight 净重	750kg



XT-355 Heavy duty semi-auto Case Sealer 重型半自动封箱机

Top and bottom, driving belts & Side belts; 2 inch or 3 inch tape head, top overlap length width adjustable from 30-70mm; Tape holder, then tape won't fall anytime; Blade cover for safety purpose; Spring tower for soft packages; Table height is adjustable from 580-780mm; Double tower screw to make a stronger machine; 180W strong motor is more durable and faster.

有上下皮带和左右皮带驱动的机型; 可选用2寸或者3寸的贴带器; 封箱的带尾长度可调: 30-70mm; 封箱胶带卡扣, 以防弹带。台面高度可调范围: 580-780mm; 双立柱带弹簧结构, 可用于易碎物品的封箱机, 机器可结实牢固; 电机功率180W, 更经久耐用, 提高了封箱速度

XT-CTB355

Top&bottom belts 上下驱动

Model No型号	XT-CTB355
Carton size 纸箱尺寸	L 170~ x W170-500 xH 120-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	20M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	186kg



XT-CRL355

Side belts 左右驱动

Model No型号	XT-CRL355
Carton size 纸箱尺寸	L 170~ x W120-500 xH 130-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	20M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	185kg



XT-355 Random Case Sealer 重型自动封箱机

Top and bottom driving belts & Side belts; 2 inch or 3 inch tape head, top overlap length width adjustable from 30-70mm; Tape holder, then tape won't fall anytime; Blade cover for safety purpose; Crank handle adjustment for height and width; Table height is adjustable from 580-780mm; Double tower screw to make a stronger machine; 120W strong motor is more durable and faster.

左右皮带驱动; 可选用2寸或者3寸的贴带器; 封箱的带尾长度可调: 30-70mm; 封箱胶带卡扣, 以防弹带。气动自动调整封箱高度和宽度; 台面高度可调范围: 580-780mm; 双立柱结构, 机器更结实牢固; 电机功率180W, 更经久耐用, 提高了封箱速度



Model No型号	XT-CARL355
Carton size 纸箱尺寸	L 170~ x W110-500 xH 120-500mm
Carton weight 纸箱重量	1-50kg
Sealing speed 封箱速度	20M/min
Table height 台面高度	600-850mm
Power supply 电源	110V/220V 50HZ/60HZ 1PHASE
Motor power 马达功率	180W x 2pcs
Tape width 胶带尺寸	2" or 3"
Net weight 净重	310kg

3 in 1 Strapping tool 三合一打包工具

A333

Sealless steel strapping tool
免扣钢带打包机

Model No 型号	A333
Applicable strap 适用带子	Steel
Tape width 带宽	13/16/19mm
Tape thickness 带厚	0.38-0.58mm
Sealing type 粘合方式	Sealless 无扣
Strap tension 捆紧力	700-850N
Net weight 净重	3.9kg



AQD-19/AQD-25

Plastic Pneumatic strapping tool
塑钢带气动打包机

Model No 型号	AQD-19/AQD25
Applicable strap 适用带子	PP/PET
Tape width 带宽	13-19mm
Tape thickness 带厚	0.5-1.5mm
Sealing type 粘合方式	Friction 摩擦热熔
Strap tension 捆紧力	3000N
Net weight 净重	3.8kg



RJ-250

Plastic Pneumatic strapping tool
棉花气动打包机

Model No 型号	RJ-250
Applicable strap 适用带子	PP/PET
Tape width 带宽	13-19mm
Tape thickness 带厚	0.5-1.5mm
Sealing type 粘合方式	Friction 摩擦热熔
Strap tension 捆紧力	-
Net weight 净重	3.0kg



意大利 ITATOOLS PET塑钢带打包工具



ITA24.25



ITA21

机身轻、拉力强符合人体工学
“一键完成”全自动或半自动
束紧、黏接、切带
所有动作按一键完成

PET带

PET带

PP带

新一代锂电池、高效率、
无电池记忆效应、随时可充电!!

充电式PET带打包机

机型	ITA 20	ITA 21	ITA 24	ITA 25
适用带宽	PP 13 - 16 mm	PP 16 mm	PP 13 - 16 mm	PET 16 - 19 mm
	PET 13 - 16 mm	PET 16 - 19 mm	PET 13 - 16 mm	
适用带厚	0.5 - 1.05 mm	PP/PET 0.8 - 1.05 mm	0.6 - 1.0 mm	0.8 - 1.27 mm
		PET 0.7 - 1.27 mm		
尺寸规格				
长	290 mm	315 mm	300 mm	300 mm
宽	140 mm	140 mm	150 mm	150 mm
高	165 mm	183 mm	160 mm	160 mm
重量	3.6 Kgs	3.8 Kgs	3.9 Kgs	4.1 Kgs
电池	14.8V-2 A/h LI-PO	14.8V-3 A/h LI-PO	14.8V-2 A/h LI-PO	14.8V-3.2 A/h LI-PO
性能				
最大拉力	2200N	4000N	2500N	5500N
拉紧速度	9mt/m	12mt/m	16mt/m	12mt/m
黏合方式	摩擦熔接			
黏合强度	黏合强度达80%			

由于产品不断创新改进，产品之规格特性得以变更，恕不另行通知。本型录仅供参考。

充电器

电源：
110V-230V 50/60Hz 80W
输出电压：16V 5A



LI-PO锂电池

14.8V 2.0A/h
14.8V 3.0A/h



14.8V 3.2A/h

KZ Pneumatic steel strapping tool

气动钢带打包机

KZ-16/19

Pneumatic steel strapping tool

气动钢带打包机

Model No 型号	KZ-16/19
Applicable strap 适用带子	Steel
Air pressure 气压	0.42-0.6mpa
Tape size 钢带尺寸	16/19x0.8-1.2mm
Tension speed 收带速度	5.5M/min
Tension 捆紧力	4.9KN/0.6mpa
Seal tension 承受拉力	6.3KN
Net weight 净重	5kg

KZ-32/40

Pneumatic steel strapping tool

气动钢带打包机

Model No 型号	KZ-32/40
Applicable strap 适用带子	Steel
Air pressure 气压	0.42-0.6mpa
Tape size 钢带尺寸	32/40x0.8-1.2mm
Tension speed 收带速度	4.2M/min
Tension 捆紧力	9.8KN/0.6mpa
Seal tension 承受拉力	18.4KN
Net weight 净重	15kg

Widely applicable for paper packing, Aluminum, Steel, Wood plated and Bars, Pallets, Fiber fabrication, Cotton, Tobacco, Chemicals,

1. Heavy duty, special construction design, easily to tension & strap steel, aluminum blocks, heavy packing stuff.

2. Equipment with long life durance, whole tool & spare parts made from alloys with high strength, high durability, developed craft technology

1. 广泛用于纸业, 铝业, 钢铁业, 木业, 托盘业, 化纤业, 棉花业, 烟草业, 化工业

2. 坚固耐用, 整机铝合金制作。



Widely applicable for paper packing, Aluminum, Steel, Wood plated and Bars, Pallets, Fiber fabrication, Cotton, Tobacco, Chemicals,

1. Easy to use, light weight, high-power electric design.
2. Sealless, Friction welding design, with nice & reliable interface.
3. Automatic working model, tensioning & welding controllable.
4. 2 pieces Nica battery and one charger are included.
5. Heavy duty, special construction design, easily to tension & strap
6. steel, aluminum blocks, heavy packing stuff.
7. Equipment with long life durance, whole tool & spare parts made from
8. alloys with high strength, high durability, developed
9. Sealing time adjustable, LED scale display

操作简单体积小, 小电池容量大, 摩擦热熔粘合, 美观大方, 无须打包扣, 带自动操作模式, 控制收紧和粘合, 一机带二电一充, 粘合时间可调, LED显示刻度。



Manual strapping tools

手动打包工具

PP/PET Tensioner

拉紧器



Model No 型号	B340	B314	B330
Applicable strap 适用带子	Weaven	Weaven	PP/PET
Tape width 带宽	50mm	13-19mm	13-19mm
Tape thickness 带厚	0.5-1.5mm	0.5-1.5mm	0.5-1.5mm
Welding type 粘合方式	with buckle 带扣	with buckle 带扣	with buckle 带扣
Net weight 净重	2kg	1.35kg	1.35kg

PP/PET Sealer

PP/PET咬口钳



Model No 型号	C401	C310	C311	C312
Applicable strap 适用带子	PP/PET	PP/PET	PP/PET	PP/PET
Tape width 带宽	13mm	16mm	16mm	19mm
Tape thickness 带厚	0.6mm	0.6mm	0.8mm	0.6mm
Arm length 臂长	50cm	50cm	50cm	50cm
Net weight 净重	1.75kg	1.75kg	1.75kg	1.75kg

Dispenser
带盘车

P-200
PP strap dispenser
PP 带盘车

Model No 型号	P200
Applicable strap 适用带子	PP
Caster 脚轮	50mm
Tool box 工具箱	Yes
Strap roll core 带卷纸芯	200mm
Strap roll width 带卷宽度	200mm
Net weight 净重	35kg



S-191
Steel strap dispenser
钢带带盘车

Model No 型号	S-191
Applicable strap 适用带子	Steel
Caster 脚轮	50mm
Tool box 工具箱	Yes
Strap roll core 带卷纸芯	-
Strap roll width 带卷宽度	32mm
Net weight 净重	30kg



PET-406
PET/PP strap dispenser
PP/PET 带盘车

Model No 型号	PET-406
Applicable strap 适用带子	PET/PP
Caster 脚轮	50mm
Tool box 工具箱	Yes
Strap roll core 带卷纸芯	200mm/406MM
Strap roll width 带卷宽度	200mm
Net weight 净重	45kg



Welcome to join us!

