




Picture			
Model	HDA-160	HDA180	HDA-190
Speed	0-12 M/Min(Adjustable)	0-18 M/Min(Adjustable)	0-28 M/Min(Adjustable)
Sealing temperature	160-220℃(Adjustable)	90-150℃(Adjustable)	90-150℃(Adjustable)
Air volume	0-280L/Min(Adjustable)	0-300L/Min(Adjustable)	0-700L/MIN(Adjustable)
Net weight	4.95KG	11.6KG	16.5KG
Gross weight	6.2KG	14KG	20KG
Power	200W	320W	450W
Power supply	110/220V 50/60HZ 1PH	110/220V 50/60HZ 1PH	110/ 220V 50/60HZ 1PH
Machine dimension	L400*W145*H290MM	L400*W170*H290MM	L400*W570*H330MM
Package dimension	L495*W280*H360MM	L495*W430*H390MM	L505*W390*H430MM
Application Film	HDPE Film	HDPE film,PA(Nylon)Film	HDPE Film,PA(Nylon) film
Roll size	Core51mm*D220MM	Core51MM*D220MM	Core51MM*D220MM
Suitable film size	T20-40micron*W100-600MM	T20-40micron*W100-600MM	T20-40micron*W100-800MM
REMARK	Can not combine with rewinder,feeding system,cage etc	Can combine with rewinder,feeding system cage etc	Can combine with rewinder,feeding system cage etc

Film specification

Core	51MM	51MM	51MM
Thickness	20-40Micron	20-40Micron	20-40Micron
Width	600MM(MAX)	600MM(MAX)	800MM(MAX)
Diameter	220MM	220MM	220MM

