

BH-4S

Portable Multi-gas Detector for CO, O2 and CL2

FEATURES

- Advanced MCU for Low-Power Consumption
- LCD display
- Self-Test Function
- Adjustable alarms
- Two Instant Alarm Points
- Audio, Visual LED and Vibratory Indicators
- Three buttons Operation for Simple Use
- Strong, Durable Rubber Casing Provides Anti-Slip Handleability
- 500pcs alarming record data logger
- Can be connected with computer Module monitoring, Sensor setup, Alarm record
- Colorful LCD gas curve display
- Available for CO, O2,CL2
- Rechargeable
- Comply with ATEX

SPECIFICATIONS

Range:

O2: 0-30%vol

CO: 0-1000 ppm **CL2:**0-20 ppm

Alarm Point:

CO:50 and 150 ppm instant **CL2:** 5-10 ppm

O2: 19.5 by Vol. decreasing and 23.5% by Vol. increasing

Method of Detection:

 Diffusion

Sensor: CO, CL2 and O2-Electrochemical

Display: LCD

Temperature: -20℃~60℃

Humidity: 5 to 95% RH, non-condensing

Power: 3.7VDC 2000mA rechargeable lithium battery

Operating time: Approximately 15 hours Continuous, non-alarm conditions

Charge Time: Approximately 6 hours

Dimensions: 123mm*62mm*30mm

Sound: 85 dB at 1m

Weight: 210g

Ingress Protection: IP65

2014/10/11

Specifications subject to change without notice

Henan Bosean Electronic Technology Co.,Ltd. No.228,West 4th Ring,National High-Tech zone, Zhengzhou,China

Tel: 0086-0371-86533226

Email: sales@bosean.com

Website: www.bosean.com

