



www.premiercoatings.com

PRODUCT DATA SHEET

Headcorn Road · Smarden · Ashford · Kent · TN27 8PJ · United Kingdom
Telephone: + 44 (0) 1233 770 663 · Fax: + 44 (0) 1233 770 633
E-mail: enquiries@premiercoatings.com

PREMPASTE S105

DESCRIPTION Soft brown paste which may be applied underwater by gloved hand, stiff bristle brush or roller. A petrolatum based compound for the preparation of metal surfaces underwater prior to the application of Premier petrolatum tapes. It deposits a layer of protective compound onto the surface such that water is displaced and voids filled when the tape is applied.

COMPOSITION Soft petrolatum containing water displacing, corrosion inhibiting and flow control additives and broad spectrum bactericides. It contains no volatile organic components.

TYPICAL PROPERTIES	DATA
Solids Content	100%
Flash Point	>180°C
Specific Gravity	1.08
Specific Volume	925cc/kg
Coverage	2-5m ² /kg
Temperature Range <i>For Application</i> <i>For Service</i>	5°C to 40°C -25°C to 50°C

SURFACE PREPARATION	Surfaces should be free from mud, loose rust, scale, flaking coatings and marine growth.
----------------------------	--

PACKAGING	2.5kg pails and 25kg drums
------------------	----------------------------

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.