



RackStation RS3617xs+

Synology RackStation RS3617xs+ provides reliable, superior-performance network attached storage solution for large scale businesses with comprehensive business applications. With built-in 10GBase-T support and scalability of up to 36 drives, RS3617xs+ simplifies data management, optimizes virtualization environments, and rapidly expands storage capacity with minimal time investment in setup and maintenance. Synology RS3617xs+ is backed with Synology's 5-year limited warranty.

Highlights

- **Reliable, superior-performance for enterprises seeking uninterrupted service with comprehensive business applications.**
- **Intel Xeon D-1531 6-core CPU boosting performance at over 4,937 MB/s throughput and 556,727 IOPS¹**
- **Dual 10GBase-T ports and optional 10GbE NICs**
- **8GB DDR4 ECC UDIMM, expandable up to 64GB**
- **Scale up to 36 drives with Synology RX1217/RX1217RP**
- **Complete virtualization solution for VMware, Windows Hyper-V, and Citrix**
- **OpenStack Cinder support**
- **Advanced Btrfs file system offering 65,000 system-wide snapshots and 1,024 snapshots per shared folder**
- **Redundant power supplies ensure service uptime**
- **Backed with Synology's 5-year limited warranty & Synology Replacement Service (SRS)**

Blazing Performance

RS3617xs+ comes with **two 10GBase-T** and **four 1GbE RJ-45 ports** by default and allows installation of two optional 10GbE Network Interface Cards (NIC), bringing flexible network configuration and bandwidth utilization. With the help of a new **Intel® Xeon D-1531 6-core processor**, RS3617xs+ delivers blazing performance at over **4,937 MB/s sequential throughput** and **556,727 IOPS** under a RAID 5 configuration with 10GbE Link Aggregation enabled¹.

Equipped with **8GB DDR4 ECC UDIMM** and **up to 64GB expansion** support, RS3617xs+ ensures data accuracy as well as superior performance to provide a rigorous foundation for the mission-critical tasks of your business.

Btrfs: Next Generation Storage Efficiency

RS3617xs+ integrates the Btrfs file system, bringing the most advanced storage technologies to meet the management needs of modern large scale businesses:

- **Flexible Shared Folder/User Quota System** provides comprehensive quota control on all user accounts and shared folders.
- **Advanced snapshot technology** with customizable backup schedule allows up to **1,024** copies of shared folder backups and **65,000** copies of system-wide snapshots without occupying huge storage capacity and system resources.
- **File or folder level data restoration** brings huge convenience and saves time for users who wish to restore only the specific single file or folder.
- **Cloud Station with file versioning** reduces down to half of storage consumption when compared with ext4 file system.

Virtualization Ready

RS3617xs+ provides seamless storage solutions for virtualization environments, including **VMware, Citrix, Hyper-V, and OpenStack Cinder**. With **VMware vSphere 6 and VAAI** integration certified, RS3617xs+ helps offload specific storage operations and optimizes computation power for unparalleled performance and efficiency in VMware environments. As the centralized storage of a virtual environment, RS3617xs+ enables virtual machine migration, allowing movement from server to server whilst eliminating service downtime and disruption to user. **Windows Offloaded Data Transfer (ODX)** and **Synology Advanced LUN** support greatly improves the efficiency on massive data transfer and migration. With **OpenStack Cinder** support, RS3617xs+ can be used as a block-based storage component for servers complying with the Cinder API.



Reliability, Availability & Disaster Recovery

Synology High Availability ensures seamless transition between clustered servers in the event of server failure with minimal impact to businesses.

Comprehensive Business Applications

Powered by the innovative Synology DiskStation Manager (DSM), RS3617xs+ comes fully-equipped with applications and features designed specifically for large-scale business:

- Easy integration with existing business network environments through **Windows® AD** and **LDAP** directory services without recreating user accounts.
- **Windows ACL** support provides fine-grained access control and efficient privilege settings, allowing RS3617xs+ to fit seamlessly into current infrastructure.
- Built-in backup applications protect information assets by regularly backing up files and iSCSI LUNs locally and remotely.
- Continuous data protection with snapshots of shared folders allows restoration of previous versions when the need arises.
- Advanced Encryption Standard (AES) on shared folders with hardware acceleration ensures security without compromising access performance, providing over 2,612MB/s in reading.

Robust Scalability

RS3617xs+ is designed to grow with businesses and provides the ability to seamlessly expand a single volume up to **108TB** (default) / **200TB** (with at least 32GB RAM installed) on the fly.

RS3617xs+ supports up to 36 HDDs or SSDs for flexible capacity and balanced performance to meet the needs of varying applications and processes. When the storage capacity of RS3617xs+ nears its limit, expansion is easily accomplished with up to two **Synology Expansion Unit RX1217/RX1217RP²** via specially-designed connection cables to maximize data transmission throughput between main server and expansion units.

Management of the large storage space on RS3617xs+ is simple and flexible. Multiple Volumes on RAID allows users to create more than one volume on a RAID structure, providing a flexible and efficient way to manage the storage across all hard drives. When the need for more space arises, the volume could be easily expanded without any service disruption.


Reliability, Availability & Disaster Recovery

System reliability is of paramount importance to businesses which depend upon their commercial servers every day. RS3617xs+ responds to these concerns with wide-ranging availability and redundancy features:


- **Synology High Availability** ensures seamless transition between clustered servers in the event of server failure with minimal impact to applications.
- **Snapshot Replication** provides schedulable, near-instantaneous data protection, ensuring business documents in shared folders, virtual machines in iSCSI LUNs, or Docker DSM data remain safe and available in the event of disaster.
- **Redundant power supplies, system fans and network ports** with failover support ensure continual service uptime.
- High reliability system design including **fan-less CPU heat-sink** and passive cooling technology prevents single point of failure.
- **DDR4 ECC UDIMMs** reduces power consumption and detect and correct errors during data transmission.
- Tool-free system fan design allows hot swap and easy exchange of malfunctioned system fans.

Connections & Buttons

Front



Rear



| | | | | | | | |
|----|----------------------------|----|-----------------------------------|----|------------------------|----|----------------|
| 1 | Power button and indicator | 2 | Beep off button | 3 | Drive status indicator | 4 | Drive tray |
| 5 | Power port | 6 | PSU indicator and beep off button | 7 | PSU fan | 8 | Console port |
| 9 | 1GbE RJ-45 port | 10 | 10GbE RJ-45 (10GBase-T) port | 11 | USB 3.0 port | 12 | Expansion port |
| 13 | PCIe 3.0 slot | 14 | Reset button | | | | |

Technical Specifications

Hardware

| | |
|-------------------------------|--|
| CPU | Intel Xeon D-1531 six-core 2.2GHz burst up to 2.7GHz |
| Hardware encryption engine | Yes (AES-NI) |
| Memory | 8GB DDR4 ECC UDIMM (expandable up to 64GB) |
| Compatible drive type | 12 x 3.5" or 2.5" SATA (hard drives not included) |
| Maximum internal raw capacity | 168TB (12 x 14TB HDD) ¹ (The actual capacity will differ according to volume types) |
| External ports | USB 3.0 x 2, Expansion port (Infiniband) x 2 |
| Size (HxWxD) | 88 mm x 430.5 mm x 692 mm |
| Weight | 14.5 kg |
| LAN | 10GbE RJ-45 (10GBase-T) x 2, 1GbE RJ-45 x 4 |
| PCIe 3.0 x8 slot | Two running at x8 mode, supports two dual-port 10GbE network interface cards |
| Wake on LAN/WAN | Yes |
| Wireless support (dongle) | Yes |
| AC input power voltage | 100V to 240V AC |
| Power frequency | 50 / 60Hz, single phase |
| Operating temperature | 5 to 35°C (40 to 95°F) |
| Storage temperature | -20 to 60°C (-5 to 140°F) |
| Relative humidity | 5% to 95% RH |

General

| | |
|-------------------------|--|
| Networking protocols | SMB, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN ² , L2TP) |
| File system | Internal: Btrfs, ext4 External: Btrfs, ext4, ext3, FAT, NTFS, HFS+, exFAT ³ |
| Storage management | Maximum single volume size: 108TB/200TB (at least 32GB RAM required, for RAID 5 or RAID 6 groups only); maximum internal volume: 1,024, maximum iSCSI target: 128, maximum iSCSI LUN: 512, RAID clone/snapshot support; Synology Expansion Unit support: RX1217/RX1217RP |
| Supported RAID type | Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10 |
| File sharing capability | Maximum user account: 16,000; maximum group: 512; maximum shared folder: 512; maximum concurrent SMB/AFP/FTP/File Station connections : 2,048 |
| Privilege | Windows Access Control List (ACL) |
| Virtualization ready | VMware vSphere 6, Microsoft Hyper-V, Citrix, OpenStack Cinder |
| Directory service | Windows AD integration: Domain Users login via Samba (SMB)/AFP/FTP/File Station, LDAP integration |
| Security | FTP over SSL/TLS, IP auto-block, firewall, encrypted network backup over Rsync, HTTPS connection |
| Utilities | Synology Web Assistant, Cloud Station Drive, Cloud Station Backup, Cloud Sync Decryption Tool, Evidence Integrity Authenticator, Photo Station Uploader, Snapshot Manager for VMware, Snapshot Manager for Windows, NFS Plug-in for VMware VAAI |
| Supported clients | Windows 7 onwards and Mac OS X ⁴ 10.10 onwards |
| Supported browsers | Chrome ⁵ , Firefox ⁶ , Internet Explorer ⁷ 9 onwards, Safari ⁸ 8 onwards, Safari (iOS ⁹ 7 onwards on iPad ¹⁰), Chrome (Android 4.0 onwards on tablets) |
| Language | English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Česky, 日本語, 한국어, 繁體中文, 简体中文 |

Applications

| | |
|-----------------------------|---|
| File Station | Virtual drive, remote folder, Windows ACL editor, compress/extract archived files, bandwidth control for specific users or groups, create sharing links, transfer logs |
| Backup solutions | Network backup; local backup; desktop backup; configuration backup; OS X Time Machine; backup data to public cloud; shared folder sync - maximum task number: 32 |
| FTP Server | Bandwidth control for TCP connections, custom FTP passive port range, anonymous FTP, FTP SSL/TLS and SFTP protocols, boot over the network with TFTP and PXE support, transfer logs |
| High Availability Manager | Combines two RS3617xs+ into one high-availability cluster |
| Security Advisor | Malware detection/removal, user account/password, network, system-related security scan |
| iOS/Android™ applications | DS cloud, DS file, DS finder, DS cam, DS note, DS audio, DS get, DS photo, DS video |
| Windows Phone® applications | DS file, DS finder, DS audio, DS get, DS photo, DS video |

Add-on Packages

| | |
|-------------------------|---|
| Antivirus Essential | Full system scan, scheduled scan, white list customization, virus definition auto update |
| Cloud Station Server | Maximum concurrent file transfers: 2,000, retain historical and deleted file versions |
| Cloud Sync | One or two-way synchronization with public cloud storage providers including Amazon Cloud Drive, Amazon S3-compatible storage, Baiduyun, Box, Dropbox, Google Cloud Storage, Google Drive, hubiC, Megafon Disk, Microsoft OneDrive, OpenStack Swift-compatible storage, WebDAV servers, Yandex Disk |
| DLNA/UPnP® Media Server | DLNA certified, PS3®/PS4®/Xbox 360®/Xbox One® support |
| Download Station | Supported download protocols: BT/HTTP/FTP/NZB/eMule; Maximum concurrent download task: 80 |
| Log Center | SSL connection, log rotation: 6 months, 1 year, 2 years, 3 years, email notification |
| MailPlus | Intuitive webmail interface for MailPlus Server; customizable mail labels, filters and user interface |
| MailPlus Server | Secure, reliable, and private mail server solution with High-availability, load balancing, security and filtering design (Including free MailPlus licenses for 5 mail accounts. Procurement of additional licenses is required.) |
| Note Station | Rich-text note organization with versioning, encryption, sharing, media embedding and attachments |
| Storage Analyzer | Volume and quota usage, total size of files, volume usage and trends based on past usage, size of shared folders, largest/most/least frequently modified files |
| Surveillance Station | Maximum IP camera: 90 (total of 2,700 FPS at 720p, H.264) (Including two free camera licenses. Procurement of additional licenses is required.) |
| VPN Server | Maximum connections: 30; supported VPN protocols: PPTP, OpenVPN™, L2TP |
| Web Station | Virtual host (up to 30 websites), PHP/MariaDB®, 3rd-party applications support |
| Other packages | Photo Station, Audio Station, iTunes® Server, 3rd-party packages |

Environment and Packaging

| | |
|----------------------|--|
| Environment | RoHS compliant |
| Package content | RS3617xs+ main unit, Quick Installation Guide, accessory pack, AC power cord x 2 |
| Optional accessories | Camera License Pack, VS360HD, Synology RKS1317 - Rail Kit Sliding, 8GB and 16GB DDR4-2133 ECC UDIMM module, Synology Expansion Unit (RX1217/RX1217RP x 2), 10Gbps Ethernet adapter E10G17-F2 / E10G15-F1 |
| Certification | FCC: Class A, CE: Class A, BSMI: Class A |
| Warranty | 5 years ⁵ |

*Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

1. Performance figures may vary depending on environment, usage and configuration.
2. RS3617xs+ supports up to 2 Synology Expansion Unit RX1217/RX1217RP, sold separately.
3. exFAT Access is purchased separately in Package Center.
4. The maximum internal raw capacity is subject to change based on the capacity of the newest drive that RS3617xs+ supports. Please refer to www.synology.com for the latest information.
5. The warranty period starts from the purchase date as stated on your purchase receipt. Visit <http://www.synology.com> for more information.

SYNOLOGY INC.

Synology is dedicated to taking full advantage of the latest technologies to bring businesses and home users reliable and affordable ways to centralize data storage, simplify data backup, share and sync files across different platforms, and access data on-the-go. Synology aims to deliver products with forward-thinking features and the best in class customer services.

Copyright© 2019, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan.

RS3617xs+-2019-ENU-REV004

Headquarters

Synology Inc. 9F., No.1, Yuandong Rd., Banqiao Dist., New Taipei City 220, Taiwan Tel: +886 2 2955 1814 Fax: +886 2 2955 1884

China

Synology Shanghai

200070, Room 201, No. 511 Tianmu W.
Rd., Jingan Dist. Shanghai, China

France

Synology France SARL

102 Terrasse Boieldieu (TOUR W)
92800 Puteaux, France
Tel: +33 147 176288

North & South America

Synology America Corp.

3535 Factoria Blvd SE #200 Bellevue,
WA98006, USA
Tel: +1 425 818 1587

United Kingdom

Synology UK Ltd.

Unit 5 Danbury Court, Linford Wood,
Milton Keynes, MK14 6PL, United Kingdom

Germany

Synology GmbH

Grafenberger Allee 125 40237 Düsseldorf
Deutschland
Tel: +49 211 9666 9666

Japan

Synology Japan Co., Ltd

4F, 3-1-2, Higashikanda, Chiyoda-ku,
Tokyo, 101-0031, Japan