

# Temp Facestation BTF-201

Temperature Detection Face Recognition  
Access Control & Time Attendance



Long range  
detection



Visible Light Facial  
Recognition



Live face detection



Touch screen



4.3" Capacitive LCD



200W Pixel



ID Card



WiFi &T



Infrared Precise  
Temperature  
Detection



Multiple Mode for face  
registration



Fast Live body  
Detection



Time Attendance and  
Access Control

## 4.3 inch touchable LCD display

4.3 inch touchable LCD display, real-time face show in prompt box, easy for user calibration.



Attendance report  
download by  
USB flash driver



## Specifications TF-201 :

|                                    |   |
|------------------------------------|---|
| CPU                                | 4 cores 1.2G  |
| Temperature detection distance     | 0.5 meter   |
| Temperature detection error        | 0.5°C   |
| Temperature detection minimum unit | 0.1°C   |
| RAM                                | 1G  |
| ROM                                | 8G  |
| Camera                             | 200W Pixel hd color camera, 100W Infrared camera                      |
| LED                                | LED Double high power infrared light                                  |
| Display                            | 4.3" Capacitive LCD touch screen                                      |
| Resolution                         | 800*480   |
| Communication                      | TCP/IP, USB type-A, WIFI  |
| FRR                                | ≤0.1%   |
| FAR                                | ≤0.001%   |
| Power supply                       | DC 12V, 2A  |
| Operating temperature              | -15°C - 60°C  |
| Operating system                   | LINUX   |
| Language                           | Chinese, English, Spanish, French, Turkish, Thai, Indonesian and more |
| User capacity                      | 10000   |
| Record Capacity                    | 1,000,000   |
| Identification style               | Visible Light Facial Recognition, PIN, ID, face & PIN combination     |
| Identification Mode                | 1:1, 1:N  |
| Recognition                        | Name recognition, work number recognition                             |
| Face recognition time              | <0.2S   |
| Intelligent function               | Live face detection   |
| Detection rang                     | 0.5-3m  |
| Magnetic door                      | support   |
| Alarm output                       | 1 set   |
| WG                                 | 1 set WG In, out  |
| Dimension                          | 184mm*113mm*20mm  |

Contact Us :

PT. BIMA UTAMA SUKSES MANDIRI Graha Prima

Blok CA No.6 Mangunjaya Tambun Selatan

Bekasi

Tlpn : 021-88326147 / 08119326699

HP.08129396152