Version 2.0	Revision Date 2016/06/14	Print Date 2016/06/15
1. IDENTIFICATION OF THE HAZARDOUS CHEMICALS AND OF THE SUPPLIER		
Product name	: Shell Omala S4 GX 220	
Product code	: 001D7851	
Manufacturer or supplier's Supplier Telephone Telefax	details Shell Malaysia Trading Sdn Bhd (6087-M) Menara Shell No. 211 Jalan Tun Sambanthan 50470 Kuala Lumpur Malaysia (+60) 3 2385 2888 :	
Emergency telephone number Email Contact for Safety Data Sheet	 1 800 88 3899 If you have any enquiries about th please email lubricantSDS@shell. 	
Recommended use of the c Recommended use	hemical and restrictions on use : Gear lubricant.	
Recommended use		

2. HAZARDS IDENTIFICATION

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	: Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

Version 2.0

Revision Date 2016/06/14

Print Date 2016/06/15

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL

Chemical nature : Blend of polyolefins and additives.

Hazardous components

4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under norm conditions.	nal
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.	
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.	
If swallowed	: In general no treatment is necessary unless large quantitie are swallowed, however, get medical advice.	S
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include format of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.	
Protection of first-aiders	: When administering first aid, ensure that you are wearing t appropriate personal protective equipment according to the incident, injury and surroundings.	
Notes to physician	: Treat symptomatically.	

5. FIRE-FIGHTING MEASURES

Version 2.0		Revision Date 2016/06/14	Print Date 2016/06/15
		dioxide, sand or earth may be used fo	r small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.	
Specific hazards during firefighting	:	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. 	
Specific extinguishing methods	:	Use extinguishing measures that are a circumstances and the surrounding er	
Special protective equipment for firefighters	:	Proper protective equipment including gloves are to be worn; chemical resist large contact with spilled product is ex Breathing Apparatus must be worn wh a confined space. Select fire fighter's of relevant Standards (e.g. Europe: EN4	ant suit is indicated if pected. Self-Contained nen approaching a fire in clothing approved to
Hazchem Code	:	NONE/TIADA	
6. ACCIDENTAL RELEASE MEAS	SUF	RES	
Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.	
emergency procedures Environmental precautions	:	Use appropriate containment to avoid	
		contamination. Prevent from spreading ditches or rivers by using sand, earth, barriers.	g or entering drains,
		contamination. Prevent from spreading ditches or rivers by using sand, earth,	g or entering drains, or other appropriate
Methods and materials for containment and cleaning up	:	contamination. Prevent from spreading ditches or rivers by using sand, earth, barriers. Local authorities should be advised if	g or entering drains, or other appropriate significant spillages clean up immediately. parrier with sand, earth ent. ch as clay, sand or other

7. HANDLING AND STORAGE

Version 2.0	Revision Date 2016/06/14	Print Date 2016/06/15
Handling		
General Precautions	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.	
Advice on safe handling	: Avoid prolonged or repeated contac Avoid inhaling vapour and/or mists. When handling product in drums, so worn and proper handling equipmen Properly dispose of any contaminat materials in order to prevent fires.	afety footwear should be nt should be
Avoidance of contact	: Strong oxidising agents.	
Product Transfer	: This material has the potential to be Proper grounding and bonding prod during all bulk transfer operations.	
Storage		
Other data	: Keep container tightly closed and ir place. Use properly labeled and closable of	
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers or steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not temperatures because of possible r	

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or

contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

Version 2.0	Revision Date 2016/06/14 Print Date 2016/06	
http://www.osha.gov/ Health and Safety Executive http://www.hse.gov.uk/ Institut für Arbeitsschutz Deu http://www.dguv.de/inhalt/ind	ealth Administration (OSHA), USA: Samp e (HSE), UK: Methods for the Determina utschen Gesetzlichen Unfallversicherun dex.jsp rche et de Securité, (INRS), France http	tion of Hazardous Substances g (IFA) , Germany
<section-header></section-header>	 The level of protection and types vary depending upon potential ex controls based on a risk assessm Appropriate measures include: Adequate ventilation to control air Where material is heated, spraye greater potential for airborne cond General Information: Define procedures for safe handli controls. Educate and train workers in the measures relevant to normal activ product. Ensure appropriate selection, tes equipment used to control expose equipment, local exhaust ventilati Drain down system prior to equip maintenance. Retain drain downs in sealed stor subsequent recycle. Always observe good personal hy washing hands after handling the drinking, and/or smoking. Routin protective equipment to remove of contaminated clothing and footwe Practice good housekeeping. 	 kposure conditions. Select hent of local circumstances. rborne concentrations. ed or mist formed, there is centrations to be generated. ing and maintenance of hazards and control vities associated with this ting and maintenance of ure, e.g. personal protective ion. ment break-in or rage pending disposal or ygiene measures, such as material and before eating, ely wash work clothing and contaminants. Discard

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an

sion 2.0	Revision Date 2016/06/14	Print Date 2016/06/15
	appropriate combination of mask a Select a filter suitable for the comb and vapours [Type A/Type P boili	pination of organic gases
Hand protection		
Remarks	: Where hand contact with the prod gloves approved to relevant stand US: F739) made from the following suitable chemical protection. PVC gloves Suitability and durability of usage, e.g. frequency and duration resistance of glove material, dexter from glove suppliers. Contaminate replaced. Personal hygiene is a ke care. Gloves must only be worn of gloves, hands should be washed a Application of a non-perfumed mo	ards (e.g. Europe: EN374, g materials may provide , neoprene or nitrile rubber a glove is dependent on n of contact, chemical erity. Always seek advice ed gloves should be ey element of effective hand n clean hands. After using and dried thoroughly.
	For continuous contact we recomme breakthrough time of more than 24 for > 480 minutes where suitable of short-term/splash protection we re- recognize that suitable gloves offer may not be available and in this ca- time maybe acceptable so long as and replacement regimes are follor a good predictor of glove resistant dependent on the exact compositi Glove thickness should be typicall depending on the glove make and	40 minutes with preference gloves can be identified. For commend the same, but string this level of protection ase a lower breakthrough appropriate maintenance wed. Glove thickness is not be to a chemical as it is on of the glove material. y greater than 0.35 mm
Eye protection	: If material is handled such that it c protective eyewear is recommend	
Skin and body protection	: Skin protection is not ordinarily red work clothes. It is good practice to wear chemica	
Thermal hazards	: Not applicable	
Environmental exposure c	ontrols	
General advice	: Take appropriate measures to fulf	ill the requirements of

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

Version 2.0	Revision Date 2016/	06/14 Print Date 2016/06/15
9. PHYSICAL AND CHEMICAL PR	PERTIES	
Appearance	: Liquid at room tempe	erature.
Colour	amber	
Odour	Slight hydrocarbon	
Odour Threshold	Data not available	
рН	Not applicable	
pour point	: -45 °C / -49 °FMetho	d: ISO 3016
Initial boiling point and boiling range	: >280 °C / 536 °Festi	mated value(s)
Flash point	: 250 °C / 482 °F Method: ISO 2592	
Evaporation rate	Data not available	
Flammability (solid, gas)	Data not available	
Upper explosion limit	Typical 10 %(V)	
Lower explosion limit	Typical 1 %(V)	
Vapour pressure	<pre>c < 0.5 Pa (20 °C / 68 ' estimated value(s)</pre>	°F)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.881 (15 °C / 59 °F)	
Density	: 881 kg/m3 (15.0 °C / Method: ISO 12185	59.0 °F)
Solubility(ies)		
Water solubility	negligible	
Solubility in other solvents	Data not available	
Partition coefficient: n- octanol/water	: Pow: > 6(based on ir	nformation on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Viscosity		
Viscosity, dynamic	Data not available	
Viscosity, kinematic	230 mm2/s (40 °C / 1 Method: ASTM D445	

Version 2.0	Revision Date 2016/06/14	Print Date 2016/06/15
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be	a static accumulator.
Decomposition temperature	: Data not available	

10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

11. TOXICOLOGICAL INFORMATION

	Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
	Symptoms of Overexposure	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
	Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity			
	Product:		
	Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low toxicity:
	Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
_	Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Version 2.0

Revision Date 2016/06/14

Print Date 2016/06/15

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Version 2.0 Aspiration toxicity Revision Date 2016/06/14

Print Date 2016/06/15

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. ECOLOGICAL INFORMATION					
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). 				
Ecotoxicity					
Product:					
Toxicity to fish (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l				
Toxicity to crustacean (Acu toxicity)	 Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l 				
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l				
Toxicity to fish (Chronic	: Remarks: Data not available				
toxicity) Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available				
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available				

Persistence and degradability

Product:

Version 2.0	Revision Date 2016/06/14 Print Date 2016/06/15	
Biodegradability	 Remarks: Expected to be not readily biodegradable., Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment. 	
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.	
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on information on similar products)	
Mobility in soil		
Product:		
Mobility	 Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water. 	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities., Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential. Poorly soluble mixture., May cause physical fouling of aquatic organisms. 	
13 DISPOSAL INFORMATION		
Disposal methods		
Waste from residues	: Waste product should not be allowed to contaminate soil or	
Waste nom residues	ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.	

Disposal should be in accordance with applicable regional,
national, and local laws and regulations.
Local regulations may be more stringent than regional or
national requirements and must be complied with.Contaminated packaging: Dispose in accordance with prevailing regulations, preferably
to a recognized collector or contractor. The competence of
the collector or contractor should be established beforehand.
Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Version 2.0	Revision Date 2016/06/14	Print Date 2016/06/15				
14. TRANSPORTATION INFORM	14. TRANSPORTATION INFORMATION					
National Regulations						
Hazchem Code	: NONE/TIADA					
International Regulation						
ADR Not regulated as a dangerous good						
IATA-DGR Not regulated as a dangerou	IATA-DGR Not regulated as a dangerous good					
IMDG-Code Not regulated as a dangerous good						
Transport in bulk according to	Annex II of MARPOL 73/78 and the IBC	C Code				
Pollution category Ship type Product name Special precautions	 Not applicable Not applicable Not applicable Not applicable Not applicable 					
Special precautions for user						
Remarks	: Special Precautions: Refer to Cha for special precautions which a use needs to comply with in connection	er needs to be aware of or				
Additional Information	: MARPOL Annex 1 rules apply for I	oulk shipments by sea.				

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

OSHA 1994 and relevant regulations.

Factories and Machinery Act 1967 and relevant regulations.

Petroleum (Safety Measures) Act 1984.

Environmental Quality Act 1974 and regulation.

Motor Vehicles (Construction and Use) (Vehicles Carrying Petroleum Products) Rules, 1965-L.N.405/65 under Road Transport Act 1987.

Motor Vehicles (Construction, Equipment and Use) (Use Of Liquefied Petroleum Gas Fuel System in Motor Vehicles) Rules 1982 – P.U. (A) 392/82 under Road Transport Act, 1987.

Other international regulations

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

Version 2.0 16. OTHER INFORMATION	Revision Date 2016/06/14	Print Date 2016/06/15
Abbreviations and Acronyms	: The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.	
Further information		
Other information	: A vertical bar () in the left margin from the previous version.	indicates an amendment
	There has been a significant chan information in section 2 & 3.	ge in compositional

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.