


# JP series

## Price Computing Scale



### ELECTRICITY USE

- Low electricity (One-time charging up to 30 days, '8 hours a day')
- Can be applied PB (charger) with Mn (battery)
- D size x 3 units (to be additionally purchased)
- Backlight color "WHITE"



### STRUCTURE

- Robust structure



### PACKAGE

- Standing-type for loading (Protect multiple layers from load cell shock)
- All-in-one handle package
- 5 ea x 1 Out box



### PRODUCT LINE UP

#### JP1



LCD Type



LED Type

#### JP2



LCD Type



LED Type

### SPECIFICATIONS

Model	JP1			JP2		
	6 kg	15 kg	30 kg	6 kg	15 kg	30 kg
Capacity	2 g	5 g	10 g	2 g	5 g	10 g
	5/5/6 (Weight/Unit/Total)					
Display	5/5/6 (Weight/Unit/Total)					
MaximumTare	Full tare					
Temperature	-5°C - 35°C					
Power	AC cord 220V			DC 8V Adaptor or Battery		
Battery charging time	-			12 hours		
Battery working hour	-			240 hours		
Plattersize(mm)	330(W) x 230(D)			330(W) x 230(D)		
Productsize(mm)	335(W) x 335(D) x 105(H)			320(W) x 360(D) x 110(H)		
Productweight(kg)	3.2			3.2		



CAS BLDG., 1315, YANGJAE-DAERO,  
GANGDONG-GU, SEOUL, KOREA

TEL\_ 82 2 2225 3500

FAX\_ 82 2 475 4668

Specifications are subject to change without notice improvement



# CAS

<http://www.globalcas.com>