



CCTV SYSTEM

8-CH NVR (NETWORK VIDEO RECORDER)

WN802



FEATURES

- 8-channel input
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K (3840x2160) resolution
- Up to 8 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- Up to 8TB for each disk
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access

SPECIFICATION

Model	WN802
Video/ Audio Input	
IP Video Input	8-Ch
Two way Audio Input	1-Ch, RCA
Network	
Incoming bandwidth	48Mbps
Outgoing bandwidth	48Mbps
Remote Users	128
Video/ Audio Output	
HDMI/ VGA Output	HDMI: 4K (3840 x 2160) /30Hz, 1920 x 1080p/ 60Hz, 1920x1080p/ 50Hz, 1600 x 1200/ 60Hz, 1280 x 1024/60Hz, 1280 x 720/ 60Hz, 1024 x 768/ 60Hz VGA: 1920 x 1080p/ 60Hz, 1920 x 1080p/ 50Hz, 1600 x 1200/ 60Hz, 1280 x 1024/ 60Hz, 1280 x 720/ 60Hz, 1024 x 768/ 60Hz
Audio Output	1-Ch, RCA
Recording Resolution	8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF
Synchronous Playback	8-Ch
Decoding	
Compression	H.265/ H.264
Live View/ Playback	8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080p/ 960p/ 720p/ D1/ 2CIF/ CIF
Capability	1 x 4K @30, 1 x 6MP @30, 1 x 5 MP @30, 2 x 4 MP @30, 4 x 1080p @30, 8 x 720p @30

Harddisk	
SATA	2 SATA interface
Capacity	Up to 8 TB for each disk
External Interface	
Network Interface	1 RJ-45 10M/ 100M self adaptive Ethernet Interface
USB Interface	Rear Panel: 2 x USB 2.0 Front Panel: 1 x USB2.0
Alarm In	4-Ch
Alarm Out	1-Ch
General	
Power Supply	12V DC
Consumption (Without HDD)	≤ 5 W
Working Temperature	-10°C~+55°C (+14°F~+131°F)
Working Humidity	10%~90%
Dimensions (mm)	46 x 315 x 380 (1.8" x 12.4" x 15.0")
Weight (Kg) (without HDD)	≤ 2.18 Kg (4.81 lb)

*All specification may change without prior notification

