



CS 561

Fibre discs for Steel, NF metals, Metals



Applications		Properties
Steel	●	Bonding agent Resin
NF metals	●	Grain Aluminium oxide
Metals	●	Coating Close
Plastic	○	
Stainless steel	○	
Wood	○	

Advantages: For universal use - Largest selection of diameters, grit sizes and hole patterns

Available grits

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------

Diameter in mm	Bore in mm	Grit	Vmax in m/s	Max. RPM in rpm	Cat.number
100.0	16	16	80	15300.0	65708
100.0	16	24	80	15300.0	65713
100.0	16	36	80	15300.0	65718
100.0	16	40	80	15300.0	65720
100.0	16	50	80	15300.0	65725
100.0	16	60	80	15300.0	65730
100.0	16	80	80	15300.0	65735
100.0	16	100	80	15300.0	65739
100.0	16	120	80	15300.0	65743
115.0	22	16	80	13300.0	10977
115.0	22	24	80	13300.0	10978
115.0	22	30	80	13300.0	10979
115.0	22	36	80	13300.0	10980

115.0	22	40	80	13300.0	10981
115.0	22	50	80	13300.0	10982
115.0	22	60	80	13300.0	10983
115.0	22	80	80	13300.0	10984
115.0	22	100	80	13300.0	10985
115.0	22	120	80	13300.0	10986
115.0	22	150	80	13300.0	10987
115.0	22	180	80	13300.0	10988
115.0	22	220	80	13300.0	10989
115.0	22	240	80	13300.0	10990
115.0	22	320	80	13300.0	10992
115.0	22	80	80	13300.0	25472
115.0	22	16	80	13300.0	66302
115.0	22	36	80	13300.0	66308
115.0	22	50	80	13300.0	66313
115.0	22	60	80	13300.0	66318
115.0	22	100	80	13300.0	66322
115.0	22	120	80	13300.0	66327
115.0	22	40	80	13300.0	72192
115.0	22	24	80	13300.0	72298
125.0	22	16	80	12200.0	11009
125.0	22	24	80	12200.0	11010
125.0	22	30	80	12200.0	11011
125.0	22	36	80	12200.0	11012
125.0	22	40	80	12200.0	11013
125.0	22	50	80	12200.0	11014
125.0	22	60	80	12200.0	11015
125.0	22	80	80	12200.0	11016
125.0	22	100	80	12200.0	11017
125.0	22	120	80	12200.0	11018
125.0	22	150	80	12200.0	11019
125.0	22	180	80	12200.0	11020
125.0	22	220	80	12200.0	11021
125.0	22	240	80	12200.0	11022
125.0	22	320	80	12200.0	11024
125.0	22	16	80	12200.0	66354
125.0	22	24	80	12200.0	66358
125.0	22	36	80	12200.0	66364

125.0	22	40	80	12200.0	66366
125.0	22	50	80	12200.0	66371
125.0	22	60	80	12200.0	66376
125.0	22	100	80	12200.0	66379
125.0	22	120	80	12200.0	66383
125.0	22	80	80	12200.0	70439
150.0	22	24	80	10200.0	11042
150.0	22	36	80	10200.0	11044
150.0	22	40	80	10200.0	11045
150.0	22	60	80	10200.0	11047
150.0	22	80	80	10200.0	11048
150.0	22	120	80	10200.0	11050
180.0	22	16	80	8500.0	11057
180.0	22	24	80	8500.0	11058
180.0	22	36	80	8500.0	11060
180.0	22	40	80	8500.0	11061
180.0	22	50	80	8500.0	11062
180.0	22	60	80	8500.0	11063
180.0	22	80	80	8500.0	11064
180.0	22	100	80	8500.0	11065
180.0	22	120	80	8500.0	11066
180.0	22	180	80	8500.0	11068
180.0	22	240	80	8500.0	11070
180.0	22	320	80	8500.0	11072
180.0	22	16	80	8500.0	66443
180.0	22	24	80	8500.0	66451
180.0	22	36	80	8500.0	66459
180.0	22	80	80	8500.0	66465
180.0	22	100	80	8500.0	66469
180.0	22	120	80	8500.0	66472
180.0	22	40	80	8500.0	70447
180.0	22	50	80	8500.0	70448
180.0	22	60	80	8500.0	70449
235.0	22	24	80	6500.0	66497
235.0	22	36	80	6500.0	66502
235.0	22	40	80	6500.0	66504
235.0	22	60	80	6500.0	66511
235.0	22	80	80	6500.0	66514

