



SPECIFICATIONS

Product Description: **8" (20.3cm) METAL BLOWER, COM-PAX-IAL, AC**
 Part Number: **9534, 9534-15, 9534-25**
 Style: **AXIAL FAN, COMPACT**

GENERAL DESCRIPTION:

Lightweight and compact design allows for easy portability without sacrificing performance. Certified to CSA Standard C22.2 No.113.

CONSTRUCTION:

- Complete unit epoxy powder coated orange
- 15 gauge cold rolled steel housing with welded motor mount construction
- 20 gauge steel canister
- Available with 15'(4.57m) or 25'(7.62m) ducting and canister
- Enclosed wide base for greater stability
- Steel/chrome plated grill
- Carry handle made of 3-ply rubber belting
- Equipped with four rubber feet



MOTOR:

HP: 1/3 HP
 Certifications: UL Recognized, CSA Certified
 Volts: 115V AC Single Phase
 RPM: 3200 (Loaded at 120 Volts, 60 Hz)
 Current Draw: 3.6A (Loaded at 120 Volts, 60 Hz)
 Cord: 6' (1.82m) SJOW 16/3 AWG neoprene, 300V medium duty
 Plug: NEMA 5-15 125V AC



DUCTING:

- Retractable, non-collapsible design
- Single-ply, PVC coated, vinyl and polyester materials, temperature resistant up to 180°F (82.2°C)
- Yellow color with black weather-strip and integrated nylon straps
- Class 1 hard drawn spring steel wire helix that meets ASTM specs

FAN:

- Glass reinforced polypropylene (PPG) six blade fan with aluminum hub

BLOWER DIMENSIONS:

Description	Part No	Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
Blower only	9534	12" (30.4)	8" (20.3)	10" (25.4)	17 lbs (7.7)
Blower w/15' Duct Canister	9534-15	28" (71.1)	11" (27.9)	10" (25.4)	34 lbs (15.4)
Blower w 25' Duct Canister	9534-25	28" (71.1)	11" (27.9)	10" (25.4)	37 lbs (16.7)

FLOW RATES: (CFM calculated using 15' (4.57m) of 8" (20.3mc) ducting)

Free Air CFM (m ³ /hr)	One 90° Bend CFM (m ³ /hr)	Two 90° Bends CFM (m ³ /hr)
778 (1231.83)	645 (1095.86)	496 (842.71)