



## SPECIFICATIONS

Product Description: **8" (20.3cm) PLASTIC BLOWER**  
 Part Number: **9539-08**  
 Style: **AXIAL FAN 8" (20.3cm)**

### GENERAL DESCRIPTION:

This portable blower is ideally suited for light industrial or utility application. This compact blower delivers maximum airflow and is perfect for confined spaces such as manholes. Certified to CSA Standard C22.2 No.113.

### CONSTRUCTION:

- Lightweight-, corrosion-, UV-, and chemical-resistant polyethylene housing
- Durable construction design
- Super quiet
- "Safety orange"
- Bottom enclosure to protect electrical components
- Carry handle molded into blower



### MOTOR:

HP: 1/3 HP  
 Certifications: UL Recognized, CSA Certified  
 Voltage/Hz: 115V AC, 60Hz, Single Phase  
 Max RPM: 3400  
 Switch: ON/OFF switch  
 Amps: 4.8A-2.4A (50Hz) / 4.5A-2.2A (60Hz)  
 Cord: 20' (6.09m) AWG  
 Plug: NEMA 5-15P

### DUCTING: *(Optional)*

- Retractable, non-collapsible design
- Single-ply, PVC coated vinyl and polyester materials. temperature resistant up to 180°F (82.2°C)
- Yellow color with black weather strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

### BLOWER DIMENSIONS:

Length In (cm)	Width In (cm)	Height In (cm)	Weight Lb (Kg)
15" (38.1)	12½" (31.7)	18½" (46.9)	16 (7.2)

### FLOW RATES: *(CFM calculated using 15' (4.57m) of 8" (20.3cm) ducting)*

Free Air CFM (m³/hr)	One 90° Bend CFM (m³/hr)	Two 90° Bends CFM (m³/hr)
865 (1469.64)	550 (934.45)	350 (594.65)