



SPECIFICATIONS

Product Description: **16" (40.6cm) PLASTIC COM-PAX-IAL BLOWER AC**
 Part Number: **9539-16**
 Style: **AXIAL FAN 16" (40.6cm)**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow.

CONSTRUCTION:

- Polyethylene housing
- Lightweight, corrosion, UV and chemical resistant
- Super quiet, in "safety orange" housing
- Carry handle molded into blower and canister housing
- Black plastic grill

MOTOR:

HP: 1 HP
 Certification: UL Listed, CSA Certified
 Voltage/Hz: 115V/60Hz, Single Phase
 RPM: 3450
 Amps: 9A
 Switch: Built in ON/OFF Rocker
 Cord: 15' (4.57m) (UL) SJT, 14 AWG
 Plug: NEMA 5-15P

FAN:

- Polypropylene three blade fan

DUCTING: *(Optional – available in 15' and 25' lengths)*

- Retractable, non-collapsible design, Single-ply
- PVC coated vinyl and polyester materials
- Yellow color with black weather strip and integrated nylon attachment strap
- Spring steel wire helix

BLOWER DIMENSIONS:

Blower P/N	Length In. (cm)	Width In. (cm)	Height In. (cm)	Weight Lbs. (Kg)
9539-16	20" (50.8 cm)	21" (53.3 cm)	22" (55.9 cm)	40 lbs (18.1 kg)

FLOW RATES: *(CFM calculated using 15' (4.57m) of 16" (40.6cm) ducting)*

Free Air CFM (m ³ /hr)	One 90° Bend CFM (m ³ /hr)	Two 90° Bends CFM (m ³ /hr)
3200 (5436.83)	2350 (3992.67)	2250 (3822.77)

