

## Data sheet

### Laboratory Incubator CLW 15



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 15                                               |
| working capacity [l]     | 15                                               |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                             |
|---------------------------------------|---------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C   |
| temperature resolution every ... [°C] | 0,1                                         |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |     |
|----------|-----|
| width A  | 510 |
| height B | 550 |
| depth C  | 440 |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 320 |
| height E | 230 |
| depth F  | 200 |



|                                     |       |
|-------------------------------------|-------|
| shelves (standard / max)            | 1 / 2 |
| max shelf workload [kg] /5/         | 10    |
| - reinforced shelf version (PW) /3/ | -     |
| max unit workload [kg]              | 20    |
| - reinforced unit version (W) /4/   | -     |
| weight [kg]                         | 27    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 300               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 32



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 32                                               |
| working capacity [l]     | 32                                               |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                             |
|---------------------------------------|---------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C   |
| temperature resolution every ... [°C] | 0,1                                         |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |     |
|----------|-----|
| width A  | 590 |
| height B | 630 |
| depth C  | 500 |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 400 |
| height E | 320 |
| depth F  | 250 |



|                                     |       |
|-------------------------------------|-------|
| shelves (standard / max)            | 1 / 3 |
| max shelf workload [kg] /5/         | 10    |
| - reinforced shelf version (PW) /3/ | -     |
| max unit workload [kg]              | 30    |
| - reinforced unit version (W) /4/   | -     |
| weight [kg]                         | 35    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 300               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 53



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 56                                               |
| working capacity [l]     | 56                                               |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |     |
|----------|-----|
| width A  | 590 |
| height B | 700 |
| depth C  | 600 |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 400 |
| height E | 390 |
| depth F  | 360 |



|                                     |       |
|-------------------------------------|-------|
| shelves (standard / max)            | 2 / 5 |
| max shelf workload [kg] /5/         | 25    |
| - reinforced shelf version (PW) /3/ | 50    |
| max unit workload [kg]              | 40    |
| - reinforced unit version (W) /4/   | 80    |
| weight [kg]                         | 50    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 400               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**





## Data sheet

### Laboratory Incubator CLW 115



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 112                                              |
| working capacity [l]     | 112                                              |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |     |
|----------|-----|
| width A  | 650 |
| height B | 850 |
| depth C  | 700 |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 460 |
| height E | 540 |
| depth F  | 450 |



|                                     |       |
|-------------------------------------|-------|
| shelves (standard / max)            | 2 / 7 |
| max shelf workload [kg] /5/         | 25    |
| - reinforced shelf version (PW) /3/ | 50    |
| max unit workload [kg]              | 60    |
| - reinforced unit version (W) /4/   | 120   |
| weight [kg]                         | 65    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 400               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 180



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 180                                              |
| working capacity [l]     | 180                                              |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |      |
|----------|------|
| width A  | 650  |
| height B | 1030 |
| depth C  | 760  |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 470 |
| height E | 720 |
| depth F  | 560 |



|                                     |       |
|-------------------------------------|-------|
| shelves (standard / max)            | 3 / 9 |
| max shelf workload [kg] /5/         | 25    |
| - reinforced shelf version (PW) /3/ | 50    |
| max unit workload [kg]              | 75    |
| - reinforced unit version (W) /4/   | 120   |
| weight [kg]                         | 94    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 850               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 240



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 245                                              |
| working capacity [l]     | 245                                              |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing

|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |




**overall dims [mm] /2/**

|          |      |
|----------|------|
| width A  | 810  |
| height B | 1200 |
| depth C  | 760  |

**internal dims [mm]**

|          |     |
|----------|-----|
| width D  | 600 |
| height E | 800 |
| depth F  | 510 |



|                                     |        |
|-------------------------------------|--------|
| shelves (standard / max)            | 3 / 10 |
| max shelf workload [kg] /5/         | 25     |
| - reinforced shelf version (PW) /3/ | 100    |
| max unit workload [kg]              | 90     |
| - reinforced unit version (W) /4/   | 300    |
| weight [kg]                         | 126    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 800               |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 400



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 424                                              |
| working capacity [l]     | 424                                              |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |      |
|----------|------|
| width A  | 1010 |
| height B | 1430 |
| depth C  | 750  |

**internal dims [mm]**

|          |      |
|----------|------|
| width D  | 800  |
| height E | 1040 |
| depth F  | 510  |



|                                     |        |
|-------------------------------------|--------|
| shelves (standard / max)            | 3 / 14 |
| max shelf workload [kg] /5/         | 25     |
| - reinforced shelf version (PW) /3/ | 100    |
| max unit workload [kg]              | 120    |
| - reinforced unit version (W) /4/   | 300    |
| weight [kg]                         | 174    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 1200              |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**



## Data sheet

### Laboratory Incubator CLW 750



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 749                                              |
| working capacity [l]     | 749                                              |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |      |
|----------|------|
| width A  | 1260 |
| height B | 1600 |
| depth C  | 850  |

**internal dims [mm]**

|          |      |
|----------|------|
| width D  | 1040 |
| height E | 1200 |
| depth F  | 600  |



|                                     |        |
|-------------------------------------|--------|
| shelves (standard / max)            | 5 / 16 |
| max shelf workload [kg] /5/         | -      |
| - reinforced shelf version (PW) /3/ | 100    |
| max unit workload [kg]              | 140    |
| - reinforced unit version (W) /4/   | 300    |
| weight [kg]                         | 260    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 1800              |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available


1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**





## Data sheet

### Laboratory Incubator CLW 1000



The photo above is for reference only, may show additional options not included in standard equipment.  
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

#### TECHNICAL DATA

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| air convection           | forced                                           |
| chamber capacity [l] /1/ | 1005                                             |
| working capacity [l]     | 1005                                             |
| controller               | microprocessor with external LCD graphic display |

#### TEMPERATURE

|                                       |                                                                 |
|---------------------------------------|-----------------------------------------------------------------|
| temperature range [°C]                | +5°C above ambient temperature ... +100°C                       |
| temperature resolution every ... [°C] | 0,1                                                             |
| over temperature protection           | class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+ |

#### CHAMBER

|           |                                            |
|-----------|--------------------------------------------|
| door type | double / door with viewing window (option) |
|-----------|--------------------------------------------|

#### interior

|        |                                          |
|--------|------------------------------------------|
| STD    | acid-proof stainless steel to DIN 1.4301 |
| INOX/G | acid-proof stainless steel to DIN 1.4301 |

#### housing


|        |                              |
|--------|------------------------------|
| STD    | powder coated sheet          |
| INOX/G | stainless steel linen finish |

**overall dims [mm] /2/**

|          |      |
|----------|------|
| width A  | 1260 |
| height B | 2000 |
| depth C  | 850  |

**internal dims [mm]**

|          |      |
|----------|------|
| width D  | 1040 |
| height E | 1610 |
| depth F  | 600  |



|                                     |        |
|-------------------------------------|--------|
| shelves (standard / max)            | 6 / 22 |
| max shelf workload [kg] /5/         | -      |
| - reinforced shelf version (PW) /3/ | 100    |
| max unit workload [kg]              | -      |
| - reinforced unit version (W) /4/   | 300    |
| weight [kg]                         | 330    |

**ELECTRICAL PARAMETERS**

|                   |                   |
|-------------------|-------------------|
| voltage*          | 230V 50Hz         |
| nominal power [W] | 1800              |
| warranty          | 24 months         |
| manufacturer      | POL-EKO-APARATURA |

all the above technical data refer to standard units (without optional accessories)

\* - 230V 60Hz, 115V 60Hz also available

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

**OPTIONS AND ACCESSORIES**

