

F-CY-JZ flexible, Cu-screened, EMC-preferred type, meter marking**A**

Part no.	No. cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
16344	2 x 0,75	6,1	40,0	59,0	19
16345	3 G 0,75	6,3	52,0	66,0	19
16346	4 G 0,75	6,8	60,0	77,0	19
16347	5 G 0,75	7,4	71,0	93,0	19
16348	6 G 0,75	8,2	80,0	113,0	19
16349	7 G 0,75	8,2	91,0	130,0	19
16350	8 G 0,75	9,0	110,0	145,0	19
16351	10 G 0,75	10,3	137,0	180,0	19
16353	12 G 0,75	10,5	142,0	202,0	19
16354	14 G 0,75	11,3	180,0	225,0	19
16355	16 G 0,75	11,9	200,0	275,0	19
16356	18 G 0,75	12,7	212,0	292,0	19
16447	19 G 0,75	12,7	230,0	308,0	19
16357	20 G 0,75	13,6	238,0	320,0	19
16358	21 G 0,75	13,6	246,0	378,0	19
16359	24 G 0,75	14,9	270,0	435,0	19
16360	25 G 0,75	15,0	281,0	415,0	19
16361	27 G 0,75	15,0	304,0	435,0	19
16362	30 G 0,75	16,0	320,0	450,0	19
16363	32 G 0,75	16,7	342,0	484,0	19
16166	34 G 0,75	17,2	345,0	502,0	19
16364	36 G 0,75	17,4	350,0	535,0	19
16448	37 G 0,75	17,4	361,0	592,0	19
16365	40 G 0,75	18,1	369,0	610,0	19
16491	41 G 0,75	18,2	400,0	622,0	19
16366	50 G 0,75	20,3	461,0	777,0	19
16367	61 G 0,75	22,0	540,0	900,0	19
16368	80 G 0,75	25,3	711,0	1210,0	19
16369	100 G 0,75	28,0	900,0	1445,0	19
16370	2 x 1	6,4	50,0	65,0	18
16371	3 G 1	6,7	60,0	80,0	18
16372	4 G 1	7,2	71,0	98,0	18
16373	5 G 1	8,0	88,0	127,0	18
16374	6 G 1	8,7	97,0	144,0	18
16375	7 G 1	8,7	111,0	158,0	18
16376	8 G 1	9,6	127,0	197,0	18
16377	10 G 1	11,2	150,0	232,0	18
16378	12 G 1	11,4	184,0	260,0	18
16379	14 G 1	12,0	196,0	302,0	18
16380	16 G 1	12,8	209,0	346,0	18
16381	18 G 1	13,6	260,0	380,0	18
16352	19 G 1	13,6	280,0	412,0	18
16382	20 G 1	14,3	317,0	440,0	18
16383	24 G 1	16,0	320,0	493,0	18
16384	25 G 1	16,2	349,0	534,0	18
16439	27 G 1	16,4	400,0	562,0	18
16385	28 G 1	17,0	408,0	595,0	18
16386	30 G 1	17,2	441,0	616,0	18
16387	34 G 1	18,5	486,0	741,0	18
16446	37 G 1	18,6	519,0	790,0	18
16388	40 G 1	19,4	510,0	835,0	18
16492	41 G 1	19,5	531,0	843,0	18
16389	50 G 1	22,0	625,0	1025,0	18
16390	61 G 1	23,5	702,0	1205,0	18
16391	80 G 1	26,9	920,0	1445,0	18
16392	100 G 1	30,2	1120,0	1613,0	18

Part no.	No. cores x cross-sec. mm²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
16393	2 x 1,5	7,0	63,0	88,0	16
16394	3 G 1,5	7,4	80,0	100,0	16
16395	4 G 1,5	8,1	97,0	126,0	16
16396	5 G 1,5	9,0	119,0	160,0	16
16397	7 G 1,5	9,8	147,0	208,0	16
16398	8 G 1,5	10,8	170,0	244,0	16
16399	10 G 1,5	12,6	193,0	315,0	16
16400	12 G 1,5	12,8	267,0	338,0	16
16401	14 G 1,5	13,5	283,0	383,0	16
16402	16 G 1,5	14,6	315,0	424,0	16
16403	18 G 1,5	15,6	374,0	479,0	16
16449	19 G 1,5	15,6	386,0	508,0	16
16404	20 G 1,5	16,6	396,0	545,0	16
16405	21 G 1,5	16,6	425,0	560,0	16
16406	24 G 1,5	18,1	458,0	690,0	16
16407	25 G 1,5	18,4	526,0	705,0	16
16450	27 G 1,5	18,5	531,0	774,0	16
16408	28 G 1,5	19,6	541,0	810,0	16
16409	30 G 1,5	19,6	555,0	830,0	16
16410	35 G 1,5	21,4	645,0	890,0	16
16451	37 G 1,5	21,4	674,0	945,0	16
16411	40 G 1,5	22,0	725,0	1060,0	16
16493	41 G 1,5	22,2	801,0	1071,0	16
16412	50 G 1,5	25,0	885,0	1290,0	16
16413	61 G 1,5	26,8	1100,0	1705,0	16
16414	80 G 1,5	30,8	1324,0	2010,0	16
16415	100 G 1,5	34,1	1641,0	2505,0	16
16416	2 x 2,5	8,4	96,0	130,0	14
16417	3 G 2,5	8,8	144,0	167,0	14
16418	4 G 2,5	9,8	148,0	195,0	14
16419	5 G 2,5	10,8	181,0	223,0	14
16420	7 G 2,5	11,9	255,0	344,0	14
16421	10 G 2,5	15,5	340,0	460,0	14
16438	12 G 2,5	15,8	441,0	570,0	14
16452	18 G 2,5	19,0	570,0	681,0	14
16422	2 x 4	10,0	120,0	185,0	12
16423	3 G 4	10,6	174,0	240,0	12
16424	4 G 4	11,6	230,0	310,0	12
16425	5 G 4	12,8	273,0	385,0	12
16426	7 G 4	14,2	316,0	500,0	12
16427	2 x 6	11,7	173,0	268,0	10
16428	3 G 6	12,5	240,0	330,0	10
16429	4 G 6	13,8	305,0	415,0	10
16430	5 G 6	15,4	439,0	509,0	10
16431	7 G 6	17,0	505,0	672,0	10
16432	2 x 10	14,5	255,0	425,0	8
16433	3 G 10	15,6	350,0	500,0	8
16434	4 G 10	17,2	535,0	783,0	8
16435	5 G 10	19,1	592,0	856,0	8
16436	7 G 10	21,2	810,0	1305,0	8
16440	4 G 16	20,3	740,0	880,0	6
16437	5 G 16	22,2	895,0	1295,0	6
16441	4 G 25	24,7	1140,0	1570,0	4
16442	5 G 25	27,4	1380,0	1965,0	4
16443	4 G 35	28,4	1576,0	2070,0	2
16444	5 G 35	31,6	1930,0	2690,0	2
16445	4 G 50	34,2	2155,0	3015,0	1

Dimensions and specifications may be changed without prior notice. (RA01)



Suitable accessories can be found in Chapter X.

- Cable Gland - HELUTOP® HT-MS-EP4