

PrevaLED COIN 111 G2

LED modules with integrated optics and heat sink



Areas of application

- Spot and track light luminaires
- Chain stores, retail shops
- Shopping centers
- Exhibition halls
- Museums

Product family benefits

- High luminous flux
- Easy installation thanks to wiring with only two cables
- Best luminous efficacy in combination with OPTOTRONIC constant current ECG
- Easy and quick design-in for luminaire manufacturers
- 5 year guarantee

Product family features

- Fits into most existing traditional R111 luminaires
- Available with 24° or 40° beam angle
- Versions with different luminous flux and different color temperatures available
- Cable length: 500 mm, suitable for 1.6 mm²/AWG 22 wires
- Color rendering index R_a : typ. 92 or typ. 83 (depending on version)
- Module efficacy: up to 115 lm/W
- High color consistency: 4 SDCM
- Maximum temperature at t_c : 85 °C (according to IEC 62717)
- Lifetime (L70/B50): 50,000 h (temperature at $T_c = 75$ °C)

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

References / Links

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit

- ▶ www.osram.com/system-guarantee
-

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.