



CorePro LEDcapsule LV

CorePro LEDcapsuleLV 2-20W 830 G4

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.


Product data

General Information		Lamp Current (Nom)	
Cap-Base	G4 [G4]		290 mA
Nominal Lifetime (Nom)	15000 h	Wattage Equivalent	20 W
Switching Cycle	50000X	Starting Time (Nom)	0.5 s
Technical Type	2-20W	Warm Up Time to 60% Light (Nom)	0.5 s
		Power Factor (Nom)	0.5
		Voltage (Nom)	12 V
Light Technical		Controls and Dimming	
Color Code	830 [CCT of 3000K]	Dimmable	No
Luminous Flux (Nom)	200 lm		
Luminous Flux (Rated) (Nom)	200 lm	Approval and Application	
Color Designation	White (WH)	Energy Efficiency Label (EEL)	A++
Correlated Color Temperature (Nom)	3000 K	Energy Consumption kWh/1000 h	3 kWh
Luminous Efficacy (rated) (Nom)	100 lm/W		
Color Consistency	<6	Product Data	
Color Rendering Index (Nom)	80	Full product code	871869641916800
LLMF At End Of Nominal Lifetime (Nom)	70 %	Order product name	CorePro LEDcapsuleLV 2-20W 830 G4
Operating and Electrical		EAN/UPC - Product	8718696419168
Input Frequency	50 to 60 Hz	Order code	929001131802
Power (Rated) (Nom)	2 W	Numerator - Quantity Per Pack	1

CorePro LEDcapsule LV

Numerator - Packs per outer box	12
Material Nr. (12NC)	929001131802
Net Weight (Piece)	0.008 kg


Dimensional drawing




LED 2-20W 830 G4

Product	D	C
CorePro LEDcapsuleLV 2-20W 830 G4	14.3 mm	45 mm

Photometric data



2-20 W G4 /830



G4 /830

