



GreenSpace Downlight G4

DN291B 1xDLED-4000 PSU WH

GreenSpace Gen4 is the new LED downlight with high efficacy (95~ 100lm/W) delivering substantial energy saving. It offers diverse configurations within 600~2,000lm. GreenSpace Gen4 could apply to shopping mall, retail store and office application with different variants . The lifetime is 50,000 hours (L70 @ 25C)

Product data

General Information	
Number of light sources	1 pc
Light source color	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Optic type	Beam angle 60 to 120°
Optical cover/lens type	Transparent bowl with white cover
Luminaire light beam spread	90°
Control interface	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
CE mark	CE mark
ENEC mark	-
UL mark	-
Constant light output	Yes
Spare parts available	No
Number of products on MCB of 16 A type B	30
Light source engine type	LED

Operating and Electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9
Power Factor (Nom)	0.9

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Matte
Color	White

Approval and Application	
Ingress protection code	IP20 [Finger-protected]

GreenSpace Downlight G4

Mech. impact protection code	IK02 [0.2 J standard]
Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	1000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	89 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial input power	11.6 W
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Median useful life L70B50	50000 h

Application Conditions

Ambient temperature range	-20 to +40 °C
---------------------------	---------------



Product Data

Full product code	911401565021
Order product name	DN291B 1xDLED-4000 PSU WH
Order code	911401565021
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401565021
Net Weight (Piece)	0.380 kg





Dimensional drawing

Dimension 灯具尺寸	A (mm)	B (mm)
DN290B 1xDLED / ALU	95 / 99	∅ 122
DN291B 1xDLED / ALU	105 / 109	∅ 167
DN292B 1xDLED / ALU	114 / 118	∅ 218
DN293B 1xDLED / ALU	114 / 118	∅ 218



Dimension 灯具尺寸	A (mm)	B (mm)
DN290B 1xDLED / ALU	95 / 99	∅ 122
DN291B 1xDLED / ALU	105 / 109	∅ 167
DN292B 1xDLED / ALU	114 / 118	∅ 218
DN293B 1xDLED / ALU	114 / 118	∅ 218



GreenSpace Downlight G4 DN290B-293B

GreenSpace Downlight G4 DN290B-293B

