



SmartBright Suspension

RC095V LED30S/865 PSU W12L120 Grey

Power supply unit - Symmetrical - Polystyrene bowl/cover prismatic - 120°

Linear suspension solution with affordable price

Product data

Number of products on MCB of 16 A type B	210
EU RoHS compliant	Yes
Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	6.7 A
Inrush time	0.0072 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polystyrene
Optical cover/lens material	Polystyrene
Fixation material	Stainless steel

SmartBright Suspension

Frosted
600 mm
120 mm
65 mm
Gray
IP20 [Finger-protected]
IK03 [0.3 J]
IKO3 [0.3 J]
IK03 [0.3 J]
IK03 [0.3 J] 1500 lm
1500 lm
1500 lm +/-10%
1500 lm +/-10% 88 lm/W
1500 lm +/-10% 88 lm/W 6500 K
1500 lm +/-10% 88 lm/W 6500 K >80

Over Time Performance (IEC Compliant)		
Median useful life L70B50	25000 h	
Application Conditions		
Ambient temperature range	-10 to +35 °C	
Maximum dim level	Not applicable	
Suitable for random switching	No	
Product Data		
Full product code	692382862895600	
Order product name	RC095V LED30S/865 PSU W12L120 Grey	
EAN/UPC - Product	6923828628956	
Order code	911401723482	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	1	
Material Nr. (12NC)	911401723482	
Net Weight (Piece)	1.919 kg	



Dimensional drawing



SmartBright Troffer RC098V



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.