

6.6A/30T3.5/64322/EXL/DL



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield Lighting

Product datasheet

Technical data

General product information

Product Number	58850
Product Name	66A30T3564322EXLDL 12/CS 1/SKU
Ordering Abbreviation	6.6A/30T3.5/64322/EXL/DL
Brand Name	OSRAM
General Description	30 WATT, TUNGSTEN HALOGEN, CURRENT CONTROLLED, SINGLED-END, BI-PIN,AIRFIELD
Application	Airfield/Airport

Electrical data

Nominal Wattage	30 W
Current (A)	6.6 A
Type of Current	AC

Light technical data

Luminous Flux	400 lm
Light Center Length - LCL (in)	1 in
Light Center Length - LCL (mm)	25.4 mm
Color Rendering Index	100
Average Rated Life	1500 h

Physical attributes

Base	GY9.5 BIPIN
Bulb Shape	T4
Maximum Overall Length (in)	1.752 in
Maximum Overall Length (mm)	44.5 mm
Diameter d (in)	0.453 in
Diameter d (mm)	11.50 mm
Filament	C-8
Filament Dimensions Length (in)	0.1380 in
Filament Dimensions Length (mm)	3.5 mm
Filament Dimensions Width (in)	0.047 in
Filament Dimensions Width (mm)	1.2 mm

Additional product data

Operating Position	Any
Class	C (gas)

Product datasheet

Lamp Type	SINGLE ENDED
------------------	--------------

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58850	4008321100146	Folding box (SKU)	1	1.7 in x 1.7 in x 4.4 in	0.1 lb
58850	4008321100153	Shipping box (Case)	12	7.1 in x 5 in x 5.5 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.