


GATE VALVE CAST IRON JIS 5K



Flanged ends JIS B2211
Design Standards JIS F7363



Working Pressure.....6 kgf / cm²
Hydrostatic shell test.....10.6 kgf / cm²
Hydrostatic seat test.....7.7 kgf / cm²

Materials

Parts	JIS materials
Body	Cast Iron
Bonnet	Cast Iron
Stem	Brass
Disc	Cast Iron Welding Copper
Seat ring	PTFE
Gland	Ductile Iron
Gland packing	PTFE
Gasket	Asbestos - Free
Indicator	Aluminum
Hand Wheel	Cast Iron


Dimensions

DN	mm	40	50	65	80	100	125	150
	inch	1-1/2	2	2-1/2	3	4	5	6
L		140	180	190	200	230	250	270
H		220	250	285	335	391	449	495
D		140	140	160	160	180	225	225

ANGLE VALVE CAST IRON JIS 5K



Flanged ends JIS B2211
Design Standards JIS F7306



Working Pressure.....6 kgf / cm²
Hydrostatic shell test.....10.6 kgf / cm²
Hydrostatic seat test.....7.7 kgf / cm²

Materials

Parts	JIS materials
Body	Cast Iron
Bonnet	Cast Iron
Stem	Brass
Disc	Cast Brass
Disc Seat	Cast Brass
Gland	Ductile Iron
Gland Packing	PTFE
Hand Wheel	Cast Iron
Gasket	Asbestos - Free

Dimensions

DN	mm	40	50	65	80	100	125	150
	inch	1-1/2	2	2-1/2	3	4	5	6
L		85	100	115	130	150	170	190
H		199	219	233	251	279	308	358
D		140	160	180	200	220	250	300