


## GLOBE VALVE CAST IRON JIS 5K

**ONDA**  
INDUSTRIAL VALVE



Flanged ends	JIS B2211
Design Standards	JIS F7353



Working Pressure.....6 kgf / cm<sup>2</sup>  
Hydrostatic shell test.....10.6 kgf / cm<sup>2</sup>  
Hydrostatic seat test.....7.7 kgf / cm<sup>2</sup>

### Materials


Parts	JIS materials
Body	Cast Iron
Bonnet	Cast Iron
Stem	Brass
Disc	Cast Brass
Disc Seat	Cast Brass
Gland	Ductile Iron
Gland Packing	PTFE
Hand Wheel	Cast Iron
Gasket	Asbestos - Free

### Dimensions

Valve size	mm	40	50	65	80	100	125	150
	inch	1-1/2	2	2-1/2	3	4	5	6
L		160	210	250	280	340	410	480
H		225	253	273	299	332	374	432
D		140	160	180	200	220	250	300

## GLOBE VALVE DUCTILE IRON JIS 10K

**ONDA**  
INDUSTRIAL VALVE



120°C Static Water.....1.37 MPa  
220°C Steam, air, gas, oil .....0.98 MPa

### Materials

Parts	JIS materials
Body	FCD-S
Bonnet	FCD-S
Stem	SUS 420J2
Disc	SUS 403
Body Seat Ring	SUS 403 (2-1/2" & 3" : SCS 1)
Gland	SUS 403 (1/4" - 3/4" : SUS 420J2)
Gland Packing	Asbestos - Free
Packing Nut	FCD - S
Handwheel	FCD 450-10 (2-1/2" & 3" : FCD 400-15)
Wheel Nut	SS400
Gasket	Asbestos - Free
Bonnet Ring	FCD-S
Name Plate	R1050P

### Dimensions

Valve size	15	20	25	32	40	50
	1/2	3/4	1	1-1/4	1-1/2	2
L	65	80	90	105	120	140
H	122	125	146	160	180	198
D	70	80	90	100	115	135