



Essential SmartBright G3 LED Floodlight

BVP150 LED25/NW 220-240V 30W SWB CE

The Essential SmartBright G3 LED floodlight comes with a compact and sturdy design. Its light weight with robust die-cast aluminum housing and corrosion-proof coating, suitable for general outdoor application. Higher efficacy than last generation, achieves more energy savings.

Product data

General Information	
Light source color	840 neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Glass bowl/cover
Luminaire light beam spread	110°
Control interface	-
Connection	Flying leads/wires
Cable	Cable 0.3 m without plug
Protection class IEC	Safety class I
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
Optic type outdoor	Symmetrical wide beam
Constant light output	No
Number of products on MCB of 16 A type B	71
Light source engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not serviceable

Light Technical	
Standard tilt angle posttop	-
Standard tilt angle side entry	-
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	1 A
Inrush time	0.0111 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat

Essential SmartBright G3 LED Floodlight

Optical cover/lens finish	Textured
Overall length	170 mm
Overall width	130 mm
Overall height	29 mm
Color	Black

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Surge Protection (Common/Differential)	Surge protection level until 2 kV

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	2550 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	85 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	SDCM<7

Initial input power	30 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	871016333018199
Order product name	BVP150 LED25/NW 220-240V 30W SWB CE
EAN/UPC - Product	8710163330181
Order code	911401732392
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16
Material Nr. (12NC)	911401732392
Net Weight (Piece)	0.500 kg



Dimensional drawing



BVP150/161 Essential Smartbright LED

