



Regulated DC Power Supply APS 3005 (0- 30V / 0- 5A) Single Channel



Specifications

Voltage Range : 0- 30 V (Single Channel) , Volt Meter : 4 digit
Voltage Resolution : 10 mV

Current Range : 0- 5 A , Ampere meter : 4 digit
Current resolution : 1 mA

AC input : 220V/230V , 50/60 Hz

Performance : Low Noise, cooling fan controlled by heatsink temperature

Operation : Compact size, light weight
: Constat voltage /
: constant current operation
: Output On / Off Control
: Digital Panel control
: 4 pairs of panel setup save / recall
: Coarse and fine voltage / current control
: Beep output
: Button lock function

Protection : Overload protection
: Reverse polarity protection

Load regulation

Voltage : $\leq 0.01\% + 2 \text{ mV}$
Current : $\leq 0.1\% + 10 \text{ mA}$

Line regulation

Voltage : $\leq 0.01\% + 3 \text{ mV}$
Current : $\leq 0.1\% + 3 \text{ mA}$

Ripple (20-20 M)

Voltage : $\leq 2 \text{ mV rms}$
Current : $\leq 3 \text{ mA rms}$

Temp Coefficient

Voltage : $\leq 150 \text{ ppm}$
Current : $\leq 150 \text{ ppm}$

Read back resolution

Voltage : 10 nV
Current : 1 mA

Fuse : T3A / 250V

Weight : 5 Kg

Size : 33 W x 25 H x 21 D (cm)

Accessories included : User manual and Power cord

Made in China